

REPORT NUMBER: 208-MGA-2004-009

**VEHICLE SAFETY COMPLIANCE TESTING
FOR
FMVSS 208, OCCUPANT CRASH PROTECTION
FMVSS 212, WINDSHIELD MOUNTING
FMVSS 219, WINDSHIELD INTRUSION (PARTIAL)
FMVSS 301, FUEL SYSTEM INTEGRITY**

**Mitsubishi Motors North America, Inc.
2004 Mitsubishi Galant 4 Door
NHTSA No.: C45603**

**PREPARED BY:
MGA RESEARCH CORPORATION
5000 WARREN ROAD
BURLINGTON, WI 53105**



Test Dates: June 21 – July 23, 2004

Final Report Date: August 3, 2004

FINAL REPORT

**PREPARED FOR:
U.S. DEPARTMENT OF TRANSPORTATION
NATIONAL HIGHWAY TRAFFIC SAFETY ADMINISTRATION
OFFICE OF ENFORCEMENT
OFFICE OF VEHICLE SAFETY COMPLIANCE
MAIL CODE: NVS-220
400 SEVENTH STREET, SW, ROOM 6115
WASHINGTON, D.C. 20590**

This final test report was prepared for the U.S. Department of Transportation, National Highway Traffic Safety Administration, in response to Contract Number DTNH22-03-D-11002.

This publication is distributed by the U.S. Department of Transportation, National Highway Traffic Safety Administration, in the interest of information exchange. The opinions, findings and conclusions expressed in this publication are those of the author(s) and not necessarily those of the Department of Transportation or the National Highway Traffic Safety Administration. The United States Government assumes no liability for its contents or use thereof. If trade or manufacturers' names or products are mentioned it is only because they are considered essential to the object of the publication and should not be construed as an endorsement. The United States Government does not endorse products or manufacturers.

Prepared  Date: August 3, 2004
Jeff Lewandowski, Project Engineer

Reviewed by:  Date: August 3, 2004
David Winkelbauer, Facility Director

FINAL REPORT ACCEPTED BY OVSC:

Accepted By: _____

Acceptance Date: _____

Technical Report Documentation Page

1. Report No. 208-MGA-2004-009	2. Government Accession No.	3. Recipient's Catalog No.	
4. Title and Subtitle Final Report of FMVSS 208 Compliance Testing of a 2004 Mitsubishi Galant 4 Door NHTSA No.: C45603		5. Report Date August 25, 2004	
		6. Performing Organization Code MGA	
7. Author(s) Jeff Lewandowski, Project Engineer		8. Performing Organization Report No. 208-MGA-2004-009	
9. Performing Organization Name and Address MGA Research Corporation 5000 Warren Road Burlington, WI 53105		10. Work Unit No.	
		11. Contract or Grant No. DTNH22-03-D-11002	
12. Sponsoring Agency Name and Address U.S. Department of Transportation National Highway Traffic Safety Administration Office of Enforcement Office of Vehicle Safety Compliance 400 Seventh St., S.W., Room 6115, NVS-220 Washington, D.C. 20590		13. Type of Report and Period Covered 6/21/04 – 8/25/04	
		14. Sponsoring Agency Code NVS-220	
15. Supplementary Notes			
16. Abstract Compliance tests were conducted on the subject 2004 Mitsubishi Galant 4 Door in accordance with the specifications of the Office of Vehicle Safety Compliance Test Procedure No. TP208-12 for the determination of FMVSS 208 compliance. Test failures identified were as follows: TEST FAILURES: None			
17. Key Words Frontal Impact 40 kmph Vehicle Safety Compliance Testing FMVSS 208, "Occupant Crash Protection" FMVSS 212, "Windshield Mounting" FMVSS 219, (partial), "Windshield Zone Intrusion" FMVSS 301, "Fuel System Integrity"		18. Distribution Statement Copies of this report are available from the following: NHTSA Technical Information Services (TIS), Mail Code: NPO-230 400 Seventh Street, S.W., Room 5108 Washington, D.C. 20590 Tel. No.: (202) 366-4946	
19. Security Classif. (of this report) Unclassified	20. Security Classif. (of this page) Unclassified	21. No. of Pages 388	22. Price

Form DOT F1700.7 (8-72)

TABLE OF CONTENTS

<u>Section</u>	<u>Page No</u>
1 Purpose of Compliance Test	1
2 Tests Performed	2
3 Injury Result Summary	4
4 Discussion of Test (if applicable)	7
5 Test Data Sheets	8
 <u>Data Sheet</u>	
1 COTR Vehicle Work Order	9
2 Report of Vehicle Condition	13
3 Certification Label and Tire Placard Information	15
4 Rear Outboard Seating Position Seat Belts	16
5 Air Bag Labels	17
6 Readiness Indicator	30
7 Passenger Air Bag Manual Cut-Off Device	31
8 Lap Belt Lockability	35
9 Seat Belt Warning System	43
10 Belt Contact Force	45
11 Latch Plate Access	51
12 Seat Belt Retraction	55
13 Seat Belt Guides and Hardware	59
14 Marking of Reference Points for Various Test Positions & Points	65
15 Summary of Suppression Test Using 12-Month CRABI Dummy	71
16 Summary of Suppression Test Using Newborn Infant Dummy	78
17 Summary of Suppression Test Using 3-YO Dummy and Booster Seats	79
18 Summary of Suppression Test Using 3-YO Dummy and Fwd Facing Restraints	81
19 Summary of Suppression Test Using an Unbelted 3-YO Dummy	84
25 Summary of Low Risk Deployment Using an Unbelted 6-Year-Old Dummy Position 1	85
26 Summary of Low Risk Deployment Using an Unbelted 6-Year-Old Dummy Position 2	86
27 Summary of Low Risk Deployment Using an Unbelted 5 th % Dummy Position 1	87
28 Summary of Low Risk Deployment Using an Unbelted 5 th % Dummy Position 2	88
30 Vehicle Weight, Fuel Tank, and Attitude Data	89

<u>Data Sheet</u>		<u>Page No</u>
31	Vehicle Accelerometer Locations and Measurements	93
32	Photographic Targets	96
33	Camera Locations	102
34	Dummy Positioning	104
35	Dummy Measurements	117
36	Crash Test	120
38	Accident Investigation Measurements	122
39	Windshield Mounting (FMVSS 212)	124
40	Windshield Zone Intrusion (FMVSS 219)	126
41	Fuel System Integrity (FMVSS 301)	128
 <u>Appendix</u>		
A	Crash Test Data	A-1
B	Low Risk Test Data	B-1
C	Crash Test Photographs	C-1
D	Low Risk Photographs	D-1
E	Suppression Photographs	E-1
F	Instrumentation Calibration	F-1
G	Notice of Test Failure (If Applicable)	G-1

SECTION 1
PURPOSE OF COMPLIANCE TEST

The tests performed are part of a program conducted for the National Highway Traffic Safety Administration (NHTSA) by MGA Research Corporation (MGA) under Contract No. DTNH22-03-D-11002. The purpose of this test was to determine whether the subject vehicle, a 2004 Mitsubishi Galant 4 Door Sedan, NHTSA No. C45603, meets certain performance requirements of FMVSS 208, "Occupant Crash Protection"; FMVSS 212, "Windshield Mounting"; FMVSS 219, "Windshield Zone Intrusion"; and FMVSS 301, "Fuel System Integrity". The compliance test was conducted in accordance with OVSC Laboratory Test Procedure No. TP208-12 dated January 14, 2003.

SECTION 2 TESTS PERFORMED

Test Vehicle: 2004 Mitsubishi Galant 4 Door
Test Program: FMVSS 208 Compliance

NHTSA No.: C45603
Test Dates: 3/18 - 7/23/04

The following checked items indicate the tests that were performed:

- | | | |
|-------------------------------------|-----|---|
| <input checked="" type="checkbox"/> | 1. | Rear outboard seating position seat belts (S4.1.1.2(b) & (S4.2.4) |
| <input checked="" type="checkbox"/> | 2. | Air bag labels (S4.5.1) |
| <input checked="" type="checkbox"/> | 3. | Readiness indicator (S4.5.2) |
| <input checked="" type="checkbox"/> | 4. | Passenger air bag manual cut-off device (S4.5.4) |
| <input checked="" type="checkbox"/> | 5. | Lap belt lockability (S7.1.1.5) |
| <input checked="" type="checkbox"/> | 6. | Seat belt warning system (S7.3) |
| <input checked="" type="checkbox"/> | 7. | Seat belt contact force (S7.4.4) |
| <input checked="" type="checkbox"/> | 8. | Seat belt latch plate access (S7.4.4) |
| <input checked="" type="checkbox"/> | 9. | Seat belt retraction (S7.4.5) |
| <input checked="" type="checkbox"/> | 10. | Seat belt guides and hardware (S7.4.6) |
| <input checked="" type="checkbox"/> | 11. | Suppression tests with 12-month-old CRABI dummy (Part 572, Subpart R) |
| <input checked="" type="checkbox"/> | 12. | Suppression tests with newborn infant (Part 572, Subpart K) |
| <input checked="" type="checkbox"/> | 13. | Suppression tests with 3-year-old dummy (Part 572, Subpart P) |
| <input checked="" type="checkbox"/> | 14. | Suppression tests with 6-year-old dummy (Part 572, Subpart N) |
| <input checked="" type="checkbox"/> | 15. | Test of reactivation of the passenger air bag system with an unbelted 5 th percentile female dummy |
| <input type="checkbox"/> | 16. | Low risk deployment test with 12-month-old dummy (Part 572, Subpart R) |
| <input type="checkbox"/> | 17. | Low risk deployment test with 3-year-old dummy (Part 572, Subpart P) |
| <input checked="" type="checkbox"/> | 18. | Low risk deployment test with 6-year-old dummy (Part 572, Subpart N) |
| <input checked="" type="checkbox"/> | 19. | Low risk deployment test with 5 th female dummy (Part 572, Subpart O) |
| <input checked="" type="checkbox"/> | 20. | Impact Tests |
| <input type="checkbox"/> | | Frontal Oblique |
| <input type="checkbox"/> | | Belted 50 th male dummy driver and passenger (0 to 48 kmph) (S5.1.1(a)) |
| <input type="checkbox"/> | | Unbelted 50 th male dummy driver and passenger (0 to 48 kmph) (S5.1.2(a)(1)) |
| <input type="checkbox"/> | | Unbelted 50 th male dummy driver and passenger (32 to 40 kmph) (S5.1.2(a) (1) or S5.1.2(b)) |
| <input checked="" type="checkbox"/> | | Frontal 0° |
| <input type="checkbox"/> | | Belted 50 th male dummy driver (0 to 48 kmph) (S5.1.1.(b)(1) or S5.1.1(a)) |
| <input type="checkbox"/> | | Belted 50 th male dummy passenger (0 to 48 kmph) (S5.1.1.(b)(1) or S5.1.1(a)) |
| <input type="checkbox"/> | | Belted 5 th female dummy driver (0 to 48 kmph) (S16.1(a)) |
| <input type="checkbox"/> | | Belted 5 th female dummy passenger (0 to 48 kmph) (S16.1(a)) |
| <input type="checkbox"/> | | Belted 50 th male dummy driver and passenger (0 to 56 kmph) (S5.1.1.(b)(2)) |
| <input type="checkbox"/> | | Unbelted 50 th male dummy driver and passenger (0 to 48 kmph) (S5.1.2(a) (1)) |
| <input type="checkbox"/> | | Unbelted 50 th male dummy driver (32 to 40 kmph) (S5.1.2.(a)(2) or S5.1.2(b)) |

		Unbelted 50 th male dummy passenger (32 to 40 kmph) (S5.1.2.(a)(2) or S5.1.2(b))
	X	Unbelted 5 th female dummy driver (32 to 40 kmph) (S16.1(b))
	X	Unbelted 5 th female dummy passenger (32 to 40 kmph) (S16.1(b))
		40% Offset 0° Belted 5 th male dummy driver and passenger (0 to 40 kmph) (S18.1)
	21.	Sled Test: unbelted 50 th male dummy driver and passenger (S13)
	22.	FMVSS 204 Indicant Test
X	23.	FMVSS 212 Indicant Test
X	24.	FMVSS 219 Indicant Test
X	25.	FMVSS 301 Indicant Frontal Test

For the crash tests, the vehicle was instrumented with 8 accelerometers. The accelerometer data from the vehicle and dummies were sampled at 10,000 samples per second and processed as specified in SAE J211/1 MAR95 and FMVSS 208, S4.13.

The dynamic tests were recorded using high-speed film and high-speed digital video.

The vehicle appears to meet the performance requirements to which it was tested.

SECTION 3

INJURY RESULT SUMMARY FOR FMVSS 208 TESTS

Test Vehicle: 2004 Mitsubishi Galant 4 Door
 Test Program: FMVSS 208 Compliance

NHTSA No.: C45603
 Test Dates: 6/24 & 7/8/04

5th Percentile Female Low Risk Deployments

5th Percentile Female SN 505 Position 1 (Chin On Module) 6-24-04

Injury Criteria	Max. Allowable Injury Assessment Values	Measured Value
HIC15	700	7
Peak Nij (Nte)	1.0	0.4
Time (ms)	NA	11.5
Peak Nij (Ntf)	1.0	0.1
Time (ms)	NA	7.1
Peak Nij (Nce)	1.0	0.0
Time (ms)	NA	1.3
Peak Nij (Ncf)	1.0	0.0
Time (ms)	NA	5.3
Neck Tension	2070 N	855
Neck Compression	2520 N	6
Chest g	60 g	7
Chest Displacement	52 mm	4
Left Femur	6805 N	59
Right Femur	6805 N	40

Second stage fire time of 100 ms; Injuries calculated on 0 ms to 225 ms

5th Percentile Female SN 506 Position 2 (Chin On Rim) 7-8-04

Injury Criteria	Max. Allowable Injury Assessment Values	Measured Value
HIC15	700	16
Peak Nij (Nte)	1.0	0.7
Time (ms)	NA	16.0
Peak Nij (Ntf)	1.0	0.3
Time (ms)	NA	69.1
Peak Nij (Nce)	1.0	0.3
Time (ms)	NA	21.9
Peak Nij (Ncf)	1.0	0.2
Time (ms)	NA	29.1
Neck Tension	2070 N	912
Neck Compression	2520 N	85
Chest g	60 g	20
Chest Displacement	52 mm	25
Left Femur	6805 N	53
Right Femur	6805 N	31

Second stage fire time of 100 ms; Injuries calculated on 0 ms to 225 ms

SECTION 3...(continued)

INJURY RESULT SUMMARY FOR FMVSS 208 TESTS

Test Vehicle: 2004 Mitsubishi Galant 4 Door
Test Program: FMVSS 208 Compliance

NHTSA No.: C45603
Test Date: 6/24 & 7/8/04

6 Year Old Low Risk Deployments

6 Year Old SN 153 Position 1 (Chin On Instrument Panel) 6-24-04

Injury Criteria	Max. Allowable Injury Assessment Values	Measured Value
HIC15	700	9
Peak Nij (Nte)	1.0	0.2
Time (ms)	NA	24.1
Peak Nij (Ntf)	1.0	0.2
Time (ms)	NA	19.5
Peak Nij (Nce)	1.0	0.1
Time (ms)	NA	9.8
Peak Nij (Ncf)	1.0	0.1
Time (ms)	NA	10.5
Neck Tension	1490 N	375
Neck Compression	1820 N	212
Chest g	60 g	13
Chest Displacement	40 mm	8

Second stage fire time of 300 ms; Injuries calculated on 0 ms to 100 ms

6 Year Old SN 153 Position 2 (Head On Instrument Panel) 7-8-04

Injury Criteria	Max. Allowable Injury Assessment Values	Measured Value
HIC15	700	5
Peak Nij (Nte)	1.0	0.2
Time (ms)	NA	8.4
Peak Nij (Ntf)	1.0	0.0
Time (ms)	NA	0.1
Peak Nij (Nce)	1.0	0.7
Time (ms)	NA	17.6
Peak Nij (Ncf)	1.0	0.2
Time (ms)	NA	33.0
Neck Tension	1490 N	432
Neck Compression	1820 N	1281
Chest g	60 g	11
Chest Displacement	40 mm	0.5

Second stage fire time of 300 ms; Injuries calculated on 0 ms to 100 ms

SECTION 3...(continued)

INJURY RESULT SUMMARY FOR FMVSS 208 TESTS

Test Vehicle: 2004 Mitsubishi Galant 4 Door NHTSA No.: C45603
 Test Program: FMVSS 208 Compliance Test Date: 7/23/04
40 kmph Frontal Crash

Impact Angle: Zero degrees

Belted Dummies: Yes (Rear Passenger) X No (Driver and Front Passenger)
 Speed Range: 0 to 40 kmph X 32 to 40 kmph
 0 to 48 kmph 0 to 56 kmph

Test Speed: 39.8 kmph Test Weight: 1689.7 kg

Driver Dummy: X 5th female 50th male
 Passenger Dummy: X 5th female 50th male
 Right Rear Passenger Dummy: 5th female 50th male

5th Percentile Female Frontal Crash Test Vehicles certified to S16.1(a), S16.1(b), or S18.1

Injury Criteria	Max. Allowable Injury Assessment Values	Driver	Passenger
HIC15	700	69	74
N _{te}	1.0	0.7	0.8
N _{tf}	1.0	0.2	0.3
N _{ce}	1.0	0.6	0.7
N _{cf}	1.0	0.2	0.1
Neck Tension	2620 N	1192	852
Neck Compression	2520 N	1379	249
Chest g	60 g	37	34
Chest Displacement	52 mm	18	13
Left Femur	6805 N	2676	3415
Right Femur	6805 N	4013	3318

SECTION 4
DISCUSSION OF TESTS

Test Vehicle: 2004 Mitsubishi Galant 4 Door
Test Program: FMVSS 208 Compliance

NHTSA No.: C45603
Test Date: 3/18 - 7/23/04

The vehicle met all tested performance requirements.

A blanket and visor were not used in the suppression testing because they did not affect the weight sensing system used on the vehicle.

There were no other unexpected events or items to discuss.

SECTION 5
TEST DATA SHEETS

Test Vehicle: 2004 Mitsubishi Galant 4 Door
Test Program: FMVSS 208 Compliance

NHTSA No.: C45603
Test Dates: 3/18 - 7/23/04

DATA SHEET 1

COTR VEHICLE WORK ORDER

Test Vehicle: 2004 Mitsubishi Galant 4 Door
 Test Program: FMVSS 208 Compliance

NHTSA No.: C45603
 Test Dates: 3/18 - 7/23/04

COTR Signature: Charles R. Case

Test to be performed for this vehicle are checked below:

- | | |
|----------|---|
| X | 1. Rear Outboard Seating Position Seat Belts (S4.1.2(b)) & (S4.2.4) |
| X | 2. Air Bag Labels (S4.5.1) |
| X | 3. Readiness Indicator (S4.5.2) |
| X | 4. Passenger Air Bag Manual Cut-off Device (S4.5.4) |
| X | 5. Lap Belt Lockability (S7.1.1.5) |
| X | 6. Seat Belt Warning System (S7.3) |
| X | 7. Seat Belt Contact Force (S7.4.4) |
| X | 8. Seat Belt Latch Plate Access (S7.4.4) |
| X | 9. Seat Belt Retraction (S7.4.5) |
| X | 10. Seat Belt Guides and Hardware (S7.4.6) |
| X | 11. Suppression tests with 12-month-old CRABI dummy (Part 572, Subpart R) using the following indicated child restraints. |

Section B

X	Britax Handle with Care 191	X	Full Rearward	X	Mid Position	X	Full Forward
	Century Assura 4553		Full Rearward		Mid Position		Full Forward
	Century Avanta SE 41530		Full Rearward		Mid Position		Full Forward
	Century Smart Fit 4543		Full Rearward		Mid Position		Full Forward
	Cosco Arriva 02727		Full Rearward		Mid Position		Full Forward
	Cosco Opus 35 02603		Full Rearward		Mid Position		Full Forward
	Evenflo Discovery Adjust Right 212		Full Rearward		Mid Position		Full Forward
X	Evenflo First Choice 204	X	Full Rearward	X	Mid Position	X	Full Forward
	Evenflo On My Way Position Right V 282		Full Rearward		Mid Position		Full Forward
X	Graco Infant 8457	X	Full Rearward	X	Mid Position	X	Full Forward

Section C

X	Britax Roundabout 161	X	Full Rearward	X	Mid Position	X	Full Forward
X	Century Encore 4612	X	Full Rearward	X	Mid Position	X	Full Forward
	Century STE 1000 4416		Full Rearward		Mid Position		Full Forward
	Cosco Olympian 02803		Full Rearward		Mid Position		Full Forward
	Cosco Touriva 02519		Full Rearward		Mid Position		Full Forward
	Evenflo Horizon V 425		Full Rearward		Mid Position		Full Forward
X	Evenflo Medallion 254	X	Full Rearward	X	Mid Position	X	Full Forward
X	12. Suppression tests with newborn infant (Part 572, Subpart K) using the following indicated child restraints.						

Section A

X	Cosco Dream Ride 02-719	X	Full Rearward	X	Mid Position	X	Full Forward
X	13. Suppression tests with 3-year-old dummy (Part 572, Subpart P) using the following indicated child restraints where a child restraint is required.						

Section C

<input checked="" type="checkbox"/>	Britax Roundabout 161	<input checked="" type="checkbox"/>	Full Rearward	<input checked="" type="checkbox"/>	Mid Position	<input checked="" type="checkbox"/>	Full Forward
<input checked="" type="checkbox"/>	Century Encore 4612	<input checked="" type="checkbox"/>	Full Rearward	<input checked="" type="checkbox"/>	Mid Position	<input checked="" type="checkbox"/>	Full Forward
<input type="checkbox"/>	Century STE 1000 4416	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward
<input type="checkbox"/>	Cosco Olympian 02803	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward
<input type="checkbox"/>	Cosco Touriva 02519	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward
<input type="checkbox"/>	Evenflo Horizon V 425	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward
<input checked="" type="checkbox"/>	Evenflo Medallion 254	<input checked="" type="checkbox"/>	Full Rearward	<input checked="" type="checkbox"/>	Mid Position	<input checked="" type="checkbox"/>	Full Forward

Section D

<input type="checkbox"/>	Britax Roadster 9004	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward
<input checked="" type="checkbox"/>	Century Next Step 4920	<input checked="" type="checkbox"/>	Full Rearward	<input checked="" type="checkbox"/>	Mid Position	<input checked="" type="checkbox"/>	Full Forward
<input checked="" type="checkbox"/>	Cosco High Back Booster 02-442	<input checked="" type="checkbox"/>	Full Rearward	<input checked="" type="checkbox"/>	Mid Position	<input checked="" type="checkbox"/>	Full Forward
<input type="checkbox"/>	Evenflo Right Fit 245	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward

- ☐ 14. Suppression tests with representative 3-year-old child using the following indicated child restraints where a child restraint is required. (Appendix H, Data Sheet 16H and 17H)

Section C

<input type="checkbox"/>	Britax Roundabout 161	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward
<input type="checkbox"/>	Century Encore 4612	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward
<input type="checkbox"/>	Century STE 1000 4416	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward
<input type="checkbox"/>	Cosco Olympian 02803	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward
<input type="checkbox"/>	Cosco Touriva 02519	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward
<input type="checkbox"/>	Evenflo Horizon V 425	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward
<input type="checkbox"/>	Evenflo Medallion 254	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward

Section D

<input type="checkbox"/>	Britax Roadster 9004	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward
<input type="checkbox"/>	Century Next Step 4920	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward
<input type="checkbox"/>	Cosco High Back Booster 02-442	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward
<input type="checkbox"/>	Evenflo Right Fit 245	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward

- ☒ 15. Suppression tests with 3-year-old dummy (Part 572, Subpart P) in the following Forward, Middle, and Rearward seat track positions

<input checked="" type="checkbox"/>	Sitting on seat with back against seat back (S22.2.2.1)
<input checked="" type="checkbox"/>	Sitting on seat with back against reclined seat back (S22.2.2.2)
<input checked="" type="checkbox"/>	Sitting on seat with back not against seat back (S22.2.2.3)
<input checked="" type="checkbox"/>	Sitting on seat edge, spine vertical, hands by the child's side (S22.2.2.4)
<input checked="" type="checkbox"/>	Standing on seat, facing forward (S22.2.2.5)
<input checked="" type="checkbox"/>	Kneeling on seat facing forward (S22.2.2.6)
<input checked="" type="checkbox"/>	Kneeling on seat facing rearward (S22.2.2.7)
<input type="checkbox"/>	Lying on seat (S22.2.2.8)

- ☐ 16. Suppression tests with representative 3-year-old child in the following positions

<input type="checkbox"/>	Sitting on seat with back against seat back (S22.2.2.1)
<input type="checkbox"/>	Sitting on seat with back against reclined seat back (S22.2.2.2)
<input type="checkbox"/>	Sitting on seat with back not against seat back (S22.2.2.3)
<input type="checkbox"/>	Sitting on seat edge, spine vertical, hands by the child's side (S22.2.2.4)
<input type="checkbox"/>	Standing on seat, facing forward (S22.2.2.5)
<input type="checkbox"/>	Kneeling on seat facing forward (S22.2.2.6)
<input type="checkbox"/>	Kneeling on seat facing rearward (S22.2.2.7)
<input type="checkbox"/>	Lying on seat (S22.2.2.8)

- ☐ 17. Suppression tests with 6-year-old dummy (Part 572, Subpart N) using the following indicated child restraints where a child restraint is required.

Section D

<input type="checkbox"/>	Britax Roadster 9004	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward
<input type="checkbox"/>	Century Next Step 4920	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward
<input type="checkbox"/>	Cosco High Back Booster 02-442	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward
<input type="checkbox"/>	Evenflo Right Fit 245	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward
<input type="checkbox"/>	18. Suppression tests with representative 6-year-old child using the following indicated child restraints where a child restraint is required.						

Section D

<input type="checkbox"/>	Britax Roadster 9004	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward
<input type="checkbox"/>	Century Next Step 4920	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward
<input type="checkbox"/>	Cosco High Back Booster 02-442	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward
<input type="checkbox"/>	Evenflo Right Fit 245	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward
<input type="checkbox"/>	19. Suppression tests with 6-year-old dummy (Part 572, Subpart N) in the following Forward, Middle, and Rearward seat track positions						
<input type="checkbox"/>	Sitting on seat with back against seat back (S22.2.2.1)						
<input type="checkbox"/>	Sitting on seat with back against reclined seat back (S22.2.2.2)						
<input type="checkbox"/>	Sitting on seat edge, spine vertical, hands by the child's side (S22.2.2.4)						
<input type="checkbox"/>	Sitting back in the seat and leaning on the right front passenger door (S24.2.3)						
<input type="checkbox"/>	20. Suppression tests with representative 6-year-old child in the following positions						
<input type="checkbox"/>	Sitting on seat with back against seat back (S22.2.2.1)						
<input type="checkbox"/>	Sitting on seat with back against reclined seat back (S22.2.2.2)						
<input type="checkbox"/>	Sitting on seat edge, spine vertical, hands by the child's side (S22.2.2.4)						
<input type="checkbox"/>	Sitting back in the seat and leaning on the right front passenger door (S24.2.3)						
<input checked="" type="checkbox"/>	21. Test of Reactivation of the Passenger Air Bag System with an Unbelted 5 th percentile female dummy (S20.3, 22.3, S24.3). Perform this test after the following suppression tests: After each restraint.						
<input type="checkbox"/>	22. Test of Reactivation of the passenger air bag system with a representative 5 th percentile female (S20.3, 22.3, S24.3). Perform this test after the following suppression tests:						
<input type="checkbox"/>	23. Low risk deployment test with 12-month-old dummy (Part 572, Subpart R) using the following indicated child restraints.						

Section B

<input type="checkbox"/>	Britax Handle with Care 191	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward
<input type="checkbox"/>	Century Assura 4553	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward
<input type="checkbox"/>	Century Avanta SE 41530	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward
<input type="checkbox"/>	Century Smart Fit 4543	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward
<input type="checkbox"/>	Cosco Arriva 02727	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward
<input type="checkbox"/>	Cosco Opus 35 02603	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward
<input type="checkbox"/>	Evenflo Discovery Adjust Right 212	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward
<input type="checkbox"/>	Evenflo First Choice 204	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward
<input type="checkbox"/>	Evenflo On My Way Position Right V 282	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward
<input type="checkbox"/>	Graco Infant 8457	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward

Section C

<input type="checkbox"/>	Britax Roundabout 161	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward
<input type="checkbox"/>	Century Encore 4612	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward
<input type="checkbox"/>	Century STE 1000 4416	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward
<input type="checkbox"/>	Cosco Olympian 02803	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward
<input type="checkbox"/>	Cosco Touriva 02519	<input type="checkbox"/>	Full Rearward	<input type="checkbox"/>	Mid Position	<input type="checkbox"/>	Full Forward

		Evenflo Horizon V 425		Full Rearward		Mid Position		Full Forward
		Evenflo Medallion 254		Full Rearward		Mid Position		Full Forward
		24. Low risk deployment test with 3-year-old dummy (Part 572, Subpart P) in the following positions						
		Position 1						
		Position 2						
X		25. Low risk deployment test with 6-year-old dummy (Part 572, Subpart N) in the following positions						
	X	Position 1						
	X	Position 2						
X		26. Low risk deployment test with 5 th percentile female dummy (Part 572, Subpart O) in the following positions						
	X	Position 1						
	X	Position 2						
X		27. Impact Tests						
		Frontal Oblique – Test Speed:						
		Belted 50 th male dummy driver and passenger (0 to 48 kmph) (S5.1.1(a))						
		Unbelted 50 th male dummy driver and passenger (0 to 48 kmph) (S5.1.2(a)(1))						
		Unbelted 50 th male dummy driver and passenger (32 to 40 kmph) (S5.1.2(a) (1) or S5.1.2(b))						
	X	Frontal 0° - Test Speed: 39.8 kmph						
		Belted 50 th male dummy driver (0 to 48 kmph) (S5.1.1.(b)(1) or S5.1.1(a))						
		Belted 50 th male dummy passenger (0 to 48 kmph) (S5.1.1.(b)(1) or S5.1.1(a))						
		Belted 5 th female dummy driver (0 to 48 kmph) (S16.1(a))						
		Belted 5 th female dummy passenger (0 to 48 kmph) (S16.1(a))						
		Belted 50 th male dummy driver and passenger (0 to 56 kmph) (S5.1.1.(b)(2))						
		Unbelted 50 th male dummy driver and passenger (0 to 48 kmph) (S5.1.2(a) (1))						
		Unbelted 50 th male dummy driver (32 to 40 kmph) (S5.1.2.(a)(2) or S5.1.2(b))						
		Unbelted 50 th male dummy passenger (32 to 40 kmph) (S5.1.2.(a)(2) or S5.1.2(b))						
	X	Unbelted 5 th female dummy driver (32 to 40 kmph) (S16.1(b))						
	X	Unbelted 5 th female dummy passenger (32 to 40 kmph) (S16.1(b))						
		40% Offset 0° Belted 5 th male dummy driver and passenger (0 to 40 kmph) (S18.1)						
		– Test Speed:						
		28. Sled Test: Unbelted 50 th male dummy driver and passenger (S13)						
		29. FMVSS 204 Indicant Test						
	X	30. FMVSS 212 Indicant Test						
	X	31. FMVSS 219 Indicant Test						
	X	32. FMVSS 301 Indicant Frontal Test						

DATA SHEET 2
REPORT OF VEHICLE CONDITION

Test Vehicle: 2004 Mitsubishi Galant 4 Door
Test Program: FMVSS 208 Compliance

NHTSA No.: C45603
Test Dates: 3/18 - 7/23/04

CONTRACT NO. DTNH22- 03-D-11002
FROM (Lab and rep name): MGA Research Corporation
TO: NHTSA, OVSC (NVS-220)

Date: 7/27/04

PURPOSE: () Initial Receipt () Received via Transfer (X) Present vehicle condition

MODEL YEAR/MAKE/MODEL/BODY STYLE: 2004 Mitsubishi Galant 4 Door
MANUFACTURE DATE: 10/03
NHTSA NO. C45603 GVWR: 1960 kg (4321 lbs)
BODY COLOR: SILVER GAWR (Fr): 1040 kg (2293 lbs)
VIN: 4A3AB56F64E051855 GAWR (Rr): 920 kg (2028 lbs)

ODOMETER READINGS: ARRIVAL (miles): 143 DATE: 2/19/04
COMPLETION (miles): 146 DATE: 7/27/04

PURCHASE PRICE: (\$) 23,799.00

DEALER'S NAME: Biggers Mitsubishi 1325 E Chicago St Elgin, IL 60120

- A. All options listed on window sticker are present on the test vehicle:
X Yes ___ No
- B. Tires and wheel rims are new and the same as listed: X Yes ___ No
- C. There are no dents or other interior or exterior flaws: X Yes ___ No
- D. The vehicle has been properly prepared and is in running condition:
X Yes ___ No
- E. Keyless remote is available and working: X Yes ___ No
- F. The glove box contains an owner's manual, warranty document, consumer information, and extra set of keys: X Yes ___ No
- G. Proper fuel filler cap is supplied on the test vehicle: X Yes ___ No
- H. Using permanent marker, identify vehicle with NHTSA number and FMVSS test type(s) on roof line above driver door or for school buses, place a placard with NHTSA number inside the windshield and to the exterior front and rear side of bus:
X Yes ___ No
- I. Place vehicle in storage area: X Yes ___ No
- J. Inspect the vehicle's interior and exterior, including all windows, seats, doors, etc. to confirm that each system is complete and functional per the manufacturer's specifications. Any damage, misadjustment, or other unusual condition that could influence the test program or test results shall be recorded. Report any abnormal condition to the NHTSA COTR before beginning any test:
X Vehicle OK ___ Conditions reported below

REPORT OF VEHICLE CONDITION AT THE COMPLETION OF TESTING

LIST OF FMVSS TESTS PERFORMED BY THIS LAB: FMVSS 208, 212, 219, 301

VEHICLE: 2004 Mitsubishi Galant 4 Door NHTSA NO. C45603

REMARKS:

Equipment that is no longer on the test vehicle as noted on previous page:

Tool & jack, trunk room trims, rear seat, and spare tire

Explanation for equipment removal:

Components removed for instrumentation installation and to meet target weight.

Test Vehicle Condition:

25 mph frontal impact damage- front suspension & structure damaged, hood & front quarter panels damaged, radiator damaged, air bags & pretensioners deployed, Stoddard in fuel system

RECORDED BY: Jeff Lewandowski DATE: 7/27/2004

APPROVED BY: David Winkelbauer DATE: 7/27/2004

#####

RELEASE OF TEST VEHICLE

The vehicle described above is released from MGA to be delivered to:

Date: Time: Odometer:

Lab Rep's Signature:

Title:

Carrier/Customer Rep:

Date:

DATA SHEET 3**CERTIFICATION LABEL AND TIRE PLACARD INFORMATION**

Test Vehicle: 2004 Mitsubishi Galant 4 Door
Test Program: FMVSS 208 Compliance
Test Technician: Clark Subrt

NHTSA No.: C45603
Test Date: 7/23/04

Certification Label	
Manufacturer:	Mitsubishi Motors North America, Inc.
Date of Manufacture:	10/03
VIN:	4A3AB56F64E051855
Vehicle Certified As (Pass. Car/MPV/Truck/Bus):	Passenger Car
Front Axle GVWR:	1040 kg (2293 lbs)
Rear Axle GVWR:	920 kg (2028 lbs)
Total GVWR:	1960 kg (4321 lbs)

Tire Placard	
Not applicable, vehicle is not a passenger car and does not have a tire placard.	Passenger Car
This is not a passenger car, but all or part of this information is still contained on a vehicle label and is reported here.	Passenger Car
Vehicle Capacity Weight:	375 kg (825 lbs)
Designated Seating Capacity Front:	2
Designated Seating Capacity Rear:	3
Total Designated Seating Capacity:	5
Recommended Cold Tire Inflation Pressure Front:	220 kpa (32 psi)
Recommended Cold Tire Inflation Pressure Rear:	220 kpa (32 psi)
Recommended Tire Size:	P215/60R16

Signature: 

Date: 7/22/04

DATA SHEET 4

REAR OUTBOARD SEATING POSITION SEAT BELTS

Test Vehicle: 2004 Mitsubishi Galant 4 Door

NHTSA No.: C45603

Test Program: FMVSS 208 Compliance

Test Date: 3/18/04

Test Technician: Wayne Dahlke

	Yes	No
Do all rear outboard seating positions have Type 2 seat belts?	X	

If NO, describe the seat belt installed, the seat location, and any other information about the seat that would explain why a Type 2 seat belt was not installed.

REMARKS: NONE

Signature: Wayne Dahlke

Date: 3/18/04

DATA SHEET 5

AIR BAG LABELS (S4.5.1)

Test Vehicle: 2004 Mitsubishi Galant 4 Door
 Test Program: FMVSS 208 Compliance
 Test Technician: Wayne Dahlke

NHTSA No.: C45603
 Test Date: 3/18/04

- ☒ 1. Air bag maintenance label and owner's manual instructions: (S4.5.1(a))
- ☒ 1.1 Does the manufacturer recommend periodic maintenance or replacement of the air bag?
- ☐ Yes, go to 1.2
- ☒ No – go to 2
- ☐ 1.2 Does the vehicle have a label specifying air bag maintenance or replacement?
- ☐ Yes – Pass
- ☐ No – Fail
- ☐ 1.3 Does the label contain one of the following?
- ☐ Yes – Pass
- ☐ No – Fail
- Check applicable schedule:
- ___ Schedule on label specifies month and year (Record date___)
- ___ Schedule on label specified vehicle mileage (Record mileage___)
- ___ Schedule on label specifies interval measured from date on certification label (Record interval___)
- ☐ 1.4 Is the label permanently affixed within the passenger compartment such that it cannot be removed without destroying or defacing the label or the sunvisor?
- ☐ Yes – Pass
- ☐ No – Fail
- ☐ 1.5 Is the label lettered in English?
- ☐ Yes – Pass
- ☐ No – Fail
- ☐ 1.6 Is the label in block capitals and numerals?
- ☐ Yes – Pass
- ☐ No – Fail
- ☐ 1.7 Are the letters and numerals at least 3/32 inches high?
- ☐ Yes – Pass
- ☐ No – Fail
- ☐ 1.8 Does the owner's manual set forth the recommended schedule for maintenance or replacement?
- ☒ 2. Does the owner's manual: (S4.5.1(f))
- ☒ 2.1 Include a description of the vehicle's air bag system in an easily understandable format?
- ☒ Yes – Pass
- ☐ No – Fail
- ☒ 2.2 Include a statement that the vehicle is equipped with an air bag and a lap/shoulder belt at the front outboard seating position?
- ☒ Yes – Pass
- ☐ No – Fail

- ☒ 2.3 Include a statement that the air bag is a supplement restraint at the front outboard seating position?
- ☒ Yes – Pass
☐ No – Fail
- ☒ 2.4 Emphasize that all occupants, including the driver, should always wear their seat belts whether or not an air bag is also provided at their seating positions to minimize the risk of severe injury or death in the event of a crash?
- ☒ Yes – Pass
☐ No – Fail
- ☒ 2.5 Provide any necessary precautions regarding the proper positioning of occupants, including children, at seating positions equipped with air bags to ensure maximum safety protection for those occupants?
- ☒ Yes – Pass
☐ No – Fail
- ☒ 2.6 Explain that no objects should be placed over or near the air bag on the steering wheel or on the instrument panel, because any such objects could cause harm if the vehicle is in a crash severe enough to cause the air bag to inflate?
- ☒ Yes – Pass
☐ No – Fail
- ☒ 2.7 Is the vehicle certified to meet the requirements of S14.5, S15, S17, S19, S21, S23, and S25? (Obtain answer from COTR) (S4.5.1(f)(2))
- ☒ Yes – (Go to 2.7.1)
☐ No – (Go to 3.)
- ☒ 2.7.1 Explain the proper functioning of the advanced air bag system? (S4.5.1(f)(2))
- ☒ Yes – Pass
☐ No – Fail
- ☒ 2.7.2 Provide a summary of the actions that may affect the proper functioning of the system? (S4.5.1(f)(2))
- ☒ Yes – Pass
☐ No – Fail
- ☒ 2.7.3 Present and explain the main components of the advanced passenger air bag system? (S4.5.1(f)(2)(i))
- ☒ Yes – Pass
☐ No – Fail
- ☒ 2.7.4 Explain how the components function together as part of the advanced passenger air bag system? (S4.5.1(f)(2)(ii))
- ☒ Yes – Pass
☐ No – Fail
- ☒ 2.7.5 Contain the basic requirements for proper operation, including an explanation of the actions that may affect the proper functioning of the system? (S4.5.1(f)(2)(iii))
- ☒ Yes – Pass
☐ No – Fail
- ☒ 2.7.6 Is the vehicle certified to the requirements of S19.2, S21.2, or 23.2 (automatic suppression)?
- ☒ Yes, continue with 2.7.6
☐ No, go to 2.7.7
- ☒ 2.7.6.1 Contain a complete description of the passenger air bag suppression system installed in the vehicle, including a discussion of any suppression zone? (S4.5.1(f)(2)(iv))
- ☒ Yes – Pass
☐ No – Fail

- ☒ 2.7.6.2 Discuss the telltale light, specifying its location in the vehicle and explaining when the light is illuminated?
- ☒ Yes – Pass
☐ No – Fail
- ☒ 2.7.7 Explain the interaction of the advanced passenger air bag system with other vehicle components, such as seat belts, seats or other components? (S4.5.1(f)(2)(v))
- ☒ Yes – Pass
☐ No – Fail
- ☒ 2.7.8 Summarize the expected outcomes when child restraint systems, children and small teenagers or adults are both properly and improperly positioned in the passenger seat, including cautionary advice against improper placement of child restraint systems? (S4.5.1(f)(2)(vi))
- ☒ Yes – Pass
☐ No – Fail
- ☒ 2.7.9 Provide information on how to contact the vehicle manufacturer concerning modifications for persons with disabilities that may affect the advanced air bag system? (S4.5.1(f)(2)(vii))
- ☒ Yes – Pass
☐ No – Fail
- ☒ 3. Sun Visor Air Bag Warning Label (S4.5.1(b)) Check only one of the following:
- ☐ The vehicle is not certified to meet the requirements of S19, S21, and S23 (Obtain answer from COTR) (S4.5.1(b)(1)) Go to 3.1 and skip 3.2 and 3.3
- ☐ The vehicle is certified to meet the requirements of S19, S21, and S23 before 9/1/03. (Obtain answer from COTR) (S4.5.1(b)(2)) Go to 3.2 and skip 3.1 and 3.3
- ☒ The vehicle is certified to meet the requirements of S19, S21, and S23 on 9/1/03 or later. (Obtain answer from COTR) (S4.5.1(b)(3)) Go to 3.3 and skip 3.1 and 3.2
- ☐ 3.1 Vehicles not certified to meet the requirements of S19, S21, and S23.
- ☐ 3.1.1 Is the label permanently affixed (including permanent marking on the visor material or molding into the visor material) to either side of the sun visor at each front outboard seating position such that it cannot be removed without destroying or defacing it? (S4.5.1(b)(1))
- ☐ Driver Side, Yes – Pass
☐ Driver Side, No – Fail
☐ Passenger Side, Yes – Pass
☐ Passenger Side, No – Fail

3.1.2

Does the label conform in content to the label shown in either Figure 6A or 6B (Figure 6b is for vehicles with passenger air bag on-off switches), as appropriate, at each front outboard seating position? (S4.5.1(b)(1)) (Vehicles without back seats may omit the statement: "The back seat is the safest place for children." (S4.5.1(b)(1)(iv))



Figure 6a. Sun Visor Label Visible When Visor is in Down Position.



Figure 6b. Sun Visor Label Visible When Visor is in Down Position.

- ☐ Driver Side, Yes – Pass
- ☐ Driver Side, No – Fail
- ☐ Passenger Side, Yes – Pass
- ☐ Passenger Side, No – Fail

3.1.3

Is the label heading area yellow with the word "WARNING" and the alert symbol in black? (S4.5.1(b)(1)(i))

- ☐ Driver Side, Yes – Pass
- ☐ Driver Side, No – Fail
- ☐ Passenger Side, Yes – Pass
- ☐ Passenger Side, No – Fail

3.1.4

Is the message area white with black text? (S4.5.1(b)(1)(ii))

- ☐ Driver Side, Yes – Pass
- ☐ Driver Side, No – Fail
- ☐ Passenger Side, Yes – Pass
- ☐ Passenger Side, No – Fail

<input type="checkbox"/>	3.1.5	Is the message area at least 30 cm ² ? (S4.5.1(b)(1)(ii)) Driver Side: Length_____, Width_____ Passenger Side: Length_____, Width_____ Actual message area _____ cm ²
		<input type="checkbox"/> Driver Side, Yes – Pass
		<input type="checkbox"/> Driver Side, No – Fail
		<input type="checkbox"/> Passenger Side, Yes – Pass
		<input type="checkbox"/> Passenger Side, No – Fail
<input type="checkbox"/>	3.1.6	Is the pictogram black with a red circle and slash on a white background? (S4.5.1(b)(2)(iii))
		<input type="checkbox"/> Driver Side, Yes – Pass
		<input type="checkbox"/> Driver Side, No – Fail
		<input type="checkbox"/> Passenger Side, Yes – Pass
		<input type="checkbox"/> Passenger Side, No – Fail
<input type="checkbox"/>	3.1.7	Is the pictogram at least 30 mm in diameter? (S4.5.1(b)(2)(iii)) Actual diameter_____mm
		<input type="checkbox"/> Driver Side, Yes – Pass
		<input type="checkbox"/> Driver Side, No – Fail
		<input type="checkbox"/> Passenger Side, Yes – Pass
		<input type="checkbox"/> Passenger Side, No – Fail
<input type="checkbox"/>	3.2	Vehicles certified to meet the requirements of S19, S21, and S23 before 9/1/03.
<input type="checkbox"/>	3.2.1	Is the label permanently affixed (including permanent marking on the visor material or molding into the visor material) to either side of the sun visor at each front outboard seating position such that it cannot be removed without destroying or defacing the label or the sun visor? (S4.5.1(b)(2))
		<input type="checkbox"/> Driver Side, Yes – Pass
		<input type="checkbox"/> Driver Side, No – Fail
		<input type="checkbox"/> Passenger Side, Yes – Pass
		<input type="checkbox"/> Passenger Side, No – Fail



3.2.2

Does the label conform in content to the label shown in either Figure 8 or 11 at each front outboard seating position? (S4.5.1(b)(2)) (Vehicles without back seats may omit the statement: "The back seat is the safest place for children." (S4.5.1(b)(2)(iv)) Vehicles without back seats or the back seat is too small to accommodate a rear-facing child restraint may omit the statement "Never put a rear-facing child seat in the front."(S4.5.1(b)(2)(v))



Figure 8. Sun Visor Label Visible when Visor is in Down Position.



Figure 11. Sun Visor Label Visible when Visor is in Down Position.



- Driver Side, Yes – Pass
- Driver Side, No – Fail
- Passenger Side, Yes – Pass
- Passenger Side, No – Fail



3.2.3

Is the label heading area yellow with the word "WARNING" and the alert symbol in black? (S4.5.1(b)(2)(i))



- Driver Side, Yes – Pass
- Driver Side, No – Fail
- Passenger Side, Yes – Pass
- Passenger Side, No – Fail



3.2.4

Is the message area white with black text? (S4.5.1(b)(2)(ii))



- Driver Side, Yes – Pass
- Driver Side, No – Fail
- Passenger Side, Yes – Pass
- Passenger Side, No – Fail

- ☐ 3.2.5 Is the message area at least 30 cm²? (S4.5.1(b)(2)(ii))
 Driver Side: Length_____, Width_____
 Passenger Side: Length_____, Width_____
 Actual message area _____ cm²
- ☐ Driver Side, Yes – Pass
☐ Driver Side, No – Fail
☐ Passenger Side, Yes – Pass
☐ Passenger Side, No – Fail
- ☐ 3.2.6 Is the pictogram black on a white background? (S4.5.1(b)(2)(iii))
- ☐ Driver Side, Yes – Pass
☐ Driver Side, No – Fail
☐ Passenger Side, Yes – Pass
☐ Passenger Side, No – Fail
- ☐ 3.2.7 Is the pictogram at least 30 mm (1.2 inches) in length? (S4.5.1(b)(2)(iii))
 Driver Side: Length_____
 Passenger Side: Length_____
- ☐ Driver Side, Yes – Pass
☐ Driver Side, No – Fail
☐ Passenger Side, Yes – Pass
☐ Passenger Side, No – Fail
- ☒ 3.3 Vehicles certified to meet the requirements of S19, S21, and S23 on 9/1/03 and later. (S4.5.1(b)(3))
- ☒ 3.3.1 Is the label permanently affixed (including permanent marking on the visor material or molding into the visor material) to either side of the sun visor at each front outboard seating position such that it cannot be removed without destroying or defacing the label or the sun visor? (S4.5.1(b)(3))
- ☒ Driver Side, Yes – Pass
☐ Driver Side, No – Fail
☒ Passenger Side, Yes – Pass
☐ Passenger Side, No – Fail
- ☒ 3.3.2 Does the label conform in content to the label shown in either Figure 11 at each front outboard seating position? (S4.5.1(b)(2)) (Vehicles without back seats may omit the statement: "The back seat is the safest place for children." (S4.5.1(b)(3)(iv)) Vehicles without back seats or the back seat is too small to accommodate a rear-facing child restraint may omit the statement "Never put a rear-facing child seat in the front." (S4.5.1(b)(3)(v))



Figure 11. Sun Visor Label Visible when Visor is in Down Position.

		<input checked="" type="checkbox"/>	Driver Side, Yes – Pass
		<input type="checkbox"/>	Driver Side, No – Fail
		<input checked="" type="checkbox"/>	Passenger Side, Yes – Pass
		<input type="checkbox"/>	Passenger Side, No – Fail
<input checked="" type="checkbox"/>	3.3.3		Is the label heading area yellow with the word “WARNING” and the alert symbol in black? (S4.5.1(b)(3)(i))
		<input checked="" type="checkbox"/>	Driver Side, Yes – Pass
		<input type="checkbox"/>	Driver Side, No – Fail
		<input checked="" type="checkbox"/>	Passenger Side, Yes – Pass
		<input type="checkbox"/>	Passenger Side, No – Fail
<input checked="" type="checkbox"/>	3.3.4		Is the message area white with black text? (S4.5.1(b)(3)(ii))
		<input checked="" type="checkbox"/>	Driver Side, Yes – Pass
		<input type="checkbox"/>	Driver Side, No – Fail
		<input checked="" type="checkbox"/>	Passenger Side, Yes – Pass
		<input type="checkbox"/>	Passenger Side, No – Fail
<input checked="" type="checkbox"/>	3.3.5		Is the message area at least 30 cm ² ? (S4.5.1(b)(3)(ii))
			Driver Side: Length <u>8.9 cm</u> , Width <u>3.5 cm</u>
			Passenger Side: Length <u>8.9 cm</u> , Width <u>3.5 cm</u>
			Driver Actual message area <u>31.15 cm²</u>
			Passenger Actual message area <u>31.15 cm²</u>
		<input checked="" type="checkbox"/>	Driver Side, Yes – Pass
		<input type="checkbox"/>	Driver Side, No – Fail
		<input checked="" type="checkbox"/>	Passenger Side, Yes – Pass
		<input type="checkbox"/>	Passenger Side, No – Fail
<input checked="" type="checkbox"/>	3.3.6		Is the pictogram black on a white background? (S4.5.1(b)(3)(iii))
		<input checked="" type="checkbox"/>	Driver Side, Yes – Pass
		<input type="checkbox"/>	Driver Side, No – Fail
		<input checked="" type="checkbox"/>	Passenger Side, Yes – Pass
		<input type="checkbox"/>	Passenger Side, No – Fail
<input checked="" type="checkbox"/>	3.3.7		Is the pictogram at least 30 mm (1.2 inches) in length? (S4.5.1(b)(3)(iii))
			Driver Side: Length <u>32 mm</u>
			Passenger Side: Length <u>32 mm</u>
		<input checked="" type="checkbox"/>	Driver Side, Yes – Pass
		<input type="checkbox"/>	Driver Side, No – Fail
		<input checked="" type="checkbox"/>	Passenger Side, Yes – Pass
		<input type="checkbox"/>	Passenger Side, No – Fail
<input checked="" type="checkbox"/>	3.4		Is the same side of the sun visor that contains the air bag warning label free of other information with the exception of the air bag maintenance label and/or the rollover-warning label? (S4.5.1(b)(5)(i))
		<input checked="" type="checkbox"/>	Driver Side, Yes – Pass
		<input type="checkbox"/>	Driver Side, No – Fail
		<input checked="" type="checkbox"/>	Passenger Side, Yes – Pass
		<input type="checkbox"/>	Passenger Side, No – Fail

<input checked="" type="checkbox"/>	3.5	Is the sun visor free of other information about air bags or the need to wear seat belts with the exception of the air bag alert label and/or the rollover-warning label? (S4.5.1(b)(5)(ii))
	<input checked="" type="checkbox"/>	Driver Side, Yes – Pass
	<input type="checkbox"/>	Driver Side, No – Fail
	<input checked="" type="checkbox"/>	Passenger Side, Yes – Pass
	<input type="checkbox"/>	Passenger Side, No – Fail
<input checked="" type="checkbox"/>	3.6	Does the driver side visor contain a rollover-warning label on the same side of the visor as the air bag warning label?
		<input type="checkbox"/> Yes, go to 3.6.1
		<input checked="" type="checkbox"/> No, go to 4 (skipping 3.6.1 through 3.6.3)
<input type="checkbox"/>	3.6.1	Are both the rollover-warning label and the air bag warning label surrounded by a continuous solid-lined border?
		<input type="checkbox"/> Yes, go to 3.6.2 and skip 3.6.3
		<input type="checkbox"/> No, go to 3.6.3 and skip 3.6.2
<input type="checkbox"/>	3.6.2	Is the shortest distance from the border of the rollover label to the border of the air bag warning label at least 1 cm? (575.105 (d)(1)(iv)(B))
		<input type="text"/> actual distance
<input type="checkbox"/>	3.6.3	Is the shortest distance from any of the lettering or graphics on the rollover-warning label to any of the lettering or graphics of the air bag warning label at least 3 cm? (575.105 (d)(1)(iv)(A))
		<input type="text"/> actual distance
		<input type="checkbox"/> Yes-Pass <input type="checkbox"/> No-FAIL
<input checked="" type="checkbox"/>	4.	Air Bag Alert Label (S4.5.1(c) (A “Rollover Warning Label” or “Rollover Alert Label” may be on the same side of the driver’s sun visor as the “Air Bag Alert Label.” 575.105(d))
<input checked="" type="checkbox"/>	4.1	Is the sun visor warning label visible when the sun visor is in the stowed position?
	<input checked="" type="checkbox"/>	If yes for driver and passenger, go to 5.
	<input checked="" type="checkbox"/>	Driver Side, Yes – Pass
	<input type="checkbox"/>	Driver Side, No – Fail
	<input checked="" type="checkbox"/>	Passenger Side, Yes – Pass
	<input type="checkbox"/>	Passenger Side, No – Fail
<input type="checkbox"/>	4.2	Is the air bag alert label permanently affixed (including permanent marking on the visor material or molding into the visor material) to the sun visor at each front outboard seating position such that it cannot be removed without destroying or defacing the label or the sun visor? (S4.5.1(c))
	<input type="checkbox"/>	Driver Side, Yes – Pass
	<input type="checkbox"/>	Driver Side, No – Fail
	<input type="checkbox"/>	Passenger Side, Yes – Pass
	<input type="checkbox"/>	Passenger Side, No – Fail

☐ 4.3 Is the air bag alert label visible when the visor is in the stowed position? (S4.5.1(c))

- ☐ Driver Side, Yes – Pass
- ☐ Driver Side, No – Fail
- ☐ Passenger Side, Yes – Pass
- ☐ Passenger Side, No – Fail

☐ 4.4 Does the label conform in content to the label shown in Figure 6C? (S4.5.1(c))




Figure 6c. Sun Visor Label Visible When Visor is in Up Position.

- ☐ Driver Side, Yes – Pass
- ☐ Driver Side, No – Fail
- ☐ Passenger Side, Yes – Pass
- ☐ Passenger Side, No – Fail

☐ 4.5 Is the message area black with yellow text? (S4.5.1(c)(1))

- ☐ Driver Side, Yes – Pass
- ☐ Driver Side, No – Fail
- ☐ Passenger Side, Yes – Pass
- ☐ Passenger Side, No – Fail

☐ 4.6 Is the message area at least 20 cm²? (S4.5.1(c)(1))

Driver Side: Length _____, Width _____
Passenger Side: Length _____, Width _____
Actual message area _____ cm²

- ☐ Driver Side, Yes – Pass
- ☐ Driver Side, No – Fail
- ☐ Passenger Side, Yes – Pass
- ☐ Passenger Side, No – Fail

☐ 4.7 Is the pictogram black with a red circle and slash on a white background? (S4.5.1(c)(2))

- ☐ Driver Side, Yes – Pass
- ☐ Driver Side, No – Fail
- ☐ Passenger Side, Yes – Pass
- ☐ Passenger Side, No – Fail

- ☐ 4.8 Is the pictogram at least 20 mm in diameter? (S4.5.1(c)(2))
 Driver Side Diameter _____ mm
 Passenger Side Diameter _____ mm
- ☐ Driver Side, Yes – Pass
☐ Driver Side, No – Fail
☐ Passenger Side, Yes – Pass
☐ Passenger Side, No – Fail
- ☒ 5. Label on the Dashboard
- ☒ 5.1 Is the vehicle certified to meet the requirements of S19, S21, and S23? (Obtain answer from COTR) (S4.5.1(3)(2))
- ☒ Yes, go to 5.1.1 and **skip 5.2**
☐ No, go to 5.2, skipping 5.1.1 through 5.1.6
- ☒ 5.1.1 Does the vehicle have a label on the dash or steering wheel hub? (S4.5.1(e)(2))
- ☒ Yes – Pass
☐ No – Fail
- ☒ 5.1.2 Is the label clearly visible from all front seating positions? (S4.5.1(e)(2))
- ☒ Yes – Pass
☐ No - Fail
- ☒ 5.1.3 Does the label conform in content to the label shown in Figure 9? (S4.5.1(e)(2))
 Vehicles without back seats may omit the statement: "The back seat is the safest place for children." (S4.5.1(e)(2)(iii))
- ☒ Yes – Pass
☐ No - Fail



Figure 9. Removable Label on Dash.

- ☒ 5.1.4 Is the heading area yellow with black text? (S4.5.1(e)(2)(i))
- ☒ Yes – Pass
☐ No - Fail
- ☒ 5.1.5 Is the message white with black text? (S4.5.1(e)(2)(ii))
- ☒ Yes – Pass
☐ No - Fail

- ☒ 5.1.6 Is the message area at least 30 cm²? (S4.5.1(e)(2)(ii))
Length 9.6 cm , Width 3.3 cm
Actual message area 31.68 cm²
- ☒ Yes – Pass
☐ No - Fail
- ☐ 5.2 Does the vehicle have a label on the dash or steering wheel hub? (S4.5.1(e)(1))
- ☐ Yes – Pass
☐ No - Fail
- ☐ 5.2.1 Is the label clearly visible from all front seating positions? (S4.5.1(e)(1))
- ☐ Yes – Pass
☐ No - Fail
- ☐ 5.2.2 Does the label conform in content to the label shown in Figure 7? (S4.5.1(e)(1)(iii))
Vehicles without back seats may omit the statement: "The back seat is the safest place for children." (S4.5.1(e)(2)(iii))
- ☐ Yes – Pass
☐ No - Fail




Figure 7. Removable Label on Dash.

- ☐ 5.2.3 Is the heading area yellow with the word "WARNING" and the alert symbol in black? (S4.5.1(e)(1)(i))
- ☐ Yes – Pass
☐ No - Fail
- ☐ 5.2.4 Is the message white with black text? (S4.5.1(e)(1)(ii))
- ☐ Yes – Pass
☐ No - Fail
- ☐ 5.2.5 Is the message area at least 30 cm²? (S4.5.1(e)(1)(ii))
Length _____, Width _____
Actual message area _____ cm²
- ☐ Yes – Pass
☐ No - Fail

I certify that I have read and performed each instruction.

Signature: Wayne Zuhl

Date: 3/18/04

DATA SHEET 6

FMVSS 208 READINESS INDICATOR (S4.5.2)

Test Vehicle: 2004 Mitsubishi Galant 4 Door
Test Program: FMVSS 208 Compliance
Test Technician: Wayne Dahlke

NHTSA No.: C45603
Test Date: 3/18/04

An occupant restraint system that deploys in the event of a crash shall have a monitoring system with a readiness indicator. A totally mechanical system is exempt from this requirement. (11/8/94 legal interpretation to Lawrence F. Hennegerger on behalf of Breed)

- ☒ 1. Is the system totally mechanical? If Yes, this data sheet is complete.
☐ Yes
☒ No
- ☒ 2. Describe the location of the readiness indicator: Lower right corner of the instrument panel
- ☒ 3. Is the readiness indicator clearly visible to the driver?
☒ Yes – Pass
☐ No - Fail
- ☒ 4. Is a list of the elements in the occupant restraint system, being monitored by the readiness indicator, provided on a label or in the owner's manual?
☒ Yes – Pass
☐ No - Fail
- ☒ 5. Does the vehicle have an on-off switch for the passenger air bag?
☐ If Yes, go to 6
☒ If No, this form is complete.
- ☐ 6. Is the air bag readiness indicator off when the passenger air bag switch is in the off position?
☐ Yes – Pass
☐ No - Fail

REMARKS: NONE

I certify that I have read and performed each instruction.

Signature: Wayne Dahlke

Date: 3/18/04

DATA SHEET 7

PASSENGER AIR BAG MANUAL CUT-OFF DEVICE (S4.5.4)

Test Vehicle: 2004 Mitsubishi Galant 4 Door
 Test Program: FMVSS 208 Compliance
 Test Technician: Wayne Dahlke

NHTSA No.: C45603
 Test Date: 3/18/04

- | | | |
|-------------------------------------|-----|--|
| <input checked="" type="checkbox"/> | 1. | Is the vehicle equipped with an on-off switch that deactivates the air bag installed at the right front outboard seating position? |
| | | <input type="checkbox"/> Yes, go to 2 |
| | | <input checked="" type="checkbox"/> No, this sheet is complete |
| <input type="checkbox"/> | 2. | Does the vehicle have any forward-facing rear designated seating positions? (S4.5.4(a)) |
| | | <input type="checkbox"/> Yes, go to 3 |
| | | <input type="checkbox"/> No, go to 4 |
| <input type="checkbox"/> | 3. | Verification of the lack of room for a child restraint in the rear seat behind the driver's seat. (S4.5.4(b)) |
| <input type="checkbox"/> | 3.1 | Position the seat's adjustable lumbar supports to that the lumbar support is in its lowest, retracted or deflated adjustment position (S8.1.3) |
| | | <input type="checkbox"/> N/A, no lumbar adjustment |
| <input type="checkbox"/> | 3.2 | Position any adjustable parts of the seat that provide additional support so that they are in the lowest or most open adjustment position. (S16.2.10.02) |
| | | <input type="checkbox"/> N/A, no additional support adjustment |
| <input type="checkbox"/> | 3.3 | If the seat cushion adjusts fore and aft, independent of the seat back, set this adjustment to the full rearward position. (S16.2.10.3.1) |
| | | <input type="checkbox"/> N/A, no independent fore-aft seat cushion adjustment |
| <input type="checkbox"/> | 3.4 | If the seat cushion height adjusts independent of the seat back, set this adjustment to the full down position (S16.2.10.3.1) |
| | | <input type="checkbox"/> N/A, no independent seat cushion height adjustment |
| <input type="checkbox"/> | 3.5 | Put the seat in its full rearward position. (S16.2.10.3.1) |
| | | <input type="checkbox"/> N/A, the seat does not have a fore-aft adjustment |
| <input type="checkbox"/> | 3.6 | If the seat height is adjustable, put it in the full down position. (S16.2.10.3.1) |
| | | <input type="checkbox"/> N/A, no seat height adjustment |
| <input type="checkbox"/> | 3.7 | Draw a horizontal reference line on the side of the seat cushion. |
| <input type="checkbox"/> | 3.8 | Using only the controls that change the seat in the fore-aft direction, mark the fore-aft seat positions. Mark the side of the seat and a reference position directly below on a part of the vehicle that does not adjust. For manual seats, move the seat forward one detent at a time and mark each detent as was done for the full rearward position. For power seats, mark only the full rearward, middle, and full forward positions. Label three of the positions with the following: F for full forward, M for mid-position (if there is no mid position, label the closest adjustment position to the rear of the mid-point), and R for full rearward. |
| | | <input type="checkbox"/> N/A – the seat does not have a fore-aft adjustment. |
| <input type="checkbox"/> | 3.9 | Using only the controls that change the seat in the fore-aft direction, place the seat in the full rearward position and then place the seat in the middle fore-aft position. (S8.1.2) |
| | | <input type="checkbox"/> N/A – the seat does not have fore-aft adjustment. |

		Mid position
		If there is no mid position, put the seat in the closest adjustment position to the rear of the midpoint. Describe the location of the seat:
	3.10	If seat adjustments, other than fore-aft, are present and the horizontal reference line is no longer horizontal, use those adjustments to maintain the reference line as closely as possible to the horizontal.
		N/A – No adjustments
		Angle of reference line as tested:
	3.11	The seat back angle, if adjustable, is set at the manufacturer's nominal design riding position for a 50th percentile adult male in the manner specified by the manufacturer. (S4.5.4.1 (b) and S8.1.3)
		N/A – No seat back angle adjustment
		Manufacturers design seat back angle:
		Tested seat back angle:
	3.12	Is the driver seat a bucket seat?
		Yes, go to 3.12.1 and skip 3.12.2
		No, go to 3.12.2 and skip 3.12.1
	3.12.1	Bucket Seats:
	3.12.1.1	Locate and mark a vertical Plane B through the longitudinal centerline of the seat driver's seat cushion. (S22.2.1.3) The longitudinal centerline of a bucket seat cushion is determined at the widest part of the seat cushion. Measure perpendicular to the longitudinal centerline of the vehicle.
		Record the width of the seat:
		Record the distance from the edge of the seat to Plane B:
	3.12.1.2	Locate the longitudinal horizontal line in plane B that is tangent to the highest point of the rear seat cushion behind the driver's seat. Measure along this line from the front of the seat back of the rear seat to the rear of the seat back of the driver's seat.
		Distance (mm):
		Less than 720 mm – Pass
		More then 720 mm – Fail
		Go to 4
	3.12.2	Bench seats (including split bench seats):
	3.12.2.1	Locate and mark a vertical Plane B through the center of the steering wheel parallel to the vehicle longitudinal centerline.
	3.12.2.2	Locate the longitudinal horizontal line in plane B that is tangent to the highest point of the rear seat cushion. Measure along this line from the front of the seat back of the rear seat to the rear of the seat back of the front seat.
		Distance (mm):
		Less than 720 mm – Pass
		More then 720 mm – Fail
		Go to 4
	4.	Does the device turn the air bag on and off using the vehicle's ignition key? (S4.5.4.2)
		Yes – Pass
		No – Fail

<input type="checkbox"/>	5.	Is the on-off device separate from the ignition switch? (S4.5.4.2)
	<input type="checkbox"/>	Yes – Pass
	<input type="checkbox"/>	No – Fail
<input type="checkbox"/>	6.	Is there a telltale light that comes on when the passenger air bag is turned off? (S4.5.4.2)
	<input type="checkbox"/>	Yes – Pass
	<input type="checkbox"/>	No – Fail
<input type="checkbox"/>	7.	Telltale light (S4.5.4.3)
<input type="checkbox"/>	7.1	Is the light yellow? S4.5.4.3(a))
	<input type="checkbox"/>	Yes – Pass
	<input type="checkbox"/>	No – Fail
<input type="checkbox"/>	7.2	Are the words “PASSENGER AIR BAG OFF” (S4.5.4.3(b))
<input type="checkbox"/>	7.2.1	on the telltale?
	<input type="checkbox"/>	Yes – Pass, go to 7.3
	<input type="checkbox"/>	No – go to 7.2.2
<input type="checkbox"/>	7.2.2	within 25 mm of the telltale?
<input type="checkbox"/>		Measurement from the edge of the telltale light (mm):
	<input type="checkbox"/>	Yes – Pass
	<input type="checkbox"/>	No – Fail
<input type="checkbox"/>	7.3	Does the telltale remain illuminated while the air bag is turned off? (S4.5.4.3c)) (Leave the air bag off for 5 minutes.)
	<input type="checkbox"/>	Yes – Pass
	<input type="checkbox"/>	No – Fail
<input type="checkbox"/>	7.4	Is the telltale illuminated while the air bag is turned on? (S4.5.4.3(d))
	<input type="checkbox"/>	Yes – Fail
	<input type="checkbox"/>	No – Pass
<input type="checkbox"/>	7.5	Is the telltale combined with the air bag readiness indicator? (S4.5.4.3(e))
	<input type="checkbox"/>	Yes – Fail
	<input type="checkbox"/>	No – Pass
<input type="checkbox"/>	8.	Owner’s Manual
<input type="checkbox"/>	8.1	Does the owner’s manual contain complete instructions on the operation of the on-off switch? (S4.5.4.4(a))
	<input type="checkbox"/>	Yes – Pass
	<input type="checkbox"/>	No – Fail
<input type="checkbox"/>	8.2	Does the owner’s manual contain a statement that the on-off switch should only be used when a member of one of the following risk groups is occupying the right front passenger seating position? (S4.5.4.4(b))
	Infants:	there is no back seat
		the rear seat is too small to accommodate a child restraint
		there is a medical condition that must be monitored constantly
	Children	there is no back seat
	aged	space is not always available in the rear seat
	1 to 12:	there is a medical condition that must be monitored constantly
	Medical	medical risk causes special risk for passenger
	condition:	greater risk for harm than with the air bag on
	<input type="checkbox"/>	Yes – Pass

<input type="checkbox"/>	8.3	<input type="checkbox"/> No – Fail
		Does the owner's manual contain a warning about the safety consequences of using the on-off switch at other times?
		<input type="checkbox"/> Yes – Pass
		<input type="checkbox"/> No – Fail

REMARKS: NONE

I certify that I have read and performed each instruction.

Signature: Wayne Gahlh

Date: 3/18/04

DATA SHEET 8

LAP BELT LOCKABILITY

**Passenger cars, trucks, buses, and multipurpose passenger
Vehicles with a GVWR of 10,000 pounds or less. (S7.1.1.5)**

Test Vehicle: 2004 Mitsubishi Galant 4 Door
Test Program: FMVSS 208 Compliance
Test Technician: Wayne Dahlke

NHTSA No.: C45603
Test Date: 3/19/04

Complete one of these forms for **each** designated seating position that can be adjusted to forward-facing or that is a forward-facing seat, other than the driver's seat (S7.1.1.5(a), **and** that has seat belt retractors that are not solely automatic locking retractors. (S7.1.1.5(c))

DESIGNATED SEATING POSITION:	Front Passenger
------------------------------	------------------------

<input type="checkbox"/>		N/A – no retractor is at this position	
<input type="checkbox"/>		N/A – the retractor is an automatic locking retractor ONLY	
<input checked="" type="checkbox"/>	1.	Record test fore-aft seat position: Full Rear (S7.1.1.5(c)(1)) (Any position is acceptable)	
<input checked="" type="checkbox"/>	2.	Does the lap belt portion of the seat belt in the forward-facing seat or seat that can be adjusted to forward-facing consist of a locking device that does NOT have to be attached by the vehicle user to the seat belt webbing, retractor, or any other part of the vehicle. (S7.1.1.5 (a))	
		<input checked="" type="checkbox"/> Yes – Pass	
		<input type="checkbox"/> No – Fail	
<input checked="" type="checkbox"/>	3.	Does the lap belt portion of the seat belt in the forward-facing seat or seat that can be adjusted to forward-facing consist of a locking device that does NOT require inverting, twisting or deforming of the belt webbing. (S7.1.1.5 (a))	
		<input checked="" type="checkbox"/> Yes – Pass	
		<input type="checkbox"/> No – Fail	
<input checked="" type="checkbox"/>	4.	Buckle the seat belt. (S7.1.1.5(c)(1))	
<input checked="" type="checkbox"/>	5.	Locate a reference point A on the seat belt buckle. (S7.1.1.5(c)(2))	
<input checked="" type="checkbox"/>	6.	Locate a reference point B on the attachment hardware or retractor assembly at the other end of the lap belt or lap belt portion of the seat belt assembly. (S7.1.1.5(c)(2))	
<input checked="" type="checkbox"/>	7.	Does the vehicle user need to take some action to activate the locking feature on the lap belt portion of the seat belt in any forward-facing seat or seat that can be adjusted to forward-facing?	
		<input checked="" type="checkbox"/> Yes, go to 7.1	
		<input type="checkbox"/> No, go to 8	
<input checked="" type="checkbox"/>	7.1	Does the vehicle owner's manual include a description in words and/or diagrams describing how to activate the locking feature so that the seat belt assembly can tightly secure a child restraint system and how to deactivate the locking feature to remove the child restraint system. (S7.1.1.5(b))	
		<input checked="" type="checkbox"/> Yes – Pass	
		<input type="checkbox"/> No – Fail	
<input checked="" type="checkbox"/>	8.	Adjust the lap belt or lap belt portion of the seat belt assembly according to any procedures recommended in the vehicle owner's manual to activate any locking feature so that the webbing between points A and B is at the maximum length allowed by the belt system. (S7.1.1.5(c)(2) & S7.1.1.5(c)(1))	

- ☒ 9. Measure and record the distance between points A and B along the longitudinal centerline of the webbing for the lap belt or lap belt portion of the seat belt assembly. (S7.1.1.5(c)(2))
- ☒ Measured distance between A and B (inches): 69 inches
- ☒ 10. Readjust the belt system so that the webbing between points A and B is at any length that is 5 inches or more shorter than the maximum length of the webbing. (S7.1.1.5(c)(3))
- ☒ 11. To the lap belt or lap belt portion of the seat belt assembly, apply a preload of 10 pounds using the webbing tension pull device in Figure 5. Apply the load in a vertical plane parallel to the longitudinal axis of the vehicle and passing through the seating reference point of the designated seating position. Apply the preload in a horizontal direction toward the front of the vehicle with a force application angle of not less than 5 degrees nor more than 15 degrees above the horizontal. (S7.1.1.5(c)(4))
- ☒ Measured force application angle (Spec. 5-15 degrees): 8.1 degrees
- ☒ 12. Measure the length between points A and B along the longitudinal centerline of the webbing while the preload is being applied. (S7.1.1.5(c)(4))
- ☒ Measured distance between A and B (inches): 40.5 inches
- ☒ 13. Increase the load to 50 pounds at a rate of no more than 50 pounds per second. Attain the load in not more than 5 seconds. (If webbing sensitive emergency locking retractors are installed as part of the lap belt or lap belt portion of the seat belt assembly, apply the load at a rate less than the threshold value for lock-up specified by the manufacturer.) Maintain the load for at least 5 seconds. Measure and record the distance between points A and B along the longitudinal centerline of the webbing. (S7.1.1.5(c)(5))
- ☒ Record onset rate (lb/sec) (spec. 10 to 50 lb/sec) (S7.1.1.5(c)(5)): 20 lbs./sec.
- ☒ Measured distance between A and B (inches) (S7.1.1.5(c)(6)): 40.75 inches
- ☒ 14. Subtract the measurement in 12 from the measurement in 13. Is the difference 2 inches or less? (S7.1.1.5(c)(7))
- ☒ 13 - 12 = 0.25 inches
- ☒ Yes – Pass
- ☐ No – Fail
- ☒ 15. Subtract the measurement in 13 from the measurement in 9. Is the difference 3 inches or more? (S7.1.1.5(c)(8))
- ☒ 9 - 13 = 28.25 inches
- ☒ Yes – Pass
- ☐ No – Fail

REMARKS: NONE

I certify that I have read and performed each instruction.

Signature: Wayne Gahlh

Date: 3/19/04




Figure 5. - Webbing Tension Pull Device

DATA SHEET 8

LAP BELT LOCKABILITY

**Passenger cars, trucks, buses, and multipurpose passenger
Vehicles with a GVWR of 10,000 pounds or less. (S7.1.1.5)**

Test Vehicle: 2004 Mitsubishi Galant 4 Door
Test Program: FMVSS 208 Compliance
Test Technician: Wayne Dahlke

NHTSA No.: C45603
Test Date: 3/19/04

Complete one of these forms for **each** designated seating position that can be adjusted to forward-facing or that is a forward-facing seat, other than the driver's seat (S7.1.1.5(a), **and** that has seat belt retractors that are not solely automatic locking retractors. (S7.1.1.5(c))

DESIGNATED SEATING POSITION:	Left Rear Passenger
------------------------------	---------------------

<input type="checkbox"/>		N/A – no retractor is at this position	
<input type="checkbox"/>		N/A – the retractor is an automatic locking retractor ONLY	
<input checked="" type="checkbox"/>	1.	Record test fore-aft seat position: Not Adjustable (S7.1.1.5(c)(1)) (Any position is acceptable)	
<input checked="" type="checkbox"/>	2.	Does the lap belt portion of the seat belt in the forward-facing seat or seat that can be adjusted to forward-facing consist of a locking device that does NOT have to be attached by the vehicle user to the seat belt webbing, retractor, or any other part of the vehicle. (S7.1.1.5 (a))	
		<input checked="" type="checkbox"/> Yes – Pass	
		<input type="checkbox"/> No – Fail	
<input checked="" type="checkbox"/>	3.	Does the lap belt portion of the seat belt in the forward-facing seat or seat that can be adjusted to forward-facing consist of a locking device that does NOT require inverting, twisting or deforming of the belt webbing. (S7.1.1.5 (a))	
		<input checked="" type="checkbox"/> Yes – Pass	
		<input type="checkbox"/> No – Fail	
<input checked="" type="checkbox"/>	4.	Buckle the seat belt. (S7.1.1.5(c)(1))	
<input checked="" type="checkbox"/>	5.	Locate a reference point A on the seat belt buckle. (S7.1.1.5(c)(2))	
<input checked="" type="checkbox"/>	6.	Locate a reference point B on the attachment hardware or retractor assembly at the other end of the lap belt or lap belt portion of the seat belt assembly. (S7.1.1.5(c)(2))	
<input checked="" type="checkbox"/>	7.	Does the vehicle user need to take some action to activate the locking feature on the lap belt portion of the seat belt in any forward-facing seat or seat that can be adjusted to forward-facing?	
		<input checked="" type="checkbox"/> Yes, go to 7.1	
		<input type="checkbox"/> No, go to 8	
<input checked="" type="checkbox"/>	7.1	Does the vehicle owner's manual include a description in words and/or diagrams describing how to activate the locking feature so that the seat belt assembly can tightly secure a child restraint system and how to deactivate the locking feature to remove the child restraint system. (S7.1.1.5(b))	
		<input checked="" type="checkbox"/> Yes – Pass	
		<input type="checkbox"/> No – Fail	
<input checked="" type="checkbox"/>	8.	Adjust the lap belt or lap belt portion of the seat belt assembly according to any procedures recommended in the vehicle owner's manual to activate any locking feature so that the webbing between points A and B is at the maximum length allowed by the belt system. (S7.1.1.5(c)(2) & S7.1.1.5(c)(1))	

- ☒ 9. Measure and record the distance between points A and B along the longitudinal centerline of the webbing for the lap belt or lap belt portion of the seat belt assembly. (S7.1.1.5(c)(2))
- ☒ Measured distance between A and B (inches): 67.25 inches
- ☒ 10. Readjust the belt system so that the webbing between points A and B is at any length that is 5 inches or more shorter than the maximum length of the webbing. (S7.1.1.5(c)(3))
- ☒ 11. To the lap belt or lap belt portion of the seat belt assembly, apply a preload of 10 pounds using the webbing tension pull device in Figure 5. Apply the load in a vertical plane parallel to the longitudinal axis of the vehicle and passing through the seating reference point of the designated seating position. Apply the preload in a horizontal direction toward the front of the vehicle with a force application angle of not less than 5 degrees nor more than 15 degrees above the horizontal. (S7.1.1.5(c)(4))
- ☒ Measured force application angle (Spec. 5-15 degrees): 13.4 degrees
- ☒ 12. Measure the length between points A and B along the longitudinal centerline of the webbing while the preload is being applied. (S7.1.1.5(c)(4))
- ☒ Measured distance between A and B (inches): 32 inches
- ☒ 13. Increase the load to 50 pounds at a rate of no more than 50 pounds per second. Attain the load in not more than 5 seconds. (If webbing sensitive emergency locking retractors are installed as part of the lap belt or lap belt portion of the seat belt assembly, apply the load at a rate less than the threshold value for lock-up specified by the manufacturer.) Maintain the load for at least 5 seconds. Measure and record the distance between points A and B along the longitudinal centerline of the webbing. (S7.1.1.5(c)(5))
- ☒ Record onset rate (lb/sec) (spec. 10 to 50 lb/sec) (S7.1.1.5(c)(5)): 20 lbs./sec.
- ☒ Measured distance between A and B (inches) (S7.1.1.5(c)(6)): 33.25 inches
- ☒ 14. Subtract the measurement in 12 from the measurement in 13. Is the difference 2 inches or less? (S7.1.1.5(c)(7))
- ☒ $13 - 12 = 1.25$ inches
- ☒ Yes – Pass
- ☐ No – Fail
- ☒ 15. Subtract the measurement in 13 from the measurement in 9. Is the difference 3 inches or more? (S7.1.1.5(c)(8))
- ☒ $9 - 13 = 34$ inches
- ☒ Yes – Pass
- ☐ No – Fail

REMARKS: NONE

I certify that I have read and performed each instruction.

Signature: Wayne Zuhl

Date: 3/19/04




Figure 5. - Webbing Tension Pull Device

DATA SHEET 8

LAP BELT LOCKABILITY

**Passenger cars, trucks, buses, and multipurpose passenger
Vehicles with a GVWR of 10,000 pounds or less. (S7.1.1.5)**

Test Vehicle: 2004 Mitsubishi Galant 4 Door
Test Program: FMVSS 208 Compliance
Test Technician: Wayne Dahlke

NHTSA No.: C45603
Test Date: 3/19/04

Complete one of these forms for **each** designated seating position that can be adjusted to forward-facing or that is a forward-facing seat, other than the driver's seat (S7.1.1.5(a), **and** that has seat belt retractors that are not solely automatic locking retractors. (S7.1.1.5(c))

DESIGNATED SEATING POSITION:	Center Rear Passenger
------------------------------	-----------------------

<input type="checkbox"/>		N/A – no retractor is at this position	
<input type="checkbox"/>		N/A – the retractor is an automatic locking retractor ONLY	
<input checked="" type="checkbox"/>	1.	Record test fore-aft seat position: Not Adjustable (S7.1.1.5(c)(1)) (Any position is acceptable)	
<input checked="" type="checkbox"/>	2.	Does the lap belt portion of the seat belt in the forward-facing seat or seat that can be adjusted to forward-facing consist of a locking device that does NOT have to be attached by the vehicle user to the seat belt webbing, retractor, or any other part of the vehicle. (S7.1.1.5 (a))	
		<input checked="" type="checkbox"/> Yes – Pass	
		<input type="checkbox"/> No – Fail	
<input checked="" type="checkbox"/>	3.	Does the lap belt portion of the seat belt in the forward-facing seat or seat that can be adjusted to forward-facing consist of a locking device that does NOT require inverting, twisting or deforming of the belt webbing. (S7.1.1.5 (a))	
		<input checked="" type="checkbox"/> Yes – Pass	
		<input type="checkbox"/> No – Fail	
<input checked="" type="checkbox"/>	4.	Buckle the seat belt. (S7.1.1.5(c)(1))	
<input checked="" type="checkbox"/>	5.	Locate a reference point A on the seat belt buckle. (S7.1.1.5(c)(2))	
<input checked="" type="checkbox"/>	6.	Locate a reference point B on the attachment hardware or retractor assembly at the other end of the lap belt or lap belt portion of the seat belt assembly. (S7.1.1.5(c)(2))	
<input checked="" type="checkbox"/>	7.	Does the vehicle user need to take some action to activate the locking feature on the lap belt portion of the seat belt in any forward-facing seat or seat that can be adjusted to forward-facing?	
		<input checked="" type="checkbox"/> Yes, go to 7.1	
		<input type="checkbox"/> No, go to 8	
<input checked="" type="checkbox"/>	7.1	Does the vehicle owner's manual include a description in words and/or diagrams describing how to activate the locking feature so that the seat belt assembly can tightly secure a child restraint system and how to deactivate the locking feature to remove the child restraint system. (S7.1.1.5(b))	
		<input checked="" type="checkbox"/> Yes – Pass	
		<input type="checkbox"/> No – Fail	
<input checked="" type="checkbox"/>	8.	Adjust the lap belt or lap belt portion of the seat belt assembly according to any procedures recommended in the vehicle owner's manual to activate any locking feature so that the webbing between points A and B is at the maximum length allowed by the belt system. (S7.1.1.5(c)(2) & S7.1.1.5(c)(1))	

- ☒ 9. Measure and record the distance between points A and B along the longitudinal centerline of the webbing for the lap belt or lap belt portion of the seat belt assembly. (S7.1.1.5(c)(2))
- ☒ Measured distance between A and B (inches): 68 inches
- ☒ 10. Readjust the belt system so that the webbing between points A and B is at any length that is 5 inches or more shorter than the maximum length of the webbing. (S7.1.1.5(c)(3))
- ☒ 11. To the lap belt or lap belt portion of the seat belt assembly, apply a preload of 10 pounds using the webbing tension pull device in Figure 5. Apply the load in a vertical plane parallel to the longitudinal axis of the vehicle and passing through the seating reference point of the designated seating position. Apply the preload in a horizontal direction toward the front of the vehicle with a force application angle of not less than 5 degrees nor more than 15 degrees above the horizontal. (S7.1.1.5(c)(4))
- ☒ Measured force application angle (Spec. 5-15 degrees): 6.2 degrees
- ☒ 12. Measure the length between points A and B along the longitudinal centerline of the webbing while the preload is being applied. (S7.1.1.5(c)(4))
- ☒ Measured distance between A and B (inches): 29.75 inches
- ☒ 13. Increase the load to 50 pounds at a rate of no more than 50 pounds per second. Attain the load in not more than 5 seconds. (If webbing sensitive emergency locking retractors are installed as part of the lap belt or lap belt portion of the seat belt assembly, apply the load at a rate less than the threshold value for lock-up specified by the manufacturer.) Maintain the load for at least 5 seconds. Measure and record the distance between points A and B along the longitudinal centerline of the webbing. (S7.1.1.5(c)(5))
- ☒ Record onset rate (lb/sec) (spec. 10 to 50 lb/sec) (S7.1.1.5(c)(5)): 20 lbs./sec.
- ☒ Measured distance between A and B (inches) (S7.1.1.5(c)(6)): 31.5 inches
- ☒ 14. Subtract the measurement in 12 from the measurement in 13. Is the difference 2 inches or less? (S7.1.1.5(c)(7))
- ☒ 13 - 12 = 1.75 inches
- ☒ Yes – Pass
- ☐ No – Fail
- ☒ 15. Subtract the measurement in 13 from the measurement in 9. Is the difference 3 inches or more? (S7.1.1.5(c)(8))
- ☒ 9 - 13 = 36.5 inches
- ☒ Yes – Pass
- ☐ No – Fail

REMARKS: NONE

I certify that I have read and performed each instruction.

Signature: Wayne Gahl

Date: 3/19/04




Figure 5. - Webbing Tension Pull Device

DATA SHEET 8

LAP BELT LOCKABILITY

**Passenger cars, trucks, buses, and multipurpose passenger
Vehicles with a GVWR of 10,000 pounds or less. (S7.1.1.5)**

Test Vehicle: 2004 Mitsubishi Galant 4 Door
Test Program: FMVSS 208 Compliance
Test Technician: Wayne Dahlke

NHTSA No.: C45603
Test Date: 3/19/04

Complete one of these forms for **each** designated seating position that can be adjusted to forward-facing or that is a forward-facing seat, other than the driver's seat (S7.1.1.5(a), **and** that has seat belt retractors that are not solely automatic locking retractors. (S7.1.1.5(c))

DESIGNATED SEATING POSITION:	Right Rear Passenger
------------------------------	-----------------------------

<input type="checkbox"/>		N/A – no retractor is at this position
<input type="checkbox"/>		N/A – the retractor is an automatic locking retractor ONLY
<input checked="" type="checkbox"/>	1.	Record test fore-aft seat position: Not Adjustable (S7.1.1.5(c)(1)) (Any position is acceptable)
<input checked="" type="checkbox"/>	2.	Does the lap belt portion of the seat belt in the forward-facing seat or seat that can be adjusted to forward-facing consist of a locking device that does NOT have to be attached by the vehicle user to the seat belt webbing, retractor, or any other part of the vehicle. (S7.1.1.5 (a))
		<input checked="" type="checkbox"/> Yes – Pass
		<input type="checkbox"/> No – Fail
<input checked="" type="checkbox"/>	3.	Does the lap belt portion of the seat belt in the forward-facing seat or seat that can be adjusted to forward-facing consist of a locking device that does NOT require inverting, twisting or deforming of the belt webbing. (S7.1.1.5 (a))
		<input checked="" type="checkbox"/> Yes – Pass
		<input type="checkbox"/> No – Fail
<input checked="" type="checkbox"/>	4.	Buckle the seat belt. (S7.1.1.5(c)(1))
<input checked="" type="checkbox"/>	5.	Locate a reference point A on the seat belt buckle. (S7.1.1.5(c)(2))
<input checked="" type="checkbox"/>	6.	Locate a reference point B on the attachment hardware or retractor assembly at the other end of the lap belt or lap belt portion of the seat belt assembly. (S7.1.1.5(c)(2))
<input checked="" type="checkbox"/>	7.	Does the vehicle user need to take some action to activate the locking feature on the lap belt portion of the seat belt in any forward-facing seat or seat that can be adjusted to forward-facing?
		<input checked="" type="checkbox"/> Yes, go to 7.1
		<input type="checkbox"/> No, go to 8
<input checked="" type="checkbox"/>	7.1	Does the vehicle owner's manual include a description in words and/or diagrams describing how to activate the locking feature so that the seat belt assembly can tightly secure a child restraint system and how to deactivate the locking feature to remove the child restraint system. (S7.1.1.5(b))
		<input checked="" type="checkbox"/> Yes – Pass
		<input type="checkbox"/> No – Fail
<input checked="" type="checkbox"/>	8.	Adjust the lap belt or lap belt portion of the seat belt assembly according to any procedures recommended in the vehicle owner's manual to activate any locking feature so that the webbing between points A and B is at the maximum length allowed by the belt system. (S7.1.1.5(c)(2) & S7.1.1.5(c)(1))

- ☒ 9. Measure and record the distance between points A and B along the longitudinal centerline of the webbing for the lap belt or lap belt portion of the seat belt assembly. (S7.1.1.5(c)(2))
- ☒ Measured distance between A and B (inches): 69.25 inches
- ☒ 10. Readjust the belt system so that the webbing between points A and B is at any length that is 5 inches or more shorter than the maximum length of the webbing. (S7.1.1.5(c)(3))
- ☒ 11. To the lap belt or lap belt portion of the seat belt assembly, apply a preload of 10 pounds using the webbing tension pull device in Figure 5. Apply the load in a vertical plane parallel to the longitudinal axis of the vehicle and passing through the seating reference point of the designated seating position. Apply the preload in a horizontal direction toward the front of the vehicle with a force application angle of not less than 5 degrees nor more than 15 degrees above the horizontal. (S7.1.1.5(c)(4))
- ☒ Measured force application angle (Spec. 5-15 degrees): 9 degrees
- ☒ 12. Measure the length between points A and B along the longitudinal centerline of the webbing while the preload is being applied. (S7.1.1.5(c)(4))
- ☒ Measured distance between A and B (inches): 30.5 inches
- ☒ 13. Increase the load to 50 pounds at a rate of no more than 50 pounds per second. Attain the load in not more than 5 seconds. (If webbing sensitive emergency locking retractors are installed as part of the lap belt or lap belt portion of the seat belt assembly, apply the load at a rate less than the threshold value for lock-up specified by the manufacturer.) Maintain the load for at least 5 seconds. Measure and record the distance between points A and B along the longitudinal centerline of the webbing. (S7.1.1.5(c)(5))
- ☒ Record onset rate (lb/sec) (spec. 10 to 50 lb/sec) (S7.1.1.5(c)(5)): 20 lbs./sec.
- ☒ Measured distance between A and B (inches) (S7.1.1.5(c)(6)): 32 inches
- ☒ 14. Subtract the measurement in 12 from the measurement in 13. Is the difference 2 inches or less? (S7.1.1.5(c)(7))
- ☒ 13 - 12 = 1.5 inches
- ☒ Yes – Pass
- ☐ No – Fail
- ☒ 15. Subtract the measurement in 13 from the measurement in 9. Is the difference 3 inches or more? (S7.1.1.5(c)(8))
- ☒ 9 - 13 = 37.25 inches
- ☒ Yes – Pass
- ☐ No – Fail

REMARKS: NONE

I certify that I have read and performed each instruction.

Signature: Wayne Gahl

Date: 3/19/04




Figure 5. - Webbing Tension Pull Device

DATA SHEET 9

FMVSS 208 SEAT BELT WARNING SYSTEM CHECK (S7.3)

Test Vehicle: 2004 Mitsubishi Galant 4 Door
 Test Program: FMVSS 208 Compliance
 Test Technician: Wayne Dahlke

NHTSA No.: C45603
 Test Date: 3/19/04

- | | | |
|----------|-----|---|
| X | 1. | The occupant is in the driver's seat. |
| X | 2. | The seat belt is in the stowed position. |
| X | 3. | The key is in the "on" or "start" position. |
| X | 4. | The time duration of the audible signal beginning with key "on" or "start" is |
| X | | Seconds: 6.0 |
| X | 5. | The occupant is in the driver's seat. |
| X | 6. | The seat belt is in the stowed position. |
| X | 7. | The key is in the "on" or "start" position. |
| X | 8. | The time duration of the warning light beginning with key "on" or "start" is |
| X | | Seconds: Stays On |
| X | 9. | The occupant is in the driver's seat. |
| X | 10. | The seat belt is in the latched position and with at least 4 inches of belt webbing extended. |
| X | 11. | The key is in the "on" or "start" position. |
| X | 12. | The time duration of the audible signal beginning with key "on" or "start" is |
| X | | Seconds: 0.0 |
| X | 13. | The occupant is in the driver's seat. |
| X | 14. | The seat belt is in the latched position and with at least 4 inches of belt webbing extended. |
| X | 15. | The key is in the "on" or "start" position. |
| X | 16. | The time duration of the warning light beginning with key "on" or "start" is |
| X | | Seconds: 0.0 |
| X | 17. | Complete the following table with the data from 4, 8, 12, and 16 to determine which option is used. |

		Warning light	Warning light specification	Audible signal	Audible signal specification*
S7.3 (a)(1)	Belt latched & key on or start	Item 16: 0.0		Item 12: 0.0	0 seconds**
	Belt stowed & key on or start	Item 8: Stays On	60 seconds minimum	Item 4: 6.0	4 to 8 seconds
S7.3 (a)(2)	Belt latched & key on or start	Item 16: 0.0	4 to 8 seconds	Item 12: 0.0	0 seconds**
	Belt stowed & key on or start	Item 8: Stays On	4 to 8 seconds	Item 4: 6.0	4 to 8 seconds

* 49 USCS @ 30124 does NOT allow an audible signal to operate for more than 8 seconds.

** 0 seconds means the light or audible signal are NOT permitted to operate under these conditions.
 See 7/12/00 interpretation to Patrick Raheer of Hogan and Hartson

- ☒ 18. The seat belt warning system meets the requirements of (manufacturers may comply with either section)
- | | |
|-------------------------------------|--|
| <input checked="" type="checkbox"/> | S7.3 (a)(1) |
| <input type="checkbox"/> | S7.3 (a)(2) |
| <input type="checkbox"/> | FAIL – does not meet the requirements of either option |
- ☒ 19. Note wording of visual warning: (S7.3(a)(1) and S7.3(a)(2))
- | | |
|-------------------------------------|---|
| <input type="checkbox"/> | Fasten seat belts |
| <input type="checkbox"/> | Fasten belts |
| <input checked="" type="checkbox"/> | Symbol 101 |
| <input type="checkbox"/> | FAIL – does not used any of the above working or symbol |

REMARKS: NONE

I certify that I have read and performed each instruction.

Signature: Wayne Zuhl

Date: 3/19/04

DATA SHEET 10 **BELT CONTACT FORCE (S7.4.3)**

Test Vehicle: 2004 Mitsubishi Galant 4 Door
 Test Program: FMVSS 208 Compliance
 Test Technician: Wayne Dahlke

NHTSA No.: C45603
 Test Date: 3/19/04

Test all Type 2 seat belts other than those in walk-in van-type vehicles and those at front outboard designated seating positions in passenger cars. Complete a form for each applicable seat belt.

DESIGNATED SEATING POSITION:	Left Rear Passenger
------------------------------	---------------------

- | | | |
|-----------|-----|--|
| X | 1. | Does the vehicle incorporate a webbing tension-relieving device? |
| | | <input type="checkbox"/> Yes, this form is complete |
| | | X No, continue with this check sheet |
| X | 2. | Position the seat's adjustable lumbar supports so that the lumbar support is in its lowest, retracted or deflated adjustment position. (S8.1.3) |
| | | X N/A, no lumbar adjustment |
| X | 3. | Position any adjustable parts of the seat that provide additional support so that they are in the lowest or most open adjustment position. (S16.2.10.2) |
| | | X N/A, no additional support adjustment |
| X | 4. | Position any adjustable parts of the seat that provide additional support so that they are in the lowest or most open adjustment position. (S16.2.10.2) |
| | | X N/A, no independent fore-aft seat cushion adjustment |
| X | 5. | If the seat cushion adjusts fore and aft, independent of the seat back, set this adjustment to the full rearward position. (S16.2.10.3.1) |
| | | X N/A, no independent seat cushion height adjustment |
| X | 6. | Put the seat in its full rearward position. (S16.2.10.3.1) |
| | | X N/A, the seat does not have a fore-aft adjustment |
| X | 7. | If the seat cushion height adjusts independent of the seat back, set this adjustment to the full down position. (S16.2.10.3.1) |
| | | X N/A, no seat height adjustment |
| NA | 8. | Draw a horizontal reference line on the side of the seat cushion. |
| X | 9. | Using only the controls that change the seat in the fore-aft direction, mark the fore-aft seat positions. Mark the side of the seat and a reference position directly below on a part of the vehicle that does not adjust. For manual seats, move the seat forward one detent at a time and mark each detent as was done for the full rearward position. For power seats, mark only the full rearward, middle, and full forward positions. Label three of the positions with the following: F for full forward, M for mid-position (if there is no mid position, label the closest adjustment position to the rear of the mid-point), and R for full rearward. |
| | | X N/A, the seat does not have a fore-aft adjustment |
| X | 10. | Using only the controls that change the seat in the fore-aft direction, place the seat in the full rearward position and then place the seat in the middle fore-aft position for this test. (S8.1.2) |

	<input type="checkbox"/>	Mid position
		If there is no mid position, put the seat in the closest adjustment position to the rear of the midpoint. Describe the location of the seat: Not adjustable
<input checked="" type="checkbox"/>	11.	If seat adjustments other than fore-aft are present and the horizontal reference line is no longer horizontal, use those adjustments to maintain the reference line as closely as possible to the horizontal. (S16.2.10.3.2.1)
	<input checked="" type="checkbox"/>	N/A, no adjustments
		Reference line angle as tested: N/A
<input checked="" type="checkbox"/>	12.	The seat back angle, if adjustable, is set at the manufacturer's nominal design riding position for a 50th percentile adult male in the manner specified by the manufacturer. (S4.5.4.1 (b) and S8.1.3)
	<input checked="" type="checkbox"/>	N/A, no seat back angle adjustment
<input type="checkbox"/>		Manufacturer's design seat back angle:
<input type="checkbox"/>		Tested seat back angle:
<input checked="" type="checkbox"/>	13.	Position the test dummies according to dummy position placement instructions in Appendix F.
<input checked="" type="checkbox"/>	14.	Fasten the seat belt latch.
<input checked="" type="checkbox"/>	15.	Pull either 12 inches of belt webbing or the maximum available amount of belt webbing, whichever is less, from the retractor and then release it, allowing the belt webbing to return to the dummy's chest.
<input checked="" type="checkbox"/>	16.	Locate the point where the centerline of the upper torso belt webbing crosses the midsagittal line on the dummy's chest. At that point pull the belt webbing out 3 inches from the dummy's chest and release until it is within one inch from the dummy's chest. (S10.8) Using a force measuring gage with a full scale range of no more than 1.5 pounds, measure the contact force perpendicular to the dummy's chest exerted by the belt webbing.
<input checked="" type="checkbox"/>		Contact Force (lb): 0.5 lb
	<input checked="" type="checkbox"/>	0.0 to 0.7 pounds – Pass
	<input type="checkbox"/>	Greater than 0.7 pounds - Fail

REMARKS: NONE

I certify that I have read and performed each instruction.

Signature: Wayne Zuhl

Date: 3/19/04

DATA SHEET 10 **BELT CONTACT FORCE (S7.4.3)**

Test Vehicle: 2004 Mitsubishi Galant 4 Door
 Test Program: FMVSS 208 Compliance
 Test Technician: Wayne Dahlke

NHTSA No.: C45603
 Test Date: 3/19/04

Test all Type 2 seat belts other than those in walk-in van-type vehicles and those at front outboard designated seating positions in passenger cars. Complete a form for each applicable seat belt.

DESIGNATED SEATING POSITION:	Center Rear Passenger
------------------------------	-----------------------

- | | | |
|-----------|-----|--|
| X | 1. | Does the vehicle incorporate a webbing tension-relieving device?
<div style="margin-left: 20px;"> <input type="checkbox"/> Yes, this form is complete
 <input checked="" type="checkbox"/> No, continue with this check sheet </div> |
| X | 2. | Position the seat's adjustable lumbar supports so that the lumbar support is in its lowest, retracted or deflated adjustment position. (S8.1.3)
<div style="margin-left: 20px;"> <input checked="" type="checkbox"/> N/A, no lumbar adjustment </div> |
| X | 3. | Position any adjustable parts of the seat that provide additional support so that they are in the lowest or most open adjustment position. (S16.2.10.2)
<div style="margin-left: 20px;"> <input checked="" type="checkbox"/> N/A, no additional support adjustment </div> |
| X | 4. | Position any adjustable parts of the seat that provide additional support so that they are in the lowest or most open adjustment position. (S16.2.10.2)
<div style="margin-left: 20px;"> <input checked="" type="checkbox"/> N/A, no independent fore-aft seat cushion adjustment </div> |
| X | 5. | If the seat cushion adjusts fore and aft, independent of the seat back, set this adjustment to the full rearward position. (S16.2.10.3.1)
<div style="margin-left: 20px;"> <input checked="" type="checkbox"/> N/A, no independent seat cushion height adjustment </div> |
| X | 6. | Put the seat in its full rearward position. (S16.2.10.3.1)
<div style="margin-left: 20px;"> <input checked="" type="checkbox"/> N/A, the seat does not have a fore-aft adjustment </div> |
| X | 7. | If the seat cushion height adjusts independent of the seat back, set this adjustment to the full down position. (S16.2.10.3.1)
<div style="margin-left: 20px;"> <input checked="" type="checkbox"/> N/A, no seat height adjustment </div> |
| NA | 8. | Draw a horizontal reference line on the side of the seat cushion. |
| X | 9. | Using only the controls that change the seat in the fore-aft direction, mark the fore-aft seat positions. Mark the side of the seat and a reference position directly below on a part of the vehicle that does not adjust. For manual seats, move the seat forward one detent at a time and mark each detent as was done for the full rearward position. For power seats, mark only the full rearward, middle, and full forward positions. Label three of the positions with the following: F for full forward, M for mid-position (if there is no mid position, label the closest adjustment position to the rear of the mid-point), and R for full rearward. |
| X | 10. | Using only the controls that change the seat in the fore-aft direction, place the seat in the full rearward position and then place the seat in the middle fore-aft position for this test. (S8.1.2)
<div style="margin-left: 20px;"> <input checked="" type="checkbox"/> N/A, the seat does not have a fore-aft adjustment </div> |

- ☒ Mid position
If there is no mid position, put the seat in the closest adjustment position to the rear of the midpoint. Describe the location of the seat: Not adjustable
- ☒ 11. If seat adjustments other than fore-aft are present and the horizontal reference line is no longer horizontal, use those adjustments to maintain the reference line as closely as possible to the horizontal. (S16.2.10.3.2.1)
- ☒ N/A, no adjustments
Reference line angle as tested: N/A
- ☒ 12. The seat back angle, if adjustable, is set at the manufacturer's nominal design riding position for a 50th percentile adult male in the manner specified by the manufacturer. (S4.5.4.1 (b) and S8.1.3)
- ☒ N/A, no seat back angle adjustment
Manufacturer's design seat back angle:
- ☒
☒
☒ 13. Tested seat back angle:
Position the test dummies according to dummy position placement instructions in Appendix F.
- ☒ 14. Fasten the seat belt latch.
- ☒ 15. Pull either 12 inches of belt webbing or the maximum available amount of belt webbing, whichever is less, from the retractor and then release it, allowing the belt webbing to return to the dummy's chest.
- ☒ 16. Locate the point where the centerline of the upper torso belt webbing crosses the midsagittal line on the dummy's chest. At that point pull the belt webbing out 3 inches from the dummy's chest and release until it is within one inch from the dummy's chest. (S10.8) Using a force measuring gage with a full scale range of no more than 1.5 pounds, measure the contact force perpendicular to the dummy's chest exerted by the belt webbing.
- ☒ Contact Force (lb): 0.6
- ☒ 0.0 to 0.7 pounds – Pass
☐ Greater than 0.7 pounds - Fail

REMARKS: NONE

I certify that I have read and performed each instruction.

Signature: Wayne Zuhl

Date: 3/19/04

DATA SHEET 10

BELT CONTACT FORCE (S7.4.3)

Test Vehicle: 2004 Mitsubishi Galant 4 Door
 Test Program: FMVSS 208 Compliance
 Test Technician: Wayne Dahlke

NHTSA No.: C45603
 Test Date: 3/19/04

Test all Type 2 seat belts other than those in walk-in van-type vehicles and those at front outboard designated seating positions in passenger cars. Complete a form for each applicable seat belt.

DESIGNATED SEATING POSITION:	Right Rear Passenger
------------------------------	----------------------

- | | | |
|-----------|-----|--|
| X | 1. | Does the vehicle incorporate a webbing tension-relieving device?
<div style="margin-left: 20px;"> <input type="checkbox"/> Yes, this form is complete
 <input checked="" type="checkbox"/> No, continue with this check sheet </div> |
| X | 2. | Position the seat's adjustable lumbar supports so that the lumbar support is in its lowest, retracted or deflated adjustment position. (S8.1.3)
<div style="margin-left: 20px;"> <input checked="" type="checkbox"/> N/A, no lumbar adjustment </div> |
| X | 3. | Position any adjustable parts of the seat that provide additional support so that they are in the lowest or most open adjustment position. (S16.2.10.2)
<div style="margin-left: 20px;"> <input checked="" type="checkbox"/> N/A, no additional support adjustment </div> |
| X | 4. | Position any adjustable parts of the seat that provide additional support so that they are in the lowest or most open adjustment position. (S16.2.10.2)
<div style="margin-left: 20px;"> <input checked="" type="checkbox"/> N/A, no independent fore-aft seat cushion adjustment </div> |
| X | 5. | If the seat cushion adjusts fore and aft, independent of the seat back, set this adjustment to the full rearward position. (S16.2.10.3.1)
<div style="margin-left: 20px;"> <input checked="" type="checkbox"/> N/A, no independent seat cushion height adjustment </div> |
| X | 6. | Put the seat in its full rearward position. (S16.2.10.3.1)
<div style="margin-left: 20px;"> <input checked="" type="checkbox"/> N/A, the seat does not have a fore-aft adjustment </div> |
| X | 7. | If the seat cushion height adjusts independent of the seat back, set this adjustment to the full down position. (S16.2.10.3.1)
<div style="margin-left: 20px;"> <input checked="" type="checkbox"/> N/A, no seat height adjustment </div> |
| NA | 8. | Draw a horizontal reference line on the side of the seat cushion. |
| X | 9. | Using only the controls that change the seat in the fore-aft direction, mark the fore-aft seat positions. Mark the side of the seat and a reference position directly below on a part of the vehicle that does not adjust. For manual seats, move the seat forward one detent at a time and mark each detent as was done for the full rearward position. For power seats, mark only the full rearward, middle, and full forward positions. Label three of the positions with the following: F for full forward, M for mid-position (if there is no mid position, label the closest adjustment position to the rear of the mid-point), and R for full rearward. |
| X | 10. | Using only the controls that change the seat in the fore-aft direction, place the seat in the full rearward position and then place the seat in the middle fore-aft position for this test. (S8.1.2)
<div style="margin-left: 20px;"> <input checked="" type="checkbox"/> N/A, the seat does not have a fore-aft adjustment </div> |

	<input type="checkbox"/>	Mid position
		If there is no mid position, put the seat in the closest adjustment position to the rear of the midpoint. Describe the location of the seat: Not adjustable
<input checked="" type="checkbox"/>	11.	If seat adjustments other than fore-aft are present and the horizontal reference line is no longer horizontal, use those adjustments to maintain the reference line as closely as possible to the horizontal. (S16.2.10.3.2.1)
	<input checked="" type="checkbox"/>	N/A, no adjustments
		Reference line angle as tested: N/A
<input checked="" type="checkbox"/>	12.	The seat back angle, if adjustable, is set at the manufacturer's nominal design riding position for a 50th percentile adult male in the manner specified by the manufacturer. (S4.5.4.1 (b) and S8.1.3)
	<input checked="" type="checkbox"/>	N/A, no seat back angle adjustment
<input checked="" type="checkbox"/>		Manufacturer's design seat back angle:
<input checked="" type="checkbox"/>		Tested seat back angle:
<input checked="" type="checkbox"/>	13.	Position the test dummies according to dummy position placement instructions in Appendix F.
<input checked="" type="checkbox"/>	14.	Fasten the seat belt latch.
<input checked="" type="checkbox"/>	15.	Pull either 12 inches of belt webbing or the maximum available amount of belt webbing, whichever is less, from the retractor and then release it, allowing the belt webbing to return to the dummy's chest.
<input checked="" type="checkbox"/>	16.	Locate the point where the centerline of the upper torso belt webbing crosses the midsagittal line on the dummy's chest. At that point pull the belt webbing out 3 inches from the dummy's chest and release until it is within one inch from the dummy's chest. (S10.8) Using a force measuring gage with a full scale range of no more than 1.5 pounds, measure the contact force perpendicular to the dummy's chest exerted by the belt webbing.
<input checked="" type="checkbox"/>		Contact Force (lb): 0.55
	<input checked="" type="checkbox"/>	0.0 to 0.7 pounds – Pass
	<input type="checkbox"/>	Greater than 0.7 pounds - Fail

REMARKS: NONE

I certify that I have read and performed each instruction.

Signature: Wayne Zuhl

Date: 3/19/04

DATA SHEET 11

LATCH PLATE ACCESS (S7.4.4)

Test Vehicle: 2004 Mitsubishi Galant 4 Door
 Test Program: FMVSS 208 Compliance
 Test Technician: Wayne Dahlke

NHTSA No.: C45603
 Test Date: 3/19/04

Test all front outboard seat belts **other than those in** walk-in van-type vehicles and those at front outboard designated seating positions in **passenger cars**. Complete a form for each applicable seat belt.

DESIGNATED SEATING POSITION:	Not Applicable For Any Position - Passenger Car
------------------------------	---

- | | | |
|--|-----|--|
| <input style="width: 30px; height: 15px; background-color: yellow; border: 1px solid black;" type="checkbox"/> | 1. | Position the seat's adjustable lumbar supports so that the lumbar support is in its lowest, retracted or deflated adjustment position. (8.1.3) |
| | | <input style="width: 30px; height: 15px; background-color: yellow; border: 1px solid black;" type="checkbox"/> N/A, no lumbar adjustment |
| <input style="width: 30px; height: 15px; background-color: yellow; border: 1px solid black;" type="checkbox"/> | 2. | Position any adjustable parts of the seat that provide additional support so that they are in the lowest or most open adjustment position. (S16.2.10.2) |
| | | <input style="width: 30px; height: 15px; background-color: yellow; border: 1px solid black;" type="checkbox"/> N/A, no additional support adjustment |
| <input style="width: 30px; height: 15px; background-color: yellow; border: 1px solid black;" type="checkbox"/> | 3. | If the seat cushion adjusts fore and aft, independent of the seat back, set this adjustment to the full rearward position. (S16.2.10.3.1) |
| | | <input style="width: 30px; height: 15px; background-color: yellow; border: 1px solid black;" type="checkbox"/> N/A, no independent fore-aft seat cushion adjustment |
| <input style="width: 30px; height: 15px; background-color: yellow; border: 1px solid black;" type="checkbox"/> | 4. | If the seat cushion height adjusts independent of the seat back, set this adjustment to the full down position. (S16.2.10.3.1) |
| | | <input style="width: 30px; height: 15px; background-color: yellow; border: 1px solid black;" type="checkbox"/> N/A, no independent seat cushion height adjustment |
| <input style="width: 30px; height: 15px; background-color: yellow; border: 1px solid black;" type="checkbox"/> | 5. | Put the seat in its full rearward position. (S16.2.10.3.1) |
| | | <input style="width: 30px; height: 15px; background-color: yellow; border: 1px solid black;" type="checkbox"/> N/A, the seat does not have a fore-aft adjustment |
| <input style="width: 30px; height: 15px; background-color: yellow; border: 1px solid black;" type="checkbox"/> | 6. | If the seat height is adjustable, put it in the full down position. (S16.2.10.3.1) |
| | | <input style="width: 30px; height: 15px; background-color: yellow; border: 1px solid black;" type="checkbox"/> N/A, no seat height adjustment |
| <input style="width: 30px; height: 15px; background-color: yellow; border: 1px solid black;" type="checkbox"/> | 7. | Draw a horizontal reference line on the side of the seat cushion |
| <input style="width: 30px; height: 15px; background-color: yellow; border: 1px solid black;" type="checkbox"/> | 8. | Using only the controls that change the seat in the fore-aft direction, mark the fore-aft seat positions. Mark the side of the seat and a reference position directly below on a part of the vehicle that does not adjust. For manual seats, move the seat forward one detent at a time and mark each detent as was done for the full rearward position. For power seats, mark only the full rearward, middle, and full forward positions. Label three of the positions with the following: F for full forward, M for mid-position (if there is no mid position, label the closest adjustment position to the rear of the mid-point), and R for full rearward. |
| | | <input style="width: 30px; height: 15px; background-color: yellow; border: 1px solid black;" type="checkbox"/> N/A, the seat does not have a fore-aft adjustment. |
| <input style="width: 30px; height: 15px; background-color: yellow; border: 1px solid black;" type="checkbox"/> | 9. | Using only the controls that change the seat in the fore-aft direction, place the seat in the full rearward position and then place the seat in the forward most fore-aft position for this test. (S10.7) |
| <input style="width: 30px; height: 15px; background-color: yellow; border: 1px solid black;" type="checkbox"/> | 10. | If seat adjustments, other than fore-aft, are present and the horizontal reference line is no longer horizontal, use those adjustments to maintain the reference line as closely as possible to the horizontal. |
| | | <input style="width: 30px; height: 15px; background-color: yellow; border: 1px solid black;" type="checkbox"/> N/A, no adjustments |

<input type="checkbox"/>		Reference line angle as tested: Zero
<input type="checkbox"/>	11.	The seat back angle, if adjustable, is set at the manufacturer's nominal design riding position for a 50th percentile adult male in the manner specified by the manufacturer. (S4.5.4.1 (b) and S8.1.3)
<input type="checkbox"/>		N/A, no seat back angle adjustment
<input type="checkbox"/>		Manufacturer's design seat back angle:
<input type="checkbox"/>		Tested seat back angle:
<input type="checkbox"/>	12.	Position the test dummy using the procedures in Appendix A. (Some modifications to the positioning procedure may need to be made because the seat is in its forward most position. Note on the Appendix A positioning check sheet any deviations necessary to position the Part 572, Subpart E dummy.) Include the positioning check sheet with this form.
<input type="checkbox"/>	13.	Position the adjustable seat belt anchorage in the manufacturer's nominal design position for a 50 th percentile adult male occupant.
<input type="checkbox"/>	14.	Attach the inboard reach string to the base of the head following the instructions on Figure 3.
<input type="checkbox"/>	15.	Attach the outboard reach string to the torso sheath following the instructions on Figure 3.
<input type="checkbox"/>	16.	Place the latch plate in the stowed position.
<input type="checkbox"/>	17.	Extend inboard reach string in front of the dummy and then backward and outboard to the latch plate to generate an arc of the reach envelope of the test dummy's arms. Is the latch plate within the reach envelope?
<input type="checkbox"/>		Yes – Pass
<input type="checkbox"/>		No
<input type="checkbox"/>	18.	Extend outboard reach string in front of the dummy and then backward and outboard to the latch plate to generate an arc of the reach envelope of the test dummy's arms. Is the latch plate within the reach envelope?
<input type="checkbox"/>		Yes – Pass
<input type="checkbox"/>		No
<input type="checkbox"/>	19.	Is the latch plate within the inboard (item 17) or outboard (item 18) reach envelope?
<input type="checkbox"/>		Yes – Pass
<input type="checkbox"/>		No – Fail
<input type="checkbox"/>	20.	Using the clearance test block, specified in Figure 4, is there sufficient clearance between the vehicle seat and the side of vehicle interior to allow the test block to move unhindered to the latch plate or buckle?
<input type="checkbox"/>		Yes – Pass
<input type="checkbox"/>		No – Fail




Figure 3. Location of Anchoring Points for Latchplate Reach Limiting Chains or Strings to Test for Latchplate Accessibility Using Subpart E Test Device




Figure 4—USE OF CLEARANCE TEST BLOCK TO DETERMINE HAND/ARM ACCESS

REMARKS: NONE

I certify that I have read and performed each instruction.

Signature: Wayne Zuhl

Date: 3/19/04

DATA SHEET 12

SEAT BELT RETRACTION (S7.4.5)

Test Vehicle: 2004 Mitsubishi Galant 4 Door
 Test Program: FMVSS 208 Compliance
 Test Technician: Wayne Dahlke

NHTSA No.: C45603
 Test Date: 3/19/04

Test all front outboard seat belts other than those in walk-in van-type vehicles and those at front outboard designated seating positions in passenger cars. Complete a form for each applicable seat belt.

DESIGNATED SEATING POSITION:	Not Applicable For Any Position - Passenger Car
GVWR:	

- ☒ 1. Is the vehicle a passenger car or walk-in van-type vehicle?
 - ☒ Yes, this form is complete
 - ☐ No
- ☐ 2. Position the seat's adjustable lumbar supports so that the lumbar support is in its lowest, retracted or deflated adjustment position. (S8.1.3)
 - ☐ N/A, no lumbar adjustment
- ☐ 3. Position any adjustable parts of the seat that provide additional support so that they are in the lowest or most open adjustment position. (S16.2.10.2)
 - ☐ N/A, no additional support adjustment
- ☐ 4. If the seat cushion adjusts fore and aft, independent of the seat back, set this adjustment to the full rearward position. (S16.2.10.3.1)
 - ☐ N/A, no independent fore-aft seat cushion adjustment
- ☐ 5. If the seat cushion height adjusts independent of the seat back, set this adjustment to the full down position. (S16.2.10.3.1)
 - ☐ N/A, no independent seat cushion height adjustment
- ☐ 6. Put the seat in its full rearward position.
 - ☐ N/A, the seat does not have a fore-aft adjustment
- ☐ 7. If the seat height is adjustable, put it in the full down position. (S8.1.2)
 - ☐ N/A, no seat adjustment
- ☐ 8. Draw a horizontal line on the side of the seat cushion.
- ☐ 9. Using only the controls that change the seat in the fore-aft direction, mark the fore-aft seat positions. Mark the side of the seat and a reference position directly below on a part of the vehicle that does not adjust. For manual seats, move the seat forward one detent at a time and mark each detent as was done for the full rearward position. For power seats, mark only the full rearward, middle, and full forward positions. Label three of the positions with the following: F for full forward, M for mid-position (if there is no mid position, label the closest adjustment position to the rear of the mid-point), and R for full rearward.
 - ☐ N/A, the seat does not have a fore-aft adjustment.
- ☐ 10. Using only the controls that change the seat in the fore-aft direction, place the seat in the middle fore-aft position. (S8.1.2)
 - ☐ If there is no mid position, put the seat in the closest adjustment position to the rear of the midpoint. Describe the location of the seat:

- ☐ 11. If seat adjustments, other than fore-aft, are present and the reference line is no longer horizontal, use those adjustments to maintain the reference line as closely as possible to the horizontal. (S16.2.10.3.2)
- ☐ N/A – no seat adjustment
- ☐ Reference angle as tested:
- ☐ 12. The seat back angle, if adjustable, is set at the manufacturer's nominal design riding position for a 50th percentile adult male in the manner specified by the manufacturer. (S8.1.3)
- ☐ N/A – no seat back angle adjustment
- ☐ Manufacturer's design seat back angle:
- ☐ Tested seat back angle:
- ☐ 13. If adjustable, set the head restraint at the full up and full forward position. (S8.1.3) Any adjustment of the head restraint shall be used to position it full forward. For example, if it rotates, rotate it such that the head restraint extends as far forward as possible.
- ☐ N/A – no head restraint adjustment
- ☐ 14. Place any adjustable seat belt anchorages at the vehicle manufacturer's nominal design position for a 50th percentile adult male occupant (S8.1.3)
- ☐ N/A – no adjustable upper seat belt anchorage
- ☐ Manufacturer's specified anchorage position:
- ☐ Tested anchorage position:
- ☐ 15. Is the driver seat a bucket seat?
- ☐ Yes, go to 15.1 and skip 15.2.
- ☐ No, go to 15.2 and skip 15.1
- ☐ 15.1 Bucket seats - Locate and mark a vertical Plane B through the longitudinal centerline of the seat. The longitudinal centerline of a bucket seat cushion is determined at the widest part of the seat cushion. Measure perpendicular to the longitudinal centerline of the vehicle.
- ☐ Record the width of the seat:
- ☐ Record the distance from the edge of the seat to Plane B.
- ☐ 15.2 Bench seats (including split bench seats):
- ☐ Driver seat: Locate and mark a vertical Plane B through the center of the steering wheel parallel to the vehicle longitudinal centerline.
- ☐ Passenger seat: Locate and mark a vertical longitudinal Plane B on the seat that is the same distance from the longitudinal centerline of the vehicle as the center of the steering wheel.
- ☐ Distance from the vehicle centerline to the center of the steering wheel:
- ☐ Distance from the vehicle centerline to Plane B:
- ☐ 16. Stow outboard armrests that are capable of being stowed. (S7.4.5)
- ☐ 17. Remove the arms of a Subpart E dummy and place it in the seat such that the midsagittal plane is coincident with Plane B and the upper torso rests against the seat back. (S10.4.1.1 & S10.4.1.2)
- ☐ 18. Rest the thighs on the seat cushion

- ☐ 19. Position the H-point of the dummy within 0.5 inch of the vertical dimension and 0.5 inch of the horizontal dimension of a point 0.25 inch below the H-point determined by using the equipment and procedures specified in SAE J826 (APR 1980). (S10.4.2.1) Then measure the pelvic angle with respect to the horizontal using the pelvic angle gage. Adjust the dummy position until these three measurements are within the specifications. (S10.4.2.1 and S10.4.2.2)
- ☐ Horizontal inches from the point 0.25 below the determined H-point (0.5 inch max.) (S10.4.2.1)
 - ☐ Vertical inches from the point 0.25 below the determined H-point (0.5 inch max.) (S10.4.2.1)
 - ☐ Pelvic angle (20° to 25°)
 - ☐ Vertical inches from the point 0.25 below the determined H-point (0.5 inch max.) (S10.4.2.1)
 - ☐ Pelvic angle (20° to 25°) (S10.4.2.2)
- ☐ 20. Set the distance between the outboard knee clevis flange surfaces at 10.6 inches. Measured distance (10.6 inches) (S10.5):
- ☐ 21. To the extent practicable keep the thighs and the legs in a vertical plane (S10.5) and rest the thighs on the seat cushion while resting the feet on the floorpan or toe board.
- ☐ 22. Fasten the seat belt around the dummy.
- ☐ 23. Remove all slack from the lap belt portion. (S10.9)
- ☐ 24. Pull the upper torso webbing out of the retractor and allow it to retract; repeat this four times. (S10.9)
- ☐ 25. Apply a 2 to 4 pound tension load to the lap belt. (S10.9)
- ☐ Pound load applied:
- ☐ 26. Is the belt system equipped with a tension relieving device?
- ☐ __ Yes, continue
 - ☐ __ No, go to 27
- ☐ 26.1 Introduce the maximum amount of slack into the upper torso bet that is recommended by the vehicle manufacturer in the vehicle owner's manual. (S10.9). Go to 25.
- ☐ 27. Check the statement that applies to this test vehicle:
- ☐ 27.1 Check the statement that applies to this test vehicle:
The torso and lap belt webbing of the seat belt system automatically retracts to a stowed position when the adjacent vehicle door is in an open position and the seat belt latch plate is released.
- ☐ Pass
- ☐ 27.2 The torso and lap belt webbing of the seat belt system automatically retracts when the seat belt latch plate is released.
- ☐ Pass
- ☐ 27.3 Neither A or B apply
- ☐ Fail
- ☐ 28. With the webbing and hardware in the stowed position are the webbing and hardware prevented from being pinched when the door is closed?
- ☐ Yes – Pass
 - ☐ No – Fail

☐

29. If this test vehicle has an open body (without doors) and has a belt system with a tension-relieving device, does the belt system fully retract when the tension-relieving device is deactivated?

☐

N/A

☐

Yes – Pass

☐

No – Fail

REMARKS:

I certify that I have read and performed each instruction.

Signature:

Wayne Zalk

Date:

3/19/04

DATA SHEET 13

SEAT BELT GUIDES AND HARDWARE (S7.4.6)

Test Vehicle: 2004 Mitsubishi Galant 4 Door
 Test Program: FMVSS 208 Compliance
 Test Technician: Wayne Dahlke

NHTSA No.: C45603
 Test Date: 3/19/04

Test seat belts except those in walk-in van-type vehicles and those at front outboard designated seating positions in passenger cars. Complete a form for each applicable seat belt.

DESIGNATED SEATING POSITION:	Left Rear Passenger
------------------------------	---------------------

- | | | |
|----------|----|--|
| X | 1. | Is the seat cushion movable so that the seat back serves a function other than seating? (S7.4.6.1 (b)) |
| | | <input type="checkbox"/> Yes, this form is complete |
| | | <input checked="" type="checkbox"/> No, go to 2 |
| X | 2. | Is the seat removable? (S7.4.6.1(b)) |
| | | <input type="checkbox"/> Yes, this form is complete |
| | | <input checked="" type="checkbox"/> No, go to 3 |
| X | 3. | Is the seat movable so that the space formerly occupied by the seat can be used for a secondary function? (S7.4.6.1(b)) |
| | | <input type="checkbox"/> Yes, this form is complete |
| | | <input checked="" type="checkbox"/> No, go to 4 |
| X | 4. | Is the webbing designed to pass through the seat cushion or between the seat cushion and seat back? (S7.4.6.1(a)) |
| | | <input checked="" type="checkbox"/> Yes, go to 5 |
| | | <input type="checkbox"/> No, this form is complete |
| X | 5. | Does one of the following three parts, the seat belt latch plate, the buckle, or the seat belt webbing, stay on top of or above the seat cushion under normal conditions (i.e., conditions other than when belt hardware is intentionally pushed behind the seat by a vehicle occupant)? (S7.4.6.1(a)) |
| | | <input checked="" type="checkbox"/> Yes – Pass |
| | | <input type="checkbox"/> No – Fail |
| | | Identify the part(s) on top or above the seat. |
| | | <input checked="" type="checkbox"/> Seat belt latch plate |
| | | <input checked="" type="checkbox"/> Buckle |
| | | <input checked="" type="checkbox"/> Seat belt webbing |
| X | 6. | Are the remaining two seat belt parts accessible under normal conditions? |
| | | <input checked="" type="checkbox"/> Yes – Pass |
| | | <input type="checkbox"/> No – Fail |
| X | 7. | The buckle and latch plate do not pass through the guides or conduits provided and fall behind the seat when the belt is completely retracted or, if the belt is nonretractable, the belt is unlatched. (S7.4.6.2) |
| | | <input checked="" type="checkbox"/> Yes – Pass |
| | | <input type="checkbox"/> No – Fail |

- ☒ 8. The buckle and latch plate do not pass through the guides or conduits provided and fall behind the seat when the seat is moved to any position to which it is designed to be adjusted. (S7.4.6.2)
- ☒ Yes – Pass
☐ No – Fail
- ☒ 9. The buckle and latch plate do not pass through the guides or conduits provided and fall behind the seat when the seat back, if foldable, is folded forward as far as possible and then moved backward into position. (S7.4.6.2)
- ☒ Yes – Pass
☐ No – Fail
- ☒ 10. Is the inboard receptacle end of the seat belt assembly, installed in the front outboard designated seating position, accessible with the center armrest in any position to which it can be adjusted (without moving the armrest)? (S7.4.6.2)
- ☐ Yes – Pass
☐ No – Fail
☒ N/A – Rear seat

REMARKS: NONE

I certify that I have read and performed each instruction.

Signature: Wayne Zuhl

Date: 3/19/04

DATA SHEET 13

SEAT BELT GUIDES AND HARDWARE (S7.4.6)

Test Vehicle: 2004 Mitsubishi Galant 4 Door
 Test Program: FMVSS 208 Compliance
 Test Technician: Wayne Dahlke

NHTSA No.: C45603
 Test Date: 3/19/04

Test seat belts except those in walk-in van-type vehicles and those at front outboard designated seating positions in passenger cars. Complete a form for each applicable seat belt.

DESIGNATED SEATING POSITION:	Center Rear Passenger
------------------------------	-----------------------

- | | | |
|----------|----|--|
| X | 1. | Is the seat cushion movable so that the seat back serves a function other than seating? (S7.4.6.1 (b)) |
| | | <input type="checkbox"/> Yes, this form is complete |
| | | <input checked="" type="checkbox"/> No, go to 2 |
| X | 2. | Is the seat removable? (S7.4.6.1(b)) |
| | | <input type="checkbox"/> Yes, this form is complete |
| | | <input checked="" type="checkbox"/> No, go to 3 |
| X | 3. | Is the seat movable so that the space formerly occupied by the seat can be used for a secondary function? (S7.4.6.1(b)) |
| | | <input type="checkbox"/> Yes, this form is complete |
| | | <input checked="" type="checkbox"/> No, go to 4 |
| X | 4. | Is the webbing designed to pass through the seat cushion or between the seat cushion and seat back? (S7.4.6.1(a)) |
| | | <input checked="" type="checkbox"/> Yes, go to 5 |
| | | <input type="checkbox"/> No, this form is complete |
| X | 5. | Does one of the following three parts, the seat belt latch plate, the buckle, or the seat belt webbing, stay on top of or above the seat cushion under normal conditions (i.e., conditions other than when belt hardware is intentionally pushed behind the seat by a vehicle occupant)? (S7.4.6.1(a)) |
| | | <input checked="" type="checkbox"/> Yes – Pass |
| | | <input type="checkbox"/> No – Fail |
| | | Identify the part(s) on top or above the seat. |
| | | <input checked="" type="checkbox"/> Seat belt latch plate |
| | | <input checked="" type="checkbox"/> Buckle |
| | | <input checked="" type="checkbox"/> Seat belt webbing |
| X | 6. | Are the remaining two seat belt parts accessible under normal conditions? |
| | | <input checked="" type="checkbox"/> Yes – Pass |
| | | <input type="checkbox"/> No – Fail |
| X | 7. | The buckle and latch plate do not pass through the guides or conduits provided and fall behind the seat when the belt is completely retracted or, if the belt is nonretractable, the belt is unlatched. (S7.4.6.2) |
| | | <input checked="" type="checkbox"/> Yes – Pass |
| | | <input type="checkbox"/> No – Fail |

- ☒ 8. The buckle and latch plate do not pass through the guides or conduits provided and fall behind the seat when the seat is moved to any position to which it is designed to be adjusted. (S7.4.6.2)
- ☒ Yes – Pass
☐ No – Fail
- ☒ 9. The buckle and latch plate do not pass through the guides or conduits provided and fall behind the seat when the seat back, if foldable, is folded forward as far as possible and then moved backward into position. (S7.4.6.2)
- ☒ Yes – Pass
☐ No – Fail
- ☒ 10. Is the inboard receptacle end of the seat belt assembly, installed in the front outboard designated seating position, accessible with the center armrest in any position to which it can be adjusted (without moving the armrest)? (S7.4.6.2)
- ☐ Yes – Pass
☐ No – Fail
☒ N/A – Rear seat

REMARKS: NONE

I certify that I have read and performed each instruction.

Signature: Wayne Zuhl

Date: 3/19/04

DATA SHEET 13

SEAT BELT GUIDES AND HARDWARE (S7.4.6)

Test Vehicle: 2004 Mitsubishi Galant 4 Door
 Test Program: FMVSS 208 Compliance
 Test Technician: Wayne Dahlke

NHTSA No.: C45603
 Test Date: 3/19/04

Test seat belts except those in walk-in van-type vehicles and those at front outboard designated seating positions in passenger cars. Complete a form for each applicable seat belt.

DESIGNATED SEATING POSITION:	Right Rear Passenger
------------------------------	----------------------

- | | | |
|----------|----|--|
| X | 1. | Is the seat cushion movable so that the seat back serves a function other than seating? (S7.4.6.1 (b)) |
| | | <input type="checkbox"/> Yes, this form is complete |
| | | <input checked="" type="checkbox"/> No, go to 2 |
| X | 2. | Is the seat removable? (S7.4.6.1(b)) |
| | | <input type="checkbox"/> Yes, this form is complete |
| | | <input checked="" type="checkbox"/> No, go to 3 |
| X | 3. | Is the seat movable so that the space formerly occupied by the seat can be used for a secondary function? (S7.4.6.1(b)) |
| | | <input type="checkbox"/> Yes, this form is complete |
| | | <input checked="" type="checkbox"/> No, go to 4 |
| X | 4. | Is the webbing designed to pass through the seat cushion or between the seat cushion and seat back? (S7.4.6.1(a)) |
| | | <input checked="" type="checkbox"/> Yes, go to 5 |
| | | <input type="checkbox"/> No, this form is complete |
| X | 5. | Does one of the following three parts, the seat belt latch plate, the buckle, or the seat belt webbing, stay on top of or above the seat cushion under normal conditions (i.e., conditions other than when belt hardware is intentionally pushed behind the seat by a vehicle occupant)? (S7.4.6.1(a)) |
| | | <input checked="" type="checkbox"/> Yes – Pass |
| | | <input type="checkbox"/> No – Fail |
| | | Identify the part(s) on top or above the seat. |
| | | <input checked="" type="checkbox"/> Seat belt latch plate |
| | | <input checked="" type="checkbox"/> Buckle |
| | | <input checked="" type="checkbox"/> Seat belt webbing |
| X | 6. | Are the remaining two seat belt parts accessible under normal conditions? |
| | | <input checked="" type="checkbox"/> Yes – Pass |
| | | <input type="checkbox"/> No – Fail |
| X | 7. | The buckle and latch plate do not pass through the guides or conduits provided and fall behind the seat when the belt is completely retracted or, if the belt is nonretractable, the belt is unlatched. (S7.4.6.2) |
| | | <input checked="" type="checkbox"/> Yes – Pass |
| | | <input type="checkbox"/> No – Fail |

- ☒ 8. The buckle and latch plate do not pass through the guides or conduits provided and fall behind the seat when the seat is moved to any position to which it is designed to be adjusted. (S7.4.6.2)
- ☒ Yes – Pass
☐ No – Fail
- ☒ 9. The buckle and latch plate do not pass through the guides or conduits provided and fall behind the seat when the seat back, if foldable, is folded forward as far as possible and then moved backward into position. (S7.4.6.2)
- ☒ Yes – Pass
☐ No – Fail
- ☒ 10. Is the inboard receptacle end of the seat belt assembly, installed in the front outboard designated seating position, accessible with the center armrest in any position to which it can be adjusted (without moving the armrest)? (S7.4.6.2)
- ☐ Yes – Pass
☐ No – Fail
☒ N/A – Rear seat

REMARKS: NONE

I certify that I have read and performed each instruction.

Signature: Wayne Zuhl

Date: 3/19/04

DATA SHEET 14

MARKING OF REFERENCE POINTS FOR VARIOUS TEST POSITIONS AND POINTS

Test Vehicle: 2004 Mitsubishi Galant 4 Door
 Test Program: FMVSS 208 Compliance
 Test Technician: Eric Peschman

NHTSA No.: C45603
 Test Date: 7/23/04

1. Driver Designated Seating Position:

- | | | |
|--|------|--|
| <div style="background-color: yellow; border: 1px solid black; text-align: center; width: 30px; margin-bottom: 5px;">X</div> | 1.1 | Position the seat's adjustable lumbar supports so that the lumbar supports are in the lowest, retracted or deflated adjustment positions. (S16.2.10.1) |
| | | <div style="background-color: yellow; border: 1px solid black; width: 20px; height: 15px; display: inline-block;"></div> N/A – No lumbar adjustment |
| <div style="background-color: yellow; border: 1px solid black; text-align: center; width: 30px; margin-bottom: 5px;">X</div> | 1.2 | Position any adjustable parts of the seat that provide additional support so that they are in the lowest or most open adjustment position (S16.2.10.2) |
| | | <div style="background-color: yellow; border: 1px solid black; text-align: center; width: 30px; margin-bottom: 5px;">X</div> N/A – No additional support adjustment |
| <div style="background-color: yellow; border: 1px solid black; text-align: center; width: 30px; margin-bottom: 5px;">X</div> | 1.3 | Mark a point (seat cushion reference point) on the side of the seat cushion that is between 150 mm and 250 mm from the front edge of the seat cushion. |
| <div style="background-color: yellow; border: 1px solid black; text-align: center; width: 30px; margin-bottom: 5px;">X</div> | 1.4 | Draw a line (seat cushion reference line) through the seat cushion reference point. |
| <div style="background-color: yellow; border: 1px solid black; text-align: center; width: 30px; margin-bottom: 5px;">X</div> | 1.5 | Using only the controls that primarily move the seat in the fore-aft direction, move the seat cushion reference point to the rearmost position. |
| <div style="background-color: yellow; border: 1px solid black; text-align: center; width: 30px; margin-bottom: 5px;">X</div> | 1.6 | If the seat cushion adjusts fore-aft, independent of the seat back, use only the controls that primarily move the seat cushion in the fore-aft direction to move the seat cushion reference point to the rearmost position (S16.2.10.3) |
| | | <div style="background-color: yellow; border: 1px solid black; text-align: center; width: 30px; margin-bottom: 5px;">X</div> N/A – No independent fore-aft seat cushion adjustment |
| <div style="background-color: yellow; border: 1px solid black; text-align: center; width: 30px; margin-bottom: 5px;">X</div> | 1.7 | Using any part of any control, other than the parts just used for fore-aft positioning, determine the range of angles of the seat cushion reference line and set the seat cushion reference line at the mid-angle. |
| <div style="background-color: yellow; border: 1px solid black; text-align: center; width: 30px; margin-bottom: 5px;">X</div> | | Maximum Angle: 11.0 Degrees Nose Up |
| <div style="background-color: yellow; border: 1px solid black; text-align: center; width: 30px; margin-bottom: 5px;">X</div> | | Minimum Angle: 0.0 Degrees |
| <div style="background-color: yellow; border: 1px solid black; text-align: center; width: 30px; margin-bottom: 5px;">X</div> | | Mid-angle: 5.5 Degrees Nose Up |
| <div style="background-color: yellow; border: 1px solid black; text-align: center; width: 30px; margin-bottom: 5px;">X</div> | 1.8 | If the seat and/or seat cushion height is adjustable, use any part of any control other than those which primarily move the seat or seat cushion fore-aft, to put the seat cushion reference point in its lowest position with the seat cushion reference line angle at the mid-angle found in 1.7. |
| | | <div style="background-color: yellow; border: 1px solid black; width: 20px; height: 15px; display: inline-block;"></div> N/A – No seat height adjustment |
| <div style="background-color: yellow; border: 1px solid black; text-align: center; width: 30px; margin-bottom: 5px;">X</div> | 1.9 | Using only the controls that primarily move the seat in the fore-aft direction, verify the seat is in the rearmost position. |
| <div style="background-color: yellow; border: 1px solid black; text-align: center; width: 30px; margin-bottom: 5px;">X</div> | 1.10 | Using only the controls that primarily move the seat in the fore-aft direction, mark for future reference the fore-aft seat positions. Mark each position so that there is a visual indication when the seat is at a particular position. For manual seats, move the seat forward one detent at a time and mark each detent. For power seats, mark only the rearmost, middle, and foremost positions. Label three of the positions with the following: F for foremost, M for mid-position (if there is no mid-position, label the closest adjustment position to the rear of the mid-point), and R for rearmost. |
| <div style="background-color: yellow; border: 1px solid black; text-align: center; width: 30px; margin-bottom: 5px;">X</div> | 1.11 | Use only the controls that primarily move the seat in the fore-aft direction to place the seat in the rearmost position. |
| <div style="background-color: yellow; border: 1px solid black; text-align: center; width: 30px; margin-bottom: 5px;">X</div> | 1.12 | Using any controls, other than the controls that primarily move the seat and/or seat cushion in the fore-aft direction, find and visually mark for future reference the maximum, minimum, and middle height of the seat cushion reference point with the seat cushion reference line at the mid-angle determined in 1.7. |

- ☒ 1.13 Using only the controls that primarily move the seat and/or seat cushion in the fore-aft direction, place the seat in the mid-fore-aft position.
- ☒ 1.14 Using any controls, other than the controls that primarily move the seat in the fore-aft direction, find and visually mark for future reference the maximum, minimum, and middle height of the seat cushion reference point with the seat cushion reference line at the mid-angle determined in 1.7.
- ☒ 1.15 Using only the controls that change the seat in the fore-aft direction, place the seat in the foremost position.
- ☒ 1.16 Using any controls, other than the controls that primarily move the seat in the fore-aft direction, find and visually mark for future reference the maximum, minimum, and middle height of the seat cushion reference point with the seat cushion reference line at the mid-angle determined in 1.7.
- ☒ 1.17 Visually mark for future reference the seat back angle, if adjustable, at the manufacturer's nominal design riding position for a 50th percentile adult male in the manner specified by the manufacturer.
- ☐ N/A – No seat back angle adjustment
- ☒ Manufacturer's design seat back angle: 25° On Seat Back Frame
- ☒ 1.18 Is the seat a bucket seat?
- ☒ Yes, go to 1.18.1 and skip 1.18.2
- ☐ No, go to 1.18.2 and skip 1.18.1
- 1.18.1 Bucket seats:
- ☒ Locate and mark for future reference the longitudinal centerline of the seat cushion. The longitudinal centerline of a bucket seat cushion is determined at the widest part of the seat cushion. Measure perpendicular to the longitudinal centerline of the vehicle. (S16.3.1.10)
- ☒ Record the width of the seat cushion: 520 mm
- ☒ One half the width of the seat cushion is: 260 mm
- ☒ Record the distance from the edge of the seat cushion to the seat mark: 260 mm
- 1.18.2 Bench seats:
- ☐ Locate and mark for future reference the longitudinal line on the seat cushion that marks the longitudinal vertical plane through the centerline of the steering wheel.
2. Passenger Designated Seating Position
- ☒ 2.1 Is the seat adjustable independent of the driver seating position?
- ☒ Yes, go to 2.2
- ☐ No, go to 2.18
- ☒ 2.2 Position the seat's adjustable lumbar supports so that the lumbar supports are in the lowest, retracted or deflated adjustment positions (S16.2.10.1, S20.1.9.1, S22.1.7.1)
- ☒ N/A – No lumbar adjustment
- ☒ 2.3 Position any adjustable parts of the seat that provide additional support so that they are in the lowest or most open adjustment position. (S16.2.10.2, S20.1.9.2, S22.1.7.2)
- ☒ N/A – No additional support adjustment
- ☒ 2.4 Mark a point (seat cushion reference point) on the side of the seat cushion that is between 150 mm and 250 mm from the front edge of the seat cushion.
- ☒ 2.5 Draw a line (seat cushion reference line) through the seat cushion reference point.
- ☒ 2.6 Using only the controls that primarily move the seat in the fore-aft direction, move the seat cushion reference point to the rearmost position.

X	2.7	If the seat cushion adjusts fore-aft, independent of the seat back, use only the controls that primarily move the seat cushion in the fore-aft direction to move the seat cushion reference point to the rearmost position (S16.2.10.3, S20.1.9.3, S22.1.7.3)
X		N/A – No independent fore-aft seat cushion adjustment.
X	2.8	Using any part of the control, other than the parts just used for fore-aft positioning, determine the range of angles of the seat cushion reference line and set the seat cushion reference line at the mid-angle.
X		Maximum Angle: 0.0 Degrees
X		Minimum Angle: 0.0 Degrees
X		Mid-angle: 0.0 Degrees
X	2.9	If the seat and/or seat cushion height is adjustable, use any part of any control other than those which primarily move the seat or seat cushion fore-aft, to put the seat cushion reference point in its lowest position with the seat cushion reference line angle at the mid-range angle.
X		N/A – No seat height adjustment
X	2.10	Using only the controls that primarily move the seat and/or seat cushion in the fore-aft direction, verify the seat is in the rearmost position.
X	2.11	Using only the controls that primarily move the seat in the fore-aft direction, mark for future reference the fore-aft seat positions. Mark each position so that there is a visual indication when the seat is at a particular position. For manual seats, move the seat forward one detent at a time and mark each detent. For power seats, mark only the rearmost, middle, and foremost positions. Label three of the positions with the following: F for foremost, M for mid-position (if there is no mid-position, label the closest adjustment position to the rear of the mid-point), and R for rearmost.
X	2.12	Using only the controls that primarily move the seat in the fore-aft direction, place the seat in the rearmost position.
X	2.13	Using any controls, other than the controls that primarily move the seat in the fore-aft direction, find and visually mark for future reference the maximum, minimum, and middle height of the seat cushion reference point with the seat cushion reference line at the mid-angle determined in 2.8.
X		N/A – No seat height adjustment Go to 2.18
X	2.14	Using only the controls that primarily move the seat in the fore-aft direction, place the seat in the mid-fore-aft position.
X	2.15	Using any controls, other than the controls that primarily move the seat in the fore-aft direction, find and visually mark for future reference the maximum, minimum, and middle height of the seat cushion reference point with the seat cushion reference line at the mid-angle determined in 2.8.
X	2.16	Using only the controls that change the seat in the fore-aft direction, place the seat in the foremost position.
X	2.17	Using any controls, other than the controls that primarily move the seat in the fore-aft direction, find and visually mark for future reference the maximum, minimum, and middle height of the seat cushion reference point with the seat cushion reference line at the mid-angle determined in 2.8.
X	2.18	Visually mark for future reference the seat back angle, if adjustable, at the manufacturer's nominal design riding position for a 50 th percentile adult male in the manner specified by the manufacturer.
		N/A – No seat back angle adjustment
		N/A – The seat back angle adjustment is controlled by the setting of the driver seat back angle.

<input checked="" type="checkbox"/>		Manufacturer's design seat back angle: 25° On Seat Back Frame
<input checked="" type="checkbox"/>		Actual seat back angle: 25° On Seat Back Frame (10.0° On Headrest Post)
<input checked="" type="checkbox"/>	2.19	Is the seat a bucket seat?
<input checked="" type="checkbox"/>		Yes, go to 2.19.1 and skip 2.19.2
<input type="checkbox"/>		No, go to 2.19.2 and skip 2.19.1
		2.19.1 Bucket seats:
<input checked="" type="checkbox"/>		Locate and mark for future reference the longitudinal centerline of the seat cushion. (S20.2.1.3, S22.2.1.3) The longitudinal centerline of a bucket seat cushion is determined at the widest part of the seat cushion. Measure perpendicular to the longitudinal centerline of the vehicle. (S20.1.10)
<input checked="" type="checkbox"/>		Record the width of the seat cushion: 518 mm
<input checked="" type="checkbox"/>		One half the width of the seat cushion is: 259 mm
<input type="checkbox"/>		Record the distance from the edge of the seat cushion to the longitudinal centerline of the seat cushion. (The vertical plane through this longitudinal centerline is Plane B for suppression.)
		2.19.2 Bench seats:
<input type="checkbox"/>		Locate and mark for future reference the longitudinal centerline of the passenger seat cushion. The longitudinal centerline is the same distance from the longitudinal centerline of the vehicle as the center of the steering wheel. (S20.2.1.3, S22.2.1.3)
<input type="checkbox"/>		Record the distance from the longitudinal centerline of the vehicle to the center of the steering wheel:
<input type="checkbox"/>		Record the distance from the longitudinal centerline of the vehicle to the longitudinal centerline of the seat cushion. (The vertical plane through this longitudinal centerline is Plane B for suppression.)
<input checked="" type="checkbox"/>	3.	Head Restraints
<input type="checkbox"/>		N/A, vehicle contains automatic head restraints
<input type="checkbox"/>		N/A, there is no head restraint adjustment
<input checked="" type="checkbox"/>	3.1	Left outboard
<input checked="" type="checkbox"/>	3.1.1	Adjust the head restraint to its lowest position. (S16.3.4.2)
<input checked="" type="checkbox"/>	3.1.2	Any adjustment of the head restraint shall be used to position it full forward. For example, if it rotates, rotate it such that the head restraint extends as far forward as possible. Mark the foremost position.
<input checked="" type="checkbox"/>	3.1.3	Measure the vertical distance from the top most point of the head restraint to the bottom most point. Locate and mark a horizontal plane through the midpoint of this distance.
<input checked="" type="checkbox"/>		Vertical height of head restraint (mm): 170 mm
<input checked="" type="checkbox"/>		Mid-point height (mm): 85 mm
<input checked="" type="checkbox"/>	3.2	Right outboard
<input checked="" type="checkbox"/>	3.2.1	Adjust the head restraint to its lowest position. (S16.3.4.2)
<input checked="" type="checkbox"/>	3.2.2	Any adjustment of the head restraint shall be used to position it full forward. For example, if it rotates, rotate it such that the head restraint extends as far forward as possible. Mark the foremost position.
<input checked="" type="checkbox"/>	3.2.3	Measure the vertical distance from the top most point of the head restraint to the bottom most point. Locate and mark a horizontal plane through the midpoint of this distance.
<input checked="" type="checkbox"/>		Vertical height of head restraint (mm): 170 mm
<input checked="" type="checkbox"/>		Mid-point height (mm): 85 mm
<input checked="" type="checkbox"/>	4.	Steering Wheel

- ☒ 4.1 Is the steering wheel adjustable up and down and/or in and out?
- ☒ Yes, go to 4.2
- ☐ No, this form is complete
- ☒ 4.2 Find and **mark** for future reference each up and down position. Label three of the positions with the following: H for highest, M for mid-position (if there is no mid-position, label the next lowest adjustment position), and L for lowest.
- ☐ N/A, steering wheel is not adjustable up and down
- ☒ 4.3 Find and **mark** for future references each in and out position. Label three of the positions with the following: F for foremost, M for mid-position (if there is no mid-position, label the next rearmost adjustment position), and R for rearmost.
- ☒ N/A, steering wheel is not adjustable in and out
- ☒ 5. Driver Low Risk Deployment
- ☐ N/A, no low risk deployment tests scheduled
- ☒ 5.1 Position the steering wheel so the front wheels are in the straight-ahead position. (S26.2.1)
- ☒ 5.2 Position any adjustable parts of the steering controls to the mid-position as determined in item 3 above. If a mid-position adjustment is not achievable, position the controls to the next lowest detent position. (S26.2.1)
- ☒ 5.3 Locate the vertical plane parallel to the vehicle longitudinal centerline through the geometric center of the opening through which the driver air bag deploys into the occupant compartment. This is referred to as "Plane E". (Check determination method below.) (S26.2.6)
- ☒ Plane E determined using manufacturer's information supplied by the COTR . (Found in Appendix D on pages D-65 and 66)
- ☐ Plane E determined by test lab personnel and approved by the COTR. (Include supporting documentation in the test report.)
- | | Ey (mm) |
|---|---------|
| "Plane E" Measurement:: | |
| Measured: | |
| Specified: | |
| Verify Measured Equals Specified +/- 6mm: | |
- ☒ 5.4 Locate the horizontal plane through the highest point of the air bag module cover. This is referred to as "Plane F." (Check determination method below.) (S26.2.6)
- ☒ Plane F determined using manufacturer's information supplied by the COTR . (Found in Appendix D on pages D-65 and 66)
- ☐ Plane F determined by test lab personnel and approved by the COTR. (Include supporting documentation in the test report.)
- | | Fz (mm) |
|---|---------|
| "Plane F" Measurement:: | |
| Measured: | |
| Specified: | |
| Verify Measured Equals Specified +/- 6mm: | |
- ☒ 6. Passenger Low Risk Deployment – Planes C and D
- ☐ N/A, no low risk deployment tests scheduled
- ☒ 6.1 Locate the horizontal plane through the geometric center of the opening through which the right front air bag deploys into the occupant compartment. This is referred to as "Plane C." (Check location method below.) (S22.4.1.3)

- ☒ Plane C located using manufacturer's information supplied by the COTR.
(Found in Appendix D on pages D-65 and 66)
- ☐ Plane C located by test lab personnel and approved by the COTR.
(Include supporting documentation in the test report.)

	Cz (mm)
"Plane C" Measurement::	
Measured:	
Specified:	
Verify Measured Equals Specified +/- 6mm:	

- ☒ 6.2 Locate the vertical plane parallel to the vehicle longitudinal centerline through the geometric center of the opening through which the right front air bag deploys into the occupant compartment. This is referred to as "Plane D." (Check determination method below.) (S22.4.1.2)

- ☒ Plane D determined using manufacturer's information supplied by the COTR.
(Found in Appendix D on pages D-65 and 66)
- ☐ Plane D determined by test lab personnel and approved by the COTR.
(Include supporting documentation in the test report.)

	Dy (mm)
"Plane D" Measurement:	
Measured:	
Specified:	
Verify Measured Equals Specified +/- 6mm:	

- ☒ 6.3 **Mark** the intersection of Planes C and D on the instrument panel.

- ☒ 7. 5th Female Dummy
Mark a point on the chin of the dummy 40 mm below the center of the mouth. (Chin Point) (S26.2.6)

- ☒ 8. 6-Year-Old Dummy
Locate and **mark** a point on the front of the dummy's chest jacket on the midsagittal plane which is 139 mm (5.5 in) \pm 3 mm (\pm 0.1 in) along the surface of the skin down from the top of the skin at the neck line. Designate this point as "Point 1." (S24.4.1.1)

- ☒ "Point 1" measurement (mm): 139 mm
- ☐ 9. 3-Year-Old Dummy
Locate and **mark** a point on the front of the dummy's chest jacket on the midsagittal plane which is 114 mm (4.5 in) \pm 3 mm (\pm 0.1 in) along the surface of the skin down from the top of the skin at the neck line. Designate this point as "Point 1." (S22.4.1.1)

- ☐ "Point 1" measurement (mm +/- 3 mm):

REMARKS: NONE

I certify that I have read and performed each instruction.

Signature: Eric Leach

Date: 7/23/04

DATA SHEET 15 SUMMARY

Suppression Test Using 12-month-old CRABI Dummy (Part 572, Subpart R)
Section B Rear Facing CRS

NHTSA No.:	C45603	TEST DATE:	6/22/04
LABORATORY:	MGA	TECHNICIANS:	JL/TB
DUMMY TYPE:	12 Month Old	DUMMY SERIAL NO.:	082

CHILD RESTRAINT NAME:	Britax
CHILD RESTRAINT MODEL:	Handle With Care 191
DATE OF MANUFACTURE:	5-26-2000

Base: __On __Off X N/A-Restraint does not have a removable base

Manufacturer's design seat back angle: 25.0° On Seat Back

Tested seat back angle: 25.0° On Seat Back

Manufacturer's specified anchorage position: Middle

Tested anchorage position: Middle

A blanket and visor were not used in the suppression testing because they did not affect the weight sensing system used on the vehicle.

Test Summary

Seat Belt	Seat Slide	Cinch Load (N)	Handle Down	Handle Up
Belted Rear Facing	Forward	130	Suppressed	N/A
	Middle	134	Suppressed	N/A
	Rearward	127	Suppressed	N/A
Unbelted Rear Facing	Forward	N/A	Suppressed	N/A
	Middle	N/A	Suppressed	N/A
	Rearward	N/A	Suppressed	N/A
Unbelted Forward Facing	Forward	N/A	Suppressed	N/A
	Middle	N/A	Suppressed	N/A
	Rearward	N/A	Suppressed	N/A

Successful Unbelted 5th percentile Female Dummy Reactivation was performed with the seat in the Rearward position. (SN507)

DATA SHEET 15 SUMMARY

Suppression Test Using 12-month-old CRABI Dummy (Part 572, Subpart R)
Section B Rear Facing CRS

NHTSA No.:	C45603	TEST DATE:	6/22/04
LABORATORY:	MGA	TECHNICIANS:	JL/TB
DUMMY TYPE:	12 Month Old	DUMMY SERIAL NO.:	082

CHILD RESTRAINT NAME:	Evenflo
CHILD RESTRAINT MODEL:	First Choice 204
DATE OF MANUFACTURE:	6-20-2000

Base: __On __Off X N/A-Restraint does not have a removable base

Manufacturer's design seat back angle: 25.0° On Seat Back

Tested seat back angle: 25.0° On Seat Back

Manufacturer's specified anchorage position: Middle

Tested anchorage position: Middle

A blanket and visor were not used in the suppression testing because they did not affect the weight sensing system used on the vehicle.

Test Summary

Seat Belt	Seat Slide	Cinch Load (N)	Handle Down	Handle Up
Belted Rear Facing	Forward	128	N/A	Suppressed
	Middle	133	N/A	Suppressed
	Rearward	127	Suppressed	N/A
Unbelted Rear Facing	Forward 6 *	N/A	N/A	Suppressed
	Middle	N/A	N/A	Suppressed
	Rearward	N/A	Suppressed	N/A
Unbelted Forward Facing	Forward 4*	N/A	N/A	Suppressed
	Middle	N/A	N/A	Suppressed
	Rearward	N/A	N/A	Suppressed

Successful Unbelted 5th percentile Female Dummy Reactivation was performed with the seat in the Middle position. (SN507)

* The CRS would not fit in this Forward Seat Slide position. If there is a number in the Seat Slide column, it indicates the fore-aft detent position with respect to the foremost position. (1 = Full Forward; 23 = Full Rearward; 23 total Seat Slide detents)

DATA SHEET 15 SUMMARY

Suppression Test Using 12-month-old CRABI Dummy (Part 572, Subpart R)
Section B Rear Facing CRS

NHTSA No.:	C45603	TEST DATE:	6/22/04
LABORATORY:	MGA	TECHNICIANS:	JL/TB
DUMMY TYPE:	12 Month Old	DUMMY SERIAL NO.:	082

CHILD RESTRAINT NAME:	Graco
CHILD RESTRAINT MODEL:	Infant 8457
DATE OF MANUFACTURE:	8-31-2000

Base: X On Off N/A-Restraint does not have a removable base

Manufacturer's design seat back angle: 25.0° On Seat Back

Tested seat back angle: 25.0° On Seat Back

Manufacturer's specified anchorage position: Middle

Tested anchorage position: Middle

A blanket and visor were not used in the suppression testing because they did not affect the weight sensing system used on the vehicle.

Test Summary

Seat Belt	Seat Slide	Cinch Load (N)	Handle Down	Handle Up
Belted Rear Facing	Forward	130	N/A	Suppressed
	Middle	127	Suppressed	N/A
	Rearward	127	Suppressed	N/A
Unbelted Rear Facing	Forward 3 *	N/A	N/A	Suppressed
	Middle	N/A	N/A	Suppressed
	Rearward	N/A	Suppressed	N/A
Unbelted Forward Facing	Forward	N/A	N/A	Suppressed
	Middle	N/A	N/A	Suppressed
	Rearward	N/A	N/A	Suppressed

* The CRS would not fit in this Forward Seat Slide position. If there is a number in the Seat Slide column, it indicates the fore-aft detent position with respect to the foremost position. (1 = Full Forward; 23 = Full Rearward; 23 total Seat Slide detents)

DATA SHEET 15 SUMMARY

Suppression Test Using 12-month-old CRABI Dummy (Part 572, Subpart R)
Section B Rear Facing CRS

NHTSA No.:	C45603	TEST DATE:	6/22/04
LABORATORY:	MGA	TECHNICIANS:	JL/TB
DUMMY TYPE:	12 Month Old	DUMMY SERIAL NO.:	082

CHILD RESTRAINT NAME:	Graco
CHILD RESTRAINT MODEL:	Infant 8457
DATE OF MANUFACTURE:	8-31-2000

Base: __On X Off __N/A-Restraint does not have a removable base

Manufacturer's design seat back angle: 25.0° On Seat Back

Tested seat back angle: 25.0° On Seat Back

Manufacturer's specified anchorage position: Middle

Tested anchorage position: Middle

A blanket and visor were not used in the suppression testing because they did not affect the weight sensing system used on the vehicle.

Test Summary

Seat Belt	Seat Slide	Cinch Load (N)	Handle Down	Handle Up
Belted Rear Facing	Forward 6 *	127	N/A	Suppressed
	Middle	130	N/A	Suppressed
	Rearward	133	N/A	Suppressed
Unbelted Rear Facing	Forward 5 *	N/A	N/A	Suppressed
	Middle	N/A	N/A	Suppressed
	Rearward	N/A	N/A	Suppressed
Unbelted Forward Facing	Forward 4 *	N/A	N/A	Suppressed
	Middle	N/A	N/A	Suppressed
	Rearward	N/A	N/A	Suppressed

Successful Unbelted 5th percentile Female Dummy Reactivation was performed with the seat in the Forward position. (SN507)

* The CRS would not fit in this Forward Seat Slide position. If there is a number in the Seat Slide column, it indicates the fore-aft detent position with respect to the foremost position. (1 = Full Forward; 23 = Full Rearward; 23 total Seat Slide detents)

DATA SHEET 15 SUMMARY

Suppression Test Using 12-month-old CRABI Dummy (Part 572, Subpart R)
Section C Forward Facing Convertible CRS

NHTSA No.:	C45603	TEST DATE:	6/21/04
LABORATORY:	MGA	TECHNICIANS:	JL/TB
DUMMY TYPE:	12 Month Old	DUMMY SERIAL NO.:	082

CHILD RESTRAINT NAME:	Britax
CHILD RESTRAINT MODEL:	Roundabout 161
DATE OF MANUFACTURE:	7-21-2000

Base: __On __Off X N/A-Restraint does not have a removable base

Manufacturer's design seat back angle: 25.0° On Seat Back

Tested seat back angle: 25.0° On Seat Back

Manufacturer's specified anchorage position: Middle

Tested anchorage position: Middle

A blanket was not used in the suppression testing because it did not affect the weight sensing system used on the vehicle.

Test Summary

Seat Belt	Seat Slide	Cinch Load (N)	No Blanket
Belted Forward Facing	Forward	130	Suppressed
	Middle	130	Suppressed
	Rearward	132	Suppressed
Unbelted Forward Facing	Forward	N/A	Suppressed
	Middle	N/A	Suppressed
	Rearward	N/A	Suppressed
Belted Rear Facing	Forward	130	Suppressed
	Middle	127	Suppressed
	Rearward	128	Suppressed
Unbelted Rear Facing	Forward	N/A	Suppressed
	Middle	N/A	Suppressed
	Rearward	N/A	Suppressed

Successful Unbelted 5th percentile Female Dummy Reactivation was performed with the seat in the Rearward position. (SN507)

DATA SHEET 15 SUMMARY

Suppression Test Using 12-month-old CRABI Dummy (Part 572, Subpart R)
Section C Forward Facing Convertible CRS

NHTSA No.:	C45603	TEST DATE:	6/21/04
LABORATORY:	MGA	TECHNICIANS:	JL/TB
DUMMY TYPE:	12 Month Old	DUMMY SERIAL NO.:	082

CHILD RESTRAINT NAME:	Century
CHILD RESTRAINT MODEL:	Encore 4612
DATE OF MANUFACTURE:	8-16-2000

Base: __On __Off X N/A-Constraint does not have a removable base

Manufacturer's design seat back angle: 25.0° On Seat Back

Tested seat back angle: 25.0° On Seat Back

Manufacturer's specified anchorage position: Middle

Tested anchorage position: Middle

A blanket was not used in the suppression testing because it did not affect the weight sensing system used on the vehicle.

Test Summary

Seat Belt	Seat Slide	Cinch Load (N)	No Blanket
Belted Forward Facing	Forward	130	Suppressed
	Middle	129	Suppressed
	Rearward	127	Suppressed
Unbelted Forward Facing	Forward	N/A	Suppressed
	Middle	N/A	Suppressed
	Rearward	N/A	Suppressed
Belted Rear Facing	Forward	127	Suppressed
	Middle	128	Suppressed
	Rearward	133	Suppressed
Unbelted Rear Facing	Forward	N/A	Suppressed
	Middle	N/A	Suppressed
	Rearward	N/A	Suppressed

Successful Unbelted 5th percentile Female Dummy Reactivation was performed with the seat in the Middle position. (SN507)

DATA SHEET 15 SUMMARY

Suppression Test Using 12-month-old CRABI Dummy (Part 572, Subpart R)
Section C Forward Facing Convertible CRS

NHTSA No.:	C45603	TEST DATE:	6/21/04
LABORATORY:	MGA	TECHNICIANS:	JL/TB
DUMMY TYPE:	12 Month Old	DUMMY SERIAL NO.:	082

CHILD RESTRAINT NAME:	Evenflo
CHILD RESTRAINT MODEL:	Medallion 254
DATE OF MANUFACTURE:	6-1-2000

Base: __On __Off X N/A-Restraint does not have a removable base

Manufacturer's design seat back angle: 25.0° On Seat Back

Tested seat back angle: 25.0° On Seat Back

Manufacturer's specified anchorage position: Middle

Tested anchorage position: Middle

A blanket was not used in the suppression testing because it did not affect the weight sensing system used on the vehicle.

Test Summary

Seat Belt	Seat Slide	Cinch Load (N)	No Blanket
Belted Forward Facing	Forward	127	Suppressed
	Middle	130	Suppressed
	Rearward	131	Suppressed
Unbelted Forward Facing	Forward	N/A	Suppressed
	Middle	N/A	Suppressed
	Rearward	N/A	Suppressed
Belted Rear Facing	Forward	131	Suppressed
	Middle	130	Suppressed
	Rearward	133	Suppressed
Unbelted Rear Facing	Forward	N/A	Suppressed
	Middle	N/A	Suppressed
	Rearward	N/A	Suppressed

Successful Unbelted 5th percentile Female Dummy Reactivation was performed with the seat in the Forward position. (SN507)

DATA SHEET 16 SUMMARY

Suppression Test Using Newborn Infant Dummy (Part 572, Subpart K) Section A Car Bed

NHTSA No.:	C45603	TEST DATE:	6/22/04
LABORATORY:	MGA	TECHNICIANS:	JL/TB
DUMMY TYPE:	Newborn Infant	DUMMY SERIAL NO.:	003

CAR BED NAME:	Cosco
CAR BED MODEL:	Dream Ride 02-719
DATE OF MANUFACTURE:	6-16-2000

Base: __On __Off X N/A-Constraint does not have a removable base
(A car bed with a removable base shall be treated as two separate models, i.e. this form and test procedure will be completed with the base on and then repeated on a new form with the base off.

Manufacturer's design seat back angle: 25.0° On Seat Back
Tested seat back angle: 25.0° On Seat Back
Manufacturer's specified anchorage position: Middle
Tested anchorage position: Middle

A blanket and visor were not used in the suppression testing because they did not affect the weight sensing system used on the vehicle.

Test Summary

Seat Belt	Seat Slide	Handle Down	Handle Up
Belted	Forward	Won't Fit	N/A
	Middle	Suppressed	N/A
	Rearward	Won't Fit	N/A

Successful Unbelted 5th percentile Female Dummy Reactivation was performed with the seat in the Middle position. (SN507)

The CRS would not fit in the Forward Seat Slide position due to interference with the transmission shifter.

The CRS would not fit in the Rearward Seat Slide position due to interference with the center console.

DATA SHEET 17 SUMMARY

Suppression Test Using 3 Year Old Dummy And Booster Seats (Part 572, Subpart P)
Section D Forward Facing Belt Positioning Booster

NHTSA No.:	C45603	TEST DATE:	6/22/04
LABORATORY:	MGA	TECHNICIANS:	JL/TB
DUMMY TYPE:	3 Year Old	DUMMY SERIAL NO.:	032

BOOSTER SEAT NAME:	Century
BOOSTER SEAT MODEL:	Next Step 4920
DATE OF MANUFACTURE:	8-16-2000

Manufacturer's design seat back angle: 25.0° On Seat Back
Tested seat back angle: 25.0° On Seat Back
Manufacturer's specified anchorage position: Middle
Tested anchorage position: Middle

Test Summary

Seat Belt	Seat Slide	Cinch Load (N)	No Blanket
Belted Forward Facing Without Harness	Forward	18	Suppressed
	Middle	12	Suppressed
	Rearward	9	Suppressed
Belted Forward Facing Cinched With Harness	Forward	133	Suppressed
	Middle	131	Suppressed
	Rearward	132	Suppressed

Successful Unbelted 5th percentile Female Dummy Reactivation was performed with the seat in the Rearward position. (SN507)

DATA SHEET 17 SUMMARY

Suppression Test Using 3 Year Old Dummy And Booster Seats (Part 572, Subpart P)
Section D Forward Facing Toddler Belt Positioning Booster Seat

NHTSA No.:	C45603	TEST DATE:	6/22/04
LABORATORY:	MGA	TECHNICIANS:	JL/TB
DUMMY TYPE:	3 Year Old	DUMMY SERIAL NO.:	032

BOOSTER SEAT NAME:	Cosco
BOOSTER SEAT MODEL:	High Back Booster 02-442
DATE OF MANUFACTURE:	4-28-2000

Manufacturer's design seat back angle: 25.0° On Seat Back
Tested seat back angle: 25.0° On Seat Back
Manufacturer's specified anchorage position: Middle
Tested anchorage position: Middle

Test Summary

Seat Belt	Seat Slide	Cinch Load (N)	No Blanket
Belted Forward Facing Without Harness	Forward 8 *	17	Suppressed
	Middle	14	Suppressed
	Rearward	16	Suppressed
Belted Forward Facing Cinched With Harness	Forward 8 *	128	Suppressed
	Middle	129	Suppressed
	Rearward	131	Suppressed

Successful Unbelted 5th percentile Female Dummy Reactivation was performed with the seat in the Rearward position. (SN507)

* The CRS would not fit in this Forward Seat Slide position. If there is a number in the Seat Slide column, it indicates the fore-aft detent position with respect to the foremost position. (1 = Full Forward; 23 = Full Rearward; 23 total Seat Slide detents)

DATA SHEET 18 SUMMARY

Suppression Test Using 3 Year Old Dummy And Convertible Restraints (Part 572, Subpart P)
Section C Forward Facing Convertible CRS

NHTSA No.:	C45603	TEST DATE:	6/22/04
LABORATORY:	MGA	TECHNICIANS:	JL/TB
DUMMY TYPE:	3 Year Old	DUMMY SERIAL NO.:	032

CHILD RESTRAINT NAME:	Britax
CHILD RESTRAINT MODEL:	Roundabout 161
DATE OF MANUFACTURE:	7-21-2000

Manufacturer's design seat back angle: 25.0° On Seat Back
Tested seat back angle: 25.0° On Seat Back
Manufacturer's specified anchorage position: Middle
Tested anchorage position: Middle

Test Summary

Seat Belt	Seat Slide	Cinch Load (N)	Result
Belted	Forward	128	Suppressed
	Middle	131	Suppressed
	Rearward	133	Suppressed

Successful Unbelted 5th percentile Female Dummy Reactivation was performed with the seat in the Forward position. (SN507)

DATA SHEET 18 SUMMARY

Suppression Test Using 3 Year Old Dummy And Convertible Restraints (Part 572, Subpart P)
Section C Forward Facing Convertible CRS

NHTSA No.:	C45603	TEST DATE:	6/22/04
LABORATORY:	MGA	TECHNICIANS:	JL/TB
DUMMY TYPE:	3 Year Old	DUMMY SERIAL NO.:	032

CHILD RESTRAINT NAME:	Century
CHILD RESTRAINT MODEL:	Encore 4612
DATE OF MANUFACTURE:	8-16-2000

Manufacturer's design seat back angle: 25.0° On Seat Back
Tested seat back angle: 25.0° On Seat Back
Manufacturer's specified anchorage position: Middle
Tested anchorage position: Middle

Test Summary

Seat Belt	Seat Slide	Cinch Load (N)	Result
Belted	Forward 1 *	129	Suppressed
	Middle	130	Suppressed
	Rearward	132	Suppressed

Successful Unbelted 5th percentile Female Dummy Reactivation was performed with the seat in the Middle position. (SN507)

* The CRS would not fit in this Forward Seat Slide position. If there is a number in the Seat Slide column, it indicates the fore-aft detent position with respect to the foremost position. (1 = Full Forward; 23 = Full Rearward; 23 total Seat Slide detents)

DATA SHEET 18 SUMMARY

Suppression Test Using 3 Year Old Dummy And Convertible Restraints (Part 572, Subpart P)
Section C Forward Facing Convertible CRS

NHTSA No.:	C45603	TEST DATE:	6/27/04
LABORATORY:	MGA	TECHNICIANS:	JL/TB
DUMMY TYPE:	3 Year Old	DUMMY SERIAL NO.:	032

CHILD RESTRAINT NAME:	Evenflo
CHILD RESTRAINT MODEL:	Medallion 254
DATE OF MANUFACTURE:	6-1-2000

Manufacturer's design seat back angle: 25.0° On Seat Back
Tested seat back angle: 25.0° On Seat Back
Manufacturer's specified anchorage position: Middle
Tested anchorage position: Middle

Test Summary

Seat Belt	Seat Slide	Cinch Load (N)	Result
Belted	Forward 3 *	127	Suppressed
	Middle	130	Suppressed
	Rearward	131	Suppressed

Successful Unbelted 5th percentile Female Dummy Reactivation was performed with the seat in the Rearward position. (SN507)

* The CRS would not fit in this Forward Seat Slide position. If there is a number in the Seat Slide column, it indicates the fore-aft detent position with respect to the foremost position. (1 = Full Forward; 23 = Full Rearward; 23 total Seat Slide detents)

DATA SHEET 19 SUMMARY

Suppression Test Using An Unbelted 3 Year Old Dummy (Part 572, Subpart P)
No CRS

NHTSA No.:	C45603	TEST DATE:	6/22/04
LABORATORY:	MGA	TECHNICIANS:	JL/TB
DUMMY TYPE:	3 Year Old	DUMMY SERIAL NO.:	031

Test Summary

Position	Seat Slide	Seat Back Angle	Result
Position 1 Sitting on seat with back against seat back	Forward 25 *	25.0 On Seat Back	Suppressed
	Middle	25.0 On Seat Back	Suppressed
	Rearward	25.0 On Seat Back	Suppressed
Position 2 Sitting on seat with back against reclined seat back	Forward 25 *	49.7 On Seat Back	Suppressed
	Middle	49.7 On Seat Back	Suppressed
	Rearward	49.7 On Seat Back	Suppressed
Position 3 Sitting on seat with back not against seat back	Forward 50 *	25.0 On Seat Back	Suppressed
	Middle	25.0 On Seat Back	Suppressed
	Rearward	25.0 On Seat Back	Suppressed
Position 4 Sitting on seat edge, spine vertical, hands at dummy's sides	Forward 25 *	25.0 On Seat Back	Suppressed
	Middle	25.0 On Seat Back	Suppressed
	Rearward	25.0 On Seat Back	Suppressed
Position 5 Standing on seat, facing forward	Forward 25 *	31.4 On Seat Back **	Suppressed
	Middle	31.4 On Seat Back **	Suppressed
	Rearward	31.4 On Seat Back **	Suppressed
Position 6 Kneeling on seat, facing forward	Forward 25 *	25.0 On Seat Back	Suppressed
	Middle	25.0 On Seat Back	Suppressed
	Rearward	25.0 On Seat Back	Suppressed
Position 7 Kneeling on seat, facing rearward	Forward 25 *	25.0 On Seat Back	Suppressed
	Middle	25.0 On Seat Back	Suppressed
	Rearward	25.0 On Seat Back	Suppressed
Position 8 Lying on seat. (Three designated seating positions only)	Forward	25.0 On Seat Back	N/A
	Middle	25.0 On Seat Back	N/A
	Rearward	25.0 On Seat Back	N/A

Successful Unbelted 5th percentile Female Dummy Reactivation was performed with the seat in the Rearward position. (SN507)

* The ATD would not fit in this Forward Seat Slide position. If there is a number in the Seat Slide column, it indicates the fore-aft position with respect to the foremost position. (1 = Full Forward; 23 = Full Rearward; 23 total Seat Slide detents)

** The ATD contacted the roof at the design seat back angle. The seat back was reclined to 31.4° to achieve clearance.

DATA SHEET 25 SUMMARY

Low Risk Deployment Tests Using an Unbelted 6-Year-Old Dummy
(Part 572, Subpart N) (S24)
Position 1 - Chest On Instrument Panel (S24.4.2)

NHTSA No.:	C45603	TEST DATE:	6-24-04
LABORATORY:	MGA	TECHNICIANS:	CN/DW/BR
DUMMY TYPE:	6-Year-Old	DUMMY SERIAL NO.:	153

Manufacturer's design seat back angle: 25° on Seat Back; 7th notch
 Tested seat back angle: 25° on Seat Back; 7th notch
 Tested seat position: Full Aft

Thorax cavity angle: 6.0°
 Point 1 height: 82 mm Below Airbag

Air Bag Deployment Timing

Stage No.	Firing time (ms)	Recorded firing time (ms)
1	0.0	0.0
2	300.0	300.1

6-Year-Old SN 153 Position 1 (Chest On Instrument Panel) 6-24-04

Injury Criteria	Max. Allowable Injury Assessment Values	Measured Value
HIC15	700	9
Peak Nij (Nte)	1.0	0.2
Time (ms)	NA	24.1
Peak Nij (Ntf)	1.0	0.2
Time (ms)	NA	19.5
Peak Nij (Nce)	1.0	0.1
Time (ms)	NA	9.8
Peak Nij (Ncf)	1.0	0.1
Time (ms)	NA	10.5
Neck Tension	1490 N	375
Neck Compression	1820 N	212
Chest g	60 g	13
Chest Displacement	40 mm	8

Calculated on data recorded for 100 ms after the initial deployment of the air bag. (S4.11(b))

DATA SHEET 26 SUMMARY

Low Risk Deployment Tests Using an Unbelted 6-Year-Old Dummy
(Part 572, Subpart N) (S24)
Position 2 - Head On Instrument Panel (S24.4.3)

NHTSA No.:	C45603	TEST DATE:	7-08-04
LABORATORY:	MGA	TECHNICIANS:	WD/DW/BR
DUMMY TYPE:	6-Year-Old	DUMMY SERIAL NO.:	153

Manufacturer's design seat back angle: 25° on Seat Back; 7th notch
 Tested seat back angle: 25° on Seat Back; 7th notch
 Tested seat position: Full Forward

Thorax cavity angle: 36.1°
 Thigh Angle: 9.2°

Air Bag Deployment Timing

Stage No.	Firing time (ms)	Recorded firing time (ms)
1	0.0	0.0
2	300.0	300.0

6-Year-Old SN 152 Position 2 (Head On Instrument Panel) 7-08-04

Injury Criteria	Max. Allowable Injury Assessment Values	Measured Value
HIC15	700	5
Peak Nij (Nte)	1.0	0.2
Time (ms)	NA	8.4
Peak Nij (Ntf)	1.0	0.0
Time (ms)	NA	0.1
Peak Nij (Nce)	1.0	0.7
Time (ms)	NA	17.6
Peak Nij (Ncf)	1.0	0.2
Time (ms)	NA	33.0
Neck Tension	1490 N	432
Neck Compression	1820 N	1281
Chest g	60 g	11
Chest Displacement	40 mm	0.5

Calculated on data recorded for 100 ms after the initial deployment of the air bag. (S4.11(b))

DATA SHEET 27 SUMMARY

Low Risk Deployment Tests Using an Unbelted 5th Percentile Female
Dummy (Part 572, Subpart O) (S26)
Position 1 - Chin On Module (S26.2)

NHTSA No.:	C45603	TEST DATE:	6/24/04
LABORATORY:	MGA	TECHNICIANS:	CN/DW/BR
DUMMY TYPE:	5 th Percentile Female	DUMMY SERIAL NO.:	505

Manufacturer's design seat back angle: 25.0° On Seat Back
Tested seat back angle: 25.0° On Seat Back (Power Seat)
Tested seat position: Full Aft

Tested steering wheel angle: 21.0°
Thorax cavity angle: 27.0°
Chin Point height: 3 mm Above Module

Air Bag Deployment Timing

Stage No.	Firing time (ms)	Recorded firing time (ms)
1	0.0	0.0
2	100.0	99.8

5th Percentile Female SN 516 Position 1 (Chin On Module) 6-24-04

Injury Criteria	Max. Allowable Injury Assessment Values	Measured Value
HIC15	700	7
Peak Nij (Nte)	1.0	0.4
Time (ms)	NA	11.5
Peak Nij (Ntf)	1.0	0.1
Time (ms)	NA	7.1
Peak Nij (Nce)	1.0	0.0
Time (ms)	NA	1.3
Peak Nij (Ncf)	1.0	0.0
Time (ms)	NA	5.3
Neck Tension	2070 N	855
Neck Compression	2520 N	6
Chest g	60 g	7
Chest Displacement	52 mm	4
Left Femur	6805 N	59
Right Femur	6805 N	40

Calculated on data recorded for 125 ms after the initiation of the final stage of air bag deployment designed to deploy in any full frontal rigid barrier crash up to 26 km/h. (S4.11(d))
Second stage fire time of 100 ms; Injuries calculated on 0 ms to 255 ms

DATA SHEET 28 SUMMARY

Low Risk Deployment Tests Using an Unbelted 5th Percentile Female
Dummy (Part 572, Subpart O) (S26)
Position 2 - Chin On Rim (S26.3)

NHTSA No.:	C45603	TEST DATE:	7/08/04
LABORATORY:	MGA	TECHNICIANS:	WD/DW/BR
DUMMY TYPE:	5 th Percentile Female	DUMMY SERIAL NO.:	506

Manufacturer's design seat back angle: 25.0° On Seat Back
 Tested seat back angle: 25.0° On Seat Back (Power Seat)
 Tested seat position: Full Aft

Tested steering wheel angle: 18.1°
 Thorax cavity angle: 24.2°
 Chin Point height: 0 mm

*The dummy contacted the windshield with the steering wheel at mid position. The steering controls were adjusted to lower the upper steering wheel rim the necessary amount to bring the Chin Point coincident with the upper steering wheel rim. The rear thorax cavity was adjusted along with the steering wheel angle.

Air Bag Deployment Timing

Stage No.	Firing time (ms)	Recorded firing time (ms)
1	0.0	0.0
2	100.0	99.8

5th Percentile Female SN 516 Position 2 (Chin On Rim) 7-8-04

Injury Criteria	Max. Allowable Injury Assessment Values	Measured Value
HIC15	700	16
Peak Nij (Nte)	1.0	0.7
Time (ms)	NA	16.0
Peak Nij (Ntf)	1.0	0.3
Time (ms)	NA	69.1
Peak Nij (Nce)	1.0	0.3
Time (ms)	NA	21.9
Peak Nij (Ncf)	1.0	0.2
Time (ms)	NA	29.1
Neck Tension	2070 N	912
Neck Compression	2520 N	85
Chest g	60 g	20
Chest Displacement	52 mm	25
Left Femur	6805 N	53
Right Femur	6805 N	31

Calculated on data recorded for 125 ms after the initiation of the final stage of air bag deployment designed to deploy in any full frontal rigid barrier crash up to 26 km/h. (S4.11(d))
 Second stage fire time of 100 ms; Injuries calculated on 0 ms to 255 ms

DATA SHEET 30 VEHICLE WEIGHT, FUEL TANK, AND ATTITUDE DATA

Test Vehicle: 2004 Mitsubishi Galant 4 Door
 Test Program: FMVSS 208 Compliance
 Test Technician: Clark Subrt

NHTSA No.: C45603
 Test Date: 7/23/04

IMPACT ANGLE:	Zero Degrees		
BELTED DUMMIES (YES/NO):	No – Front Occupants No – Center Rear Passenger		
TEST SPEED:	X 32 to 40 kmph	0 to 48 kmph	0 to 56 kmph
DRIVER DUMMY:	X 5 TH female		50 th Male
PASSENGER DUMMY:	X 5 TH female		50th Male

- | | | |
|----------|-----|---|
| X | 1. | Fill the transmission with transmission fluid to the satisfactory range. |
| X | 2. | Drain fuel from vehicle |
| X | 3. | Run the engine until fuel remaining in the fuel delivery system is used and the engine stops. |
| X | 4. | Record the useable fuel tank capacity supplied by the COTR |
| X | | Useable Fuel Tank Capacity supplied by COTR: 67 liters (17.7 gallons) |
| X | 5. | Record the fuel tank capacity supplied in the owner's manual. |
| X | | Useable Fuel Tank Capacity in owner's manual: 67 liters (17.7 gallons) |
| X | 6. | Using purple dyed Stoddard solvent having the physical and chemical properties of Type 1 solvent or cleaning fluid, Table 1, ASTM Standard D484-71, "Standard Specifications for Hydrocarbon Dry-cleaning Solvents," or gasoline, fill the fuel tank. |
| X | | Amount Added: 67 liters (17.7 gallons) |
| X | 7. | Fill the coolant system to capacity. |
| X | 8. | Fill the engine with motor oil to the Max. mark on the dip stick. |
| X | 9. | Fill the brake reservoir with brake fluid to its normal level. |
| X | 10. | Fill the windshield washer reservoir to capacity. |
| X | 11. | Inflate the tires to the tire pressure on the tire placard. If no tire placard is available, inflate the tires to the recommended pressure in the owner's manual. |

Tire placard pressure:	RF:	32 psi	LF:	32 psi	RR:	32 psi	LR:	32 psi
Owner's manual pressure:	RF:	32 psi	LF:	32 psi	RR:	32 psi	LR:	32 psi
Actual inflated pressure:	RF:	32 psi	LF:	32 psi	RR:	32 psi	LR:	32 psi

- | | | |
|----------|-----|--|
| X | 12. | Record the vehicle weight at each wheel to determine the unloaded vehicle weight (UVW), i.e. "as delivered" weight). |
|----------|-----|--|

Right Front (kg):	455.0	Right Rear (kg):	317.1
Left Front (kg):	473.6	Left Rear (kg):	319.3
Total Front (kg):	928.6	Total Rear (kg):	636.4
% Total Weight:	59.3	% Total Weight:	40.7
UVW = TOTAL FRONT PLUS TOTAL REAR (KG):		1565.0	

- | | | |
|----------|------|---|
| X | 13. | UVW Test Vehicle Attitude: (All dimensions in millimeters) |
| X | 13.1 | Mark a point on the vehicle above the center of each wheel. |
| X | 13.2 | Place the vehicle on a level surface. |

- ☒ 13.3 Measure perpendicular to the level surface to the 4 points marked on the body and record the measurements

RF:	734	LF:	729	RR:	711	LR:	710
-----	-----	-----	-----	-----	-----	-----	-----

- ☒ 14. Calculate the Rated Cargo and Luggage Weight (RCLW).
- ☒ 14.1 Does the vehicle have the vehicle capacity weight (VCW) on the certification label or tire placard?
- ☒ Yes, go to 14.3 On inside left front door frame
- ☐ No, go to 14.2
- ☐ 14.2 VCW = Gross Vehicle Weight – UVW

$$VCW = \underline{\hspace{2cm}} - \underline{\hspace{2cm}} = \underline{\hspace{2cm}}$$

- ☒ 14.3 VCW = 375 kg (827 lbs)
- ☒ 14.4 Does the certification or tire placard contain the Designated Seating Capacity (DSC)?

- ☒ Yes, go to 14.6
- ☐ No, go to 14.5 and skip 14.6

- ☐ 14.5 DSC = Total number of seat belt assemblies =

- ☒ 14.6 DSC = 5

- ☒ 14.7 RCLW = VCW – (68 kg x DSC) = 375 kg - (68 kg x 5) = 35 kg

- ☒ 14.8 Is the vehicle certified as a truck, MPV or bus (see the certification label on the door jamb)?

- ☐ Yes, if the calculated RCLW is greater than 136 kg, use 136 kg as the RCLW. (S8.1.1)
- ☒ No, use the RCLW calculated in 14.7

- ☒ 15. Fully Loaded Weight (100% fuel fill)
- ☒ 15.1 Place the appropriate test dummy in both front outboard seating positions.

Driver: X 5th female 50th male

Passenger: X 5th female 50th male

- ☒ 15.2 Load the vehicle with the RCLW from 14.7 or 14.8 whichever is applicable.
- ☒ 15.3 Place the RCLW in the cargo area. Center the load over the longitudinal centerline of the vehicle. (S8.1.1 (d))
- ☒ 15.4 Record the vehicle weight at each wheel to determine the Fully Loaded Weight.

Right Front (kg):	479.0	Right Rear (kg):	348.8
Left Front (kg):	512.6	Left Rear (kg):	361.5
Total Front (kg):	991.6	Total Rear (kg):	710.3
% Total Weight:	58.3	% Total Weight:	41.7
% GVW	53.1	% GVW	46.9
Fully Loaded Weight = Total Front Plus Total Rear (kg):		1701.9	

- ☒ 16. Fully Loaded Test Vehicle Attitude: (All dimensions in millimeters)
- ☒ 16.1 Place the vehicle on a level surface.

- ☒ 16.2 Measure perpendicular to the level surface to the 4 points marked on the body (see 13.1 above) and record the measurements

RF:	716	LF:	724	RR:	703	LR:	694
-----	-----	-----	-----	-----	-----	-----	-----

- ☒ 17. Drain the fuel system

- ☒ 18. Using purple dyed Stoddard solvent having the physical and chemical properties of Type 1 solvent or cleaning fluid, Table 1, ASTM Standard D484-71, "Standard Specifications for Hydrocarbon Dry-cleaning Solvents," fill the fuel tank to 92 - 94 percent of useable capacity.

☒ Fuel tank capacity x .94 = 67.0 liters (17.7 gallons) x .94 = 62.8 liters (16.6 gallons)

☒ Amount added 62.8 liters (16.6 gallons) 94%

- ☒ 19. Crank the engine to fill the fuel delivery system with Stoddard solvent

- ☒ 20. Calculate the test weight range.

- ☒ 20.1 Calculated Weight = UVW (see 12 above) + RCLW (see 14 above) + 2x(dummy weight)

$$1698.0 \text{ kg} = 1565.0 \text{ kg} + 35.0 \text{ kg} + 98.0 \text{ kg}$$

- ☒ 20.2 Test Weight Range = Calculated Weight (- 4.5 kg, - 9 kg.)

$$\text{Max. Test Weight} = \text{Calculated Test Weight} - 4.5 \text{ kg} = \underline{1693.5 \text{ kg}}$$

$$\text{Min. Test Weight} = \text{Calculated Test Weight} - 9 \text{ kg} = \underline{1689.0 \text{ kg}}$$

- ☒ 21. Remove the RCLW from the cargo area.

- ☒ 22. Drain transmission fluid, engine coolant, motor oil, and windshield washer fluid from the test vehicle so that Stoddard solvent leakage from the fuel system will be evident.

- ☒ 23. Vehicle Components Removed For Weight Reduction:
Tool & jack, trunk room trims, rear seat, and spare tire

- ☒ 24. Secure the equipment and ballast in the load carrying area and distribute it, as nearly as possible, to obtain the proportion of axle weight indicated by the gross axle weight ratings and center it over the longitudinal centerline of the vehicle.

- ☒ 25. If necessary, add ballast to achieve the actual test weight.

☐ N/A

☒ Weight of Ballast: 20.4 kg in trunk

- ☒ 26. Ballast, including test equipment, must be contained so that it will not shift during the impact event or interfere with data collection or interfere with high-speed film recordings or affect the structural integrity of the vehicle or do anything else to affect test results. Care must be taken to assure that any attachment hardware added to the vehicle is not in the vicinity of the fuel tank or lines.

- ☒ 27. Record the vehicle weight at each wheel to determine the actual test weight.

Right Front (kg):	496.7	Right Rear (kg):	345.2
Left Front (kg):	504.4	Left Rear (kg):	343.4
Total Front (kg):	1001.1	Total Rear (kg):	688.6
% Total Weight:	59.2	% Total Weight:	40.8
% GVW	53.1	% GVW	46.9
(% GVW = Axle GVW divided by Vehicle GVW)			
TOTAL FRONT PLUS TOTAL REAR (kg):			1689.7

- ☒ 28. Is the test weight between the Max. Weight and the Min. Weight (See 20.2)?

☒ Yes

☐ No, explain why not.

- ☒ 29. Test Weight Vehicle Attitude: (all dimensions in millimeters)
- ☒ 29.1 Place the vehicle on a level surface
- ☒ 29.2 Measure perpendicular to the level surface to the 4 points marked on the body (see 13 above) and record the measurements

RF:	724	LF:	724	RR:	705	LR:	700
-----	-----	-----	-----	-----	-----	-----	-----

- ☒ 30. Summary of test attitude
- ☒ 30.1 AS DELIVERED:

RF:	734	LF:	729	RR:	711	LR:	710
-----	-----	-----	-----	-----	-----	-----	-----

AS TESTED:

RF:	724	LF:	724	RR:	705	LR:	700
-----	-----	-----	-----	-----	-----	-----	-----

FULLY LOADED:

RF:	716	LF:	724	RR:	703	LR:	694
-----	-----	-----	-----	-----	-----	-----	-----

- ☒ 30.2 Is the "as tested" test attitude equal to or between the "fully loaded" and "as delivered" attitude?
- ☒ Yes
- ☐ No, explain why not.

REMARKS: NONE

I certify that I have read and performed each instruction.

Signature: Clark Sulest

Date: 7/23/04

DATA SHEET 31

VEHICLE ACCELEROMETER LOCATION AND MEASUREMENT

Test Vehicle: 2004 Mitsubishi Galant 4 Door
 Test Program: FMVSS 208 Compliance
 Test Technician: Clark Subrt

NHTSA No.: C45603
 Test Date: 7/23/04

IMPACT ANGLE:	Zero Degrees		
BELTED DUMMIES (YES/NO):	No – Front Occupants Yes – Center Rear Passenger		
TEST SPEED:	X 32 to 40 kmph	0 to 48 kmph	0 to 56 kmph
DRIVER DUMMY:	X 5 TH female		50 th Male
PASSENGER DUMMY:	X 5 TH female		50th Male

- X

 1. Find the location where the vertical plane parallel to the longitudinal centerline of the vehicle and through the center of the left front outboard seating position intersects the left rear seat cross member. Install an accelerometer at this intersection on the rear seat cross member to record x-direction accelerations. Record the location on the following chart.
- X

 2. Find the location where the vertical plane parallel to the longitudinal centerline of the vehicle and through the center of the right front outboard seating position intersects the right rear seat cross member. Install an accelerometer at this intersection on the rear seat cross member to record x-direction accelerations. Record the location on the following chart.
- X

 3. Find the location where a vertical plane through the longitudinal centerline of the vehicle and a vertical transverse plane through the center of the two wheels on opposite sides of the engine intersect at the top of the engine. Install an accelerometer at this intersection to record x-direction accelerations. Record the location on the following chart.
- X

 4. Find the location where a vertical plane through the longitudinal centerline of the vehicle and a vertical transverse plane through the center of the two wheels on opposite sides of the engine intersect the bottom of the engine. Install an accelerometer at this intersection to record x-direction accelerations. Record the location on the following chart.
- X

 5. Install an accelerometer on the right front brake caliper to record x-direction accelerations. Record the location on the following chart.
- X

 6. Find the location where a vertical plane through the longitudinal centerline of the vehicle intersects the top of the instrument panel. Install an accelerometer at this intersection to record x-direction accelerations. Record the location on the following chart.
- X

 7. Install an accelerometer on the left front brake caliper to record x-direction accelerations. Record the location on the following chart.
- X

 8. Find the location where a vertical plane through the longitudinal centerline of the vehicle intersects the floor of the trunk. Install an accelerometer on the trunk floor at this intersection to record z-direction accelerations. Record the location on the following chart.

REMARKS: NONE


I certify that I have read and performed each instruction.

Signature: 

Date: 7/23/04


VEHICLE ACCELEROMETER LOCATION AND DATA SUMMARY

CENTERLINE OF
FRONT WHEELS



ACCELEROMETER
COORDINATE SYSTEM
(POSITIVE DIRECTION SHOWN)

REAR SEAT CUSHION
ASSY. FRONT ATTACHMENT
BRACKET SUPPORT



Dimensions Corresponding To The Letters "A" Through "K" (Excluding "I") Are
Recorded In The Table On The Following Page.
Accelerometers Corresponding To The Numbers 1 Through 8 Are Specified On The
Preceding Page.

DATA SHEET 31
VEHICLE ACCELEROMETER LOCATION AND MEASUREMENTS

<u>DIMENSION</u>	<u>LENGTH (mm)</u>	
<u>PRETEST VALUES</u>		
<u>A</u> (LH Rear Seat Xmbr)	392	
<u>B</u> (RH Rear Seat Xmbr)	392	
<u>C</u> (Engine Top)	4041	
<u>D</u> (Engine Bottom)	4052	
<u>E</u> (Caliper)	Right Side 3904	Left Side 3904
<u>F</u> (Left Caliper)	716	
<u>G</u> (IP)	3128	
<u>H</u> (Seat)	1800	
<u>J</u> (Right Caliper)	716	
<u>K</u> (Trunk)	314	
<u>POST TEST VALUES</u>		
<u>A</u> (LH Rear Seat Xmbr)	392	
<u>B</u> (RH Rear Seat Xmbr)	392	
<u>C</u> (Engine Top)	4018	
<u>D</u> (Engine Bottom)	4022	
<u>E</u> (Caliper)	Right Side 3845	Left Side 3842
<u>F</u> (Left Caliper)	686	
<u>G</u> (IP)	3120	
<u>H</u> (Seat)	1810	
<u>J</u> (Right Caliper)	701	
<u>K</u> (Trunk)	312	

DATA SHEET 32

PHOTOGRAPHIC TARGETS

Test Vehicle: 2004 Mitsubishi Galant 4 Door
 Test Program: FMVSS 208 Compliance
 Test Technician: Clark Subrt

NHTSA No.: C45603
 Test Date: 7/23/04

IMPACT ANGLE:	Zero Degrees		
BELTED DUMMIES (YES/NO):	No – Front Occupants No – Center Rear Passenger		
TEST SPEED:	<u>X</u> 32 to 40 kmph	<u> </u> 0 to 48 kmph	<u> </u> 0 to 56 kmph
DRIVER DUMMY:	<u>X</u> 5 TH female	<u> </u> 50 th Male	
PASSENGER DUMMY:	<u>X</u> 5 TH female	<u> </u> 50th Male	

- | | | |
|--|------|--|
| <div style="border: 1px solid black; background-color: yellow; text-align: center; width: 30px; height: 20px; margin: 2px;">X</div> | 1. | FMVSS 208 vehicle targeting requirements (See Figures 28A and 28B) |
| <div style="border: 1px solid black; background-color: yellow; text-align: center; width: 30px; height: 20px; margin: 2px;">X</div> | 1.1 | Targets A1 and A2 are on flat rectangular panels. |
| <div style="border: 1px solid black; background-color: yellow; text-align: center; width: 30px; height: 20px; margin: 2px;">X</div> | 1.2 | Three circular targets at least 90 mm in diameter and with black and yellow quadrants are mounted at the front on the outboard sides of A1 and A2. The center of each circular target is 100 mm from the one next to it. |
| <div style="border: 1px solid black; background-color: yellow; text-align: center; width: 30px; height: 20px; margin: 2px;">X</div> | | Distance between targets (mm): 100 mm |
| <div style="border: 1px solid black; background-color: yellow; text-align: center; width: 30px; height: 20px; margin: 2px;">X</div> | 1.3 | Three circular targets at least 90 mm in diameter and with black and yellow quadrants are mounted at the back on the outboard sides of on A1 and A2. The center of each circular target is 100 mm from the one next to it. |
| <div style="border: 1px solid black; background-color: yellow; text-align: center; width: 30px; height: 20px; margin: 2px;">X</div> | | Distance between targets (mm): 100 mm |
| <div style="border: 1px solid black; background-color: yellow; text-align: center; width: 30px; height: 20px; margin: 2px;">X</div> | 1.4 | The distance between the first circular target at the front of A1 and A2 and the last circular target at the back of A1 and A2 is at least 915 mm. |
| <div style="border: 1px solid black; background-color: yellow; text-align: center; width: 30px; height: 20px; margin: 2px;">X</div> | | Distance between the first and last circular targets (mm): 915 mm |
| <div style="border: 1px solid black; background-color: yellow; text-align: center; width: 30px; height: 20px; margin: 2px;">X</div> | 1.5 | Firmly fix target A1 on the vehicle roof in the vertical longitudinal plane that is coincident with the midsagittal plane of the driver dummy. |
| <div style="border: 1px solid black; background-color: yellow; text-align: center; width: 30px; height: 20px; margin: 2px;">X</div> | 1.6 | Firmly fix target A2 on the vehicle roof in the vertical longitudinal plane that is coincident with the midsagittal plane of the passenger dummy. |
| <div style="border: 1px solid black; background-color: yellow; text-align: center; width: 30px; height: 20px; margin: 2px;">X</div> | 1.7 | Two circular targets (C1 and C2) at least 90 mm in diameter and with black and yellow quadrants are mounted on the outside of the driver door. The centers of each circular target are at least 610 mm apart. |
| <div style="border: 1px solid black; background-color: yellow; text-align: center; width: 30px; height: 20px; margin: 2px;">X</div> | | Distance between targets (mm): 610 mm |
| <div style="border: 1px solid black; background-color: yellow; text-align: center; width: 30px; height: 20px; margin: 2px;">X</div> | 1.8 | Two circular targets (C1 and C2) at least 90 mm in diameter and with black and yellow quadrants are mounted on the outside of the passenger door. The centers of each circular target are at least 610 mm apart. |
| <div style="border: 1px solid black; background-color: yellow; text-align: center; width: 30px; height: 20px; margin: 2px;">X</div> | | Distance between targets (mm): 610 mm |
| <div style="border: 1px solid black; background-color: yellow; text-align: center; width: 30px; height: 20px; margin: 2px;">X</div> | 1.9 | Place tape with squares having alternating colors on the top portion of the steering wheel. |
| <div style="border: 1px solid black; background-color: yellow; text-align: center; width: 30px; height: 20px; margin: 2px;">X</div> | 1.10 | Chalk the bottom portion of the steering wheel |
| <div style="border: 1px solid black; background-color: yellow; text-align: center; width: 30px; height: 20px; margin: 2px;">X</div> | 1.11 | Is this an offset test? |
| | | <div style="border: 1px solid black; background-color: yellow; text-align: center; width: 30px; height: 20px; margin: 2px;"></div> Yes, continue with this section |
| | | <div style="border: 1px solid black; background-color: yellow; text-align: center; width: 30px; height: 20px; margin: 2px;">X</div> No, go to 2. |
| <div style="border: 1px solid black; background-color: yellow; text-align: center; width: 30px; height: 20px; margin: 2px;"></div> | 1.12 | Measure the width of the vehicle. |
| <div style="border: 1px solid black; background-color: yellow; text-align: center; width: 30px; height: 20px; margin: 2px;"></div> | | Vehicle width (mm): |
| <div style="border: 1px solid black; background-color: yellow; text-align: center; width: 30px; height: 20px; margin: 2px;"></div> | 1.13 | Find the centerline of the vehicle. (½ of the vehicle width) |

<input type="checkbox"/>	1.14	Find the line parallel to the centerline of the vehicle and 0.1 x vehicle width from the centerline of the vehicle.
<input type="checkbox"/>	1.15	Apply 25 mm wide tape with alternating black and yellow squares parallel to and on each side of the line found in 1.14. The edge of each tape shall be 50 mm from the line found in 1.14. The tape shall extend from the bottom of the bumper to the front edge of the windshield. (Figure 28D)
<input checked="" type="checkbox"/>	2.	Barrier Targeting
<input checked="" type="checkbox"/>	2.1	Fix two stationary targets D1 and D2 to the barrier as shown in the Figure 28A. One target is in the vertical longitudinal plane that is coincident with the midsagittal plane of the driver dummy. The other is in the vertical longitudinal plane that is coincident with the midsagittal plane of the passenger dummy
<input checked="" type="checkbox"/>	2.2	Targets D1 and D2 are on a rectangular panel.
<input checked="" type="checkbox"/>	2.3	Three circular targets at least 90 mm in diameter and with black and yellow quadrants are mounted on the sides of the rectangular panel away from the longitudinal centerline of the vehicle. The center of each circular target is 100 mm from the one next to it.
<input checked="" type="checkbox"/>		Distance between circular targets on D1 (mm): 100mm
<input checked="" type="checkbox"/>		Distance between circular targets on D2 (mm): 100mm
<input checked="" type="checkbox"/>	3.	FMVSS 208 Dummy Targeting Requirements
<input checked="" type="checkbox"/>	3.1	Place a circular target with black and yellow quadrants on both sides of the driver dummy head as close as possible to the center of gravity of the head in the x and z direction (relative to the measuring directions of the accelerometers).
<input checked="" type="checkbox"/>	3.2	Place a circular target with black and yellow quadrants on both sides of the passenger dummy head as close as possible to the center of gravity of the head in the x and z direction (relative to the measuring directions of the accelerometers).
<input checked="" type="checkbox"/>	3.3	Place a circular target with black and yellow quadrants on the outboard shoulder of the driver dummy. Place the target as high up on the arm as possible at the intersection of the arm and shoulder. The sleeve of the shirt on the dummy may be cut to make the target visible, but do not remove any material.
<input checked="" type="checkbox"/>	3.4	Place a circular target with black and yellow quadrants on the outboard shoulder of the passenger dummy. Place the target as high up on the arm as possible at the intersection of the arm and shoulder. The sleeve of the shirt on the dummy may be cut to make the target visible, but do not remove any material.
<input checked="" type="checkbox"/>	4.	FMVSS 204 Targeting Requirements
<input checked="" type="checkbox"/>	4.1	Is an FMVSS 204 indicant test ordered on the "COTR Vehicle Work Order?"
<input type="checkbox"/>		Yes, continue with this form.
<input checked="" type="checkbox"/>		No, this form is complete. (Removed at manufacturer's request with COTR approval)
<input type="checkbox"/>	4.2	Resection panel (Figure 28C)
<input type="checkbox"/>	4.2.1	The panel deviates no more than 6 mm from perfect flatness when suspended vertically
<input type="checkbox"/>	4.2.2	The 8 targets on the panel are circular targets at least 90 mm in diameter and with black and yellow quadrants.
<input type="checkbox"/>	4.2.3	The center of each of the 4 outer targets are placed within 1 mm of the corners of a square measuring 914 mm on each side.
<input type="checkbox"/>	4.2.4	Locate another square with 228 mm sides and with the center of this square coincident with the center of the 914 mm square.
<input type="checkbox"/>	4.2.5	The center of the 4 inner targets are placed at the midpoints of each of the 228 mm sides.
<input type="checkbox"/>	4.3	Place a circular target at least 90 mm in diameter and with black and yellow quadrants on a material (cardboard, metal, etc.) that can be taped to the top of the steering column.



- 4.4 Tape the target from 4.3 to the top of the steering column in a manner that does not interfere with the movement of the steering column in a crash


REMARKS:

I certify that I have read and performed each instruction.


Signature: Clark Subit

Date: 7/23/04


REFERENCE PHOTO TARGETS




RESECTION PANEL TARGETING ALIGNMENT



TEST RUN STEERING COLUMN CAMERA VIEW OF TYPICAL TIME ZERO VEHICLE POSITION



PRE-RUN STEERING COLUMN HIGH SPEED CAMERA VIEW



LEFT SIDE VIEW

DATA SHEET 33
CAMERA LOCATIONS

Test Vehicle: 2004 Mitsubishi Galant 4 Door
Test Program: FMVSS 208 Compliance


NHTSA No.: C45603
Test Date: 7/23/04
Time: 12:30 pm

CAMERA NO.	VIEW	CAMERA POSITIONS (mm) *			LENS (mm)	SPEED (fps)
		X	Y	Z		
1	Real Time Left Side View				13	24
2	Left Side View (Barrier face to front seat backs)	1010	-9030	1544	50	1000
3	Left Side View (Driver)	1490	-7940	1444	50	1000
4	Left Side View (B-post aimed toward center of steering wheel)	5210	-5420	250	50	1000
5	Left Side View (Steering Column)	1980	-7000	1570	35	1000
6	Left Side View (Steering Column)	1980	-7000	1034	35	1000
7	Right Side View (Overall)	2020	8070	1515	24	1000
8	Right Side View (Passenger)	1000	6870	1476	24	1000
9	Right Side View (Angle)	5200	5650	2070	50	1000
10	Right Side View (Front door)	1420	8680	1535	50	1000
11	Front View Windshield	240	0	2830	10	1000
12	Front View Driver	120	-450	1750	13	1000
13	Front View Passenger	95	470	1720	13	1000
14	Overhead Barrier Impact View	880	0	5050	16	1000
15	Pit Camera Engine View	950	0	-3150	18	1000
16	Pit Camera Fuel Tank View	2470	0	-3150	13	1000

***COORDINATES**

+X – forward of impact plane
+Y – right of monorail centerline
+Z – above ground level

CAMERA POSITIONS FOR FMVSS 208



DATA SHEET 34

APPENDIX G DUMMY POSITIONING PROCEDURES FOR 5th% DRIVER TEST DUMMY CONFORMING TO SUBPART O OF PART 572

Test Vehicle: 2004 Mitsubishi Galant 4 Door
Test Program: FMVSS 208 Compliance
Test Technician: Eric Peschman

NHTSA No.: C45603
Test Date: 7/23/04

IMPACT ANGLE:	Zero Degrees		
BELTED DUMMIES (YES/NO):	No – Front Occupants		
TEST SPEED:	<input checked="" type="checkbox"/> 32 to 40 kmph	<input type="checkbox"/> 0 to 48 kmph	<input type="checkbox"/> 0 to 56 kmph
DRIVER DUMMY:	<input checked="" type="checkbox"/> 5 TH female	<input type="checkbox"/> 50 th Male	
PASSENGER DUMMY:	<input checked="" type="checkbox"/> 5 TH female	<input type="checkbox"/> 50th Male	

- X 1. Position the seat's adjustable lumbar supports so that the lumbar supports are in the lowest, retracted or deflated adjustment position. (S16.2.10.1)
 N/A – No lumbar adjustment
- X 2. Position any adjustable parts of the seat that provide additional support so that they are in the lowest or most open adjustment position. (S16.2.10.2)
 X N/A – No additional support adjustment
- X 3. If the seat cushion adjusts fore and aft, independent of the seat back, set this adjustment to the full rearward position. (S16.2.10.3.1)
 X N/A – No independent fore-aft seat cushion adjustment
- X 4. Use the seat markings determined during the completion of Data Sheet 14 to set the rearmost fore-aft position, mid-height position and the seat cushion mid-angle. (S16.3.2.1.1)
- X 5. If the vehicle has an adjustable accelerator pedal, place it in the full forward position. (S16.3.2.2.1)
 X N/A accelerator pedal not adjustable
- X 6. Set the steering wheel hub at the geometric center of the full range of driving positions including any telescoping positions as determined in data sheet 14. (S16.2.9)
- X 7. Fully recline the seat back. (S16.3.2.1.2)
 N/A seat back not adjustable.
- X 8. Place the dummy in the seat with the legs at an angle of 120 degrees to the thighs. The calves should not be touching the seat cushion. (S16.3.2.1.2)
- X 9. Position the dummy in the seat such that the midsagittal plane is coincident with the longitudinal seat cushion markings as determined in item 1.18 of Data Sheet 14 (S16.3.2.1.3 and S16.3.2.1.4)
- X 10. Hold down the dummy's thighs and push rearward on the upper torso to maximize the pelvic angle. (S16.3.2.1.5)
- X 11. Set the angle between the legs and the thighs to 120 degrees. (S16.3.2.1.6)

- ☒ 12. Set the transverse distance between the centers of the front of the knees at 160 to 170 mm. (6.3 to 6.7 inches) Center the knee separation with respect to the longitudinal seat cushion marking as determined in item 1.18 of Data Sheet 14. (S16.3.2.1.6)
Record Knee Separation 165 mm
- ☒ 13. Push rearward on the dummy's knees until the pelvis contacts the seat back, or the backs of the calves contact the seat cushion, whichever occurs first. (S16.3.2.1.6)
☐ Pelvis contacted seat back.
☒ Calves contacted seat cushion.
- ☒ 14. Gently rock the upper torso ± 5 degrees (approximately 51 mm (2 inches)) side to side three time. (S16.3.2.1.7)
- ☒ 15. If needed, extend the legs until the feet do not contact the floor pan. The thighs should be resting on the seat cushion. (S16.3.2.1.8)
- ☒ 16. Position the right foot until the foot is in line with a longitudinal vertical plane passing through the center of the accelerator pedal. Maintain the leg and thigh in a vertical plane. (S16.3.2.1.8)
- ☒ 17. Rotate the left leg and thigh laterally to equalize the distance between each knee and the longitudinal seat cushion marking as determined in item 1.18 of Data Sheet 14. (S16.3.2.1.8)
- ☒ 18. Attempt to return the seat to the foremost fore-aft position, mid-height, and seat cushion mid-angle. The foot may contact and depress the accelerator and/or change the angle of the foot with respect to the leg. (S16.3.2.1.8)
☒ Foremost position achieved. Proceed to step 23.
☐ Foremost not achieved because of foot interference. Proceed to step 20.
☐ Foremost not achieved because of steering wheel contact.
- ☐ 19. If the dummy's legs contact the steering wheel, move the steering wheel up the minimum amount required to avoid contact. If the steering wheel is not adjustable separate the knees the minimum required to avoid contact. (S16.3.2.1.8)
☐ N/A- there was no leg contact
☐ Steering wheel repositioned
☐ Knees separated
- ☐ 20. If the left foot interferes with the clutch or brake pedals, rotate the left foot about the leg to provide clearance. If this is not sufficient, rotate the thigh outboard at the hip the minimum amount required for clearance. (S16.3.2.1.8)
☐ N/A, No foot interference with pedals.
☐ Foot adjusted to provide clearance.
☐ Foot and Thigh adjusted to provide clearance.
- ☐ 21. Continue to move the seat. Use seat controls to line up the seat markings determined during the completion of Data Sheet 14 to set the foremost fore-aft position, mid-height position and the seat cushion mid-angle. If the dummy contacts the interior move the seat rearward until a maximum clearance of 5 mm (0.2 inches) is achieved or the seat is in the closest detent position that does not cause dummy contact. (S16.3.2.1.8)

- ☐ Foremost, mid-height position and the seat cushion mid-angle reached
- ☐ Dummy contact. Clearance set at maximum of 5mm
Measured Clearance _____
- ☐ Dummy Contact. Seat set at nearest detent position.
Seat position ☐ detent positions rearward of foremost
(Foremost is position zero)
- ☐ 22. If the steering wheel was repositioned in step 19, return the steering wheel to the original position. If the steering wheel contacts the dummy before reaching the original position, position the wheel until a maximum clearance of 5mm (.2 inches) is achieved, or the steering wheel is in the closest detent position that does not cause dummy contact.
(S16.3.2.1.8)
☐ N/A Steering wheel was not repositioned.
- ☐ Original position achieved.
- ☐ Dummy contact. Clearance set at maximum of 5mm
Measured Clearance _____
- ☐ Dummy Contact. Steering wheel set at nearest detent position.
Steering wheel position ☐ detent positions upward of original position.
(Original position is position zero)
- ☒ 23. If the seat back is adjustable, rotate the seat back forward while holding the thighs in place. Continue rotating the seat back forward until the transverse instrument platform of the dummy head is level ± 0.5 degrees. If the head cannot be leveled using the seat back adjustment, or the seat back is not adjustable, use the lower neck bracket adjustment to level the head. If a level position cannot be achieved, minimize the angle.
(S16.3.2.1.9)
- ☒ Head Level Achieved. (Check all that apply)
☒ Head leveled using the adjustable seat back
☐ Head leveled using the neck bracket.
Head Angle 0.0 degrees
- ☐ Head Level NOT Achieved. (Check all that apply)
☐ Head adjusted using the adjustable seat back
☐ Head adjusted using the neck bracket.
Head Angle _____ degrees
- ☒ 24. Verify the pelvis is not interfering with the seat bight. (S16.3.2.1.9)
☒ No interference
☐ Pelvis moved forward the minimum amount so that it is not caught in the seat bight.
- ☒ 25. Verify the dummy abdomen is properly installed. (S16.3.2.1.9)
☒ Abdomen still seated properly into dummy
☐ Abdomen was adjusted because it was not seated properly into dummy

☒ 26. Head Angle
☒ N/A, neither the pelvis nor the abdomen were adjusted.

☒ 26.1 Head still level (Go to 27)

☐ 26.2 Head level adjusted

☐ Head Level Achieved. (Check all that apply)
☐ Head leveled using the adjustable seat back
☐ Head leveled using the neck bracket.
Head Angle _____ degrees

☐ Head Level NOT Achieved. (Check all that apply)
☐ Head level adjusted using the adjustable seat back
☐ Head level adjusted using the neck bracket.
Head Angle _____ degrees

☒ 27. If the dummy torso contacts the steering wheel while performing step 23, reposition the steering wheel in the following order to eliminate contact.

☒ N/A, No dummy torso contact with the steering wheel.

☒ 27.1 Adjust telescoping mechanism.

☒ N/A No telescoping adjustment.
☐ Adjustment performed (fill in appropriate change)
Steering wheel moved _____ detent positions in the forward direction.
Steering wheel moved _____ mm in the forward direction.

☒ 27.2 Adjust tilt mechanism.

☐ N/A No tilt adjustment.
☒ No adjustment performed.
☐ Adjustment performed.
Steering wheel moved _____ detent positions Upward/Downward.
(circle one)
Steering wheel moved _____ degrees Upward/Downward

☒ 27.3 Adjust Seat in the aft direction.

☒ No Adjustment performed.
☐ Seat moved aft _____ mm from original position.
☐ Seat moved aft _____ detent positions from the original position.

☒ 28. Measure and set the pelvic angle using the pelvic angle gage TE-2504. The pelvic angle should be 20.0 degrees \pm 2.5 degrees. If the pelvic angle cannot be set to the specified range because the head will not be level, adjust the pelvis as closely as possible to the angle range, but keep the head level.

☐ Pelvic angle set to 20.0 degrees \pm 2.5 degrees.
☒ Pelvic angle of 20.0 degrees not achieved, the angular difference was minimized.
☒ Record the pelvic angle: 26.7 degrees

- ☒ 29. Check the dummy for contact with the interior after completing adjustments.
 ☒ No contact.
 ___ Dummy in contact with interior.
 ___ Seat moved aft ___ mm from the previous position.
 ___ Seat moved aft ___ detent positions from the previous position.
- ☒ 30. Check the dummy to see if additional interior clearance is obtained, allowing the seat to be moved forward.
 ☒ N/A, Seat already at foremost position.
 ___ Clearance unchanged. No adjustments required.
 ___ Additional clearance available
 ___ Seat moved Forward ___ mm from the previous position.
 ___ Seat moved Forward ___ detent positions from the previous position.
- ☒ 31. Driver's foot positioning, right foot. Place the foot perpendicular to the leg and determine if the heel contacts the floor pan at any leg position. If the heel contacts the floor pan proceed to step 32 otherwise, proceed to step 33.
- ☒ 32. Perform the following steps until either all steps are completed, or the foot contacts the accelerator pedal. Step 32.6 shall be completed in all cases.
- ☒ 32.1 With the rear of the heel contacting the floor pan, move the foot forward until pedal contact occurs or the foot is at the full forward position.
- ___ 32.2 If the vehicle has an adjustable accelerator pedal, move the pedals rearward until pedal contact occurs or the pedals reach the full rearward position.
- ___ 32.3 Extend the leg, allowing the heel to lose contact with the floor until the foot contacts the pedal. Do not raise the toe of the foot higher than the top of the accelerator pedal. If the foot does not contact the pedal, proceed to the next step. If pedal contact does occur, place a tapered foam block as shown in Figure G1 under the heel with the shallow part of the taper facing forward.
- ___ 32.4 Angle the foot to achieve contact between the foot and the pedal. If the foot does not contact the pedal, return the foot to the perpendicular orientation. If pedal contact does occur, place a tapered foam block as shown in Figure G1 under the heel with the shallow part of the taper facing forward.
- ___ 32.5 Align the centerline of the foot with the vertical-longitudinal plane passing through the center of the accelerator pedal. Place a tapered foam block as shown in Figure G1 under the heel with the shallow part of the taper facing forward.
- ☒ 32.6 Record foot position
 ☒ Pedal Contact achieved. Contact occurred at step 32.1 .
 ☒ Heel contacts floor pan
 ___ Heel set _____ mm from floor pan.
 ___ Pedal Contact not achieved. Heel set _____ mm from the floor pan.




FIGURE G1

- ___33. Perform the following steps until either all steps are completed, or the foot contacts the accelerator pedal. Step 33.5 shall be completed in all cases.
 - ___33.1 Extend the leg until the foot contacts the pedal. Do not raise the toe of the foot higher than the top of the accelerator pedal. If the foot does not contact the pedal, proceed to the next step. If pedal contact does occur, place a tapered foam block as shown in Figure G1 under the heel with the shallow part of the taper facing forward.
 - ___33.2 If the vehicle has an adjustable accelerator pedal, move the pedals rearward until pedal contact occurs or the pedals reach the full rearward position. If pedal contact does occur, place a tapered foam block as shown in Figure G1 under the heel with the shallow part of the taper facing forward.
 - ___33.3 Angle the foot to achieve contact between the foot and the pedal. If the foot does not contact the pedal, return the foot to the perpendicular orientation. If pedal contact does occur, place a tapered foam block as shown in Figure G1 under the heel with the shallow part of the taper facing forward.
 - ___33.4 Align the centerline of the foot in the same horizontal plane as the centerline of the accelerator pedal. Place a tapered foam block as shown in Figure G1 under the heel with the shallow part of the taper facing forward.

33.5 Record foot position

 Pedal Contact achieved. Contact occurred at step
 Heel set mm from floor pan.

 Pedal Contact not achieved. Heel set mm from the floor pan.

 34. Driver's foot positioning, left foot.

X 34.1 Place the foot perpendicular to the leg and determine if the heel contacts the floor pan at any leg position. If the heel contacts the floor pan proceed to step 34.2, otherwise position the leg as perpendicular to the thigh as possible with the foot parallel to the floor pan.

X 34.2 Place the foot on the toe board with the heel resting on the floor pan as close to the intersection of the floor pan and the toe board as possible. Adjust the angle of the foot if necessary to contact the toe board. If the foot will not contact the toe board, set the foot perpendicular to the leg, and set the heel on the floor pan as far forward as possible. Do not place the foot on the wheel well projection or footrest. If the pedals interfere with the placement of the foot, reposition the foot by rotating the foot about the leg, or rotate the leg outboard about the hip if necessary.

 Foot rotated about the leg

 Foot rotated about the leg, and the leg rotated about the hip.

X No pedal interference

X 34.3 Record foot position.

 Heel does not contact floor pan.

 Foot placed on toe board.

X Foot placed on floor pan.

X 35. Driver arm/hand positioning.

X 35.1 Place the dummy's upper arms adjacent to the torso with the arm centerlines as close to a vertical longitudinal plane as possible. (S16.3.2.3.1)

X 35.2 Place the palms of the dummy in contact with the outer part of the steering wheel rim at its horizontal centerline with the thumbs over the steering wheel rim. (S16.3.2.3.2)

X 35.3 If it is not possible to position the thumbs inside the steering wheel rim at its horizontal centerline, then position them above and as close to the horizontal centerline of the steering wheel rim as possible. (S16.3.2.3.3)

X 35.4 Lightly tape the hands to the steering wheel rim so that if the hand of the test dummy is pushed upward by a force of not less than 9 N (2 lb) and not more than 22 N (5 lb), the tape releases the hand from the steering wheel rim. S16.3.2.3.4

X 36. Adjustable head restraints

 N/A, there is no head restraint adjustment

X 36.1 If the head restraint has an automatic adjustment, leave it where the system positions the restraint after the dummy is placed in the seat. (S16.3.4.1) Go to 37.

☒ 36.2 Adjust each head restraint vertically so that the horizontal plane determined in item 3 of Data Sheet 14 is aligned with the center of gravity (CG) of the dummy head. (S16.3.4.3)

☒ 36.3 If the above position is not attainable, move the vertical center of the head restraint to the closest detent below the center of the head CG. (S16.3.4.3)

☐ N/A midpoint position attained in previous step

☒ Headrest set at nearest detent above the head CG

☐ 36.4 If the head restraint has a fore and aft adjustment, place the restraint in the foremost position or until contact with the head is made, whichever occurs first. (S16.3.4.4)

☐ 37. Driver and passenger manual belt adjustment (for tests conducted with a belted dummy). (S16.3.5) **Unbelted Test**

☐ 37.1 If an adjustable seat belt D-ring anchorage exists, place it in the manufacturer's design position for a 5th percentile adult female.

This information will be supplied by the COTR.

Manufacturer's specified position _____

Actual Position _____

☐ 37.2 Place the Type 2 manual belt around the test dummy and fasten the latch. (S16.3.5.2)

☐ 37.3 Ensure that the dummy's head remains as level as possible. (S16.3.5.3)

☐ 37.4 Remove all slack from the lap belt. Pull the upper torso webbing out of the retractor and allow it to retract; repeat this operation four times. Apply a 9 N (2 lbf) to 18 N (4 lbf) tension load to the lap belt. If the belt system is equipped with a tension-relieving device, introduce the maximum amount of slack into the upper torso belt that is recommended by the manufacturer. If the belt system is not equipped with a tension-relieving device, allow the excess webbing in the shoulder belt to be retracted by the retractive force of the retractor. (S16.3.5.4)

REMARKS: NONE

I certify that I have read and performed each instruction.

Signature: 

Date: 7/23/04

APPENDIX G
DUMMY POSITIONING PROCEDURES
FOR 5th% PASSENGER TEST DUMMY CONFORMING TO SUBPART O OF PART 572

Test Vehicle: 2004 Mitsubishi Galant 4 Door
 Test Program: FMVSS 208 Compliance
 Test Technician: Wayne Dahlke

NHTSA No.: C45603
 Test Date: 7/23/04

IMPACT ANGLE:	Zero Degrees		
BELTED DUMMIES (YES/NO):	No – Front Occupants		
TEST SPEED:	<input checked="" type="checkbox"/> 32 to 40 kmph	<input type="checkbox"/> 0 to 48 kmph	<input type="checkbox"/> 0 to 56 kmph
DRIVER DUMMY:	<input checked="" type="checkbox"/> 5 TH female	<input type="checkbox"/> 50 th Male	
PASSENGER DUMMY:	<input checked="" type="checkbox"/> 5 TH female	<input type="checkbox"/> 50 th Male	

(Check this item ONLY if it applies to this vehicle.)

 The passenger seat adjustments are controlled by the adjustments made to the driver's seat. Therefore, positioning of the passenger dummy is made simultaneously with the driver dummy. Adjustments made to the seat to position the driver will over ride any adjustments that would normally be made to position the passenger. (S16.2.10.3)

- X 1. Position the seat's adjustable lumbar supports so that the lumbar supports are in the lowest, retracted or deflated adjustment position. (S16.2.10.1)
X N/A – No lumbar adjustment
- X 2. Position any adjustable parts of the seat that provide additional support so that they are in the lowest or most open adjustment position. (S16.2.10.2)
X N/A – No additional support adjustment
- X 3. If the seat cushion adjusts fore and aft, independent of the seat back, set this adjustment to the full rearward position. (S16.2.10.3.1)
X N/A – No independent fore-aft seat cushion adjustment
- X 4. Use the seat markings determined during the completion of Data Sheet 14 to set the rearmost fore-aft position, mid-height position and the seat cushion mid-angle. (S16.3.3.1.1)
- X 5. Fully recline the seat back. (S16.3.3.1.2)
 N/A seat back not adjustable.
- X 6. Place the dummy in the seat with the legs at an angle of 120 degrees to the thighs. The calves should not be touching the seat cushion. (S16.3.3.1.2)
- X 7. Position the dummy in the seat such that the midsagittal plane is coincident with the longitudinal seat cushion marking that was determined in item 2.19 of Data Sheet 14 (S16.3.3.1.3 and S16.3.3.1.4)
- X 8. Hold down the dummy's thighs and push rearward on the upper torso to maximize the pelvic angle. (S16.3.3.1.5)
- X 9. Set the angle between the legs and the thighs to 120 degrees. (S16.3.3.1.6)

- X 10. Set the transverse distance between the centers of the front of the knees at 160 to 170 mm. (6.3 to 6.7 inches) Center the knee separation with respect to the longitudinal seat cushion marking that was determined in item 2.19 of Data Sheet 14. (S16.3.3.1.6)
Record Knee Separation 170 mm
- X 11. Push rearward on the dummy's knees until the pelvis contacts the seat back, or the backs of the calves contact the seat cushion, whichever occurs first. (S16.3.3.1.6)
___ Pelvis contacted seat back.
X Calves contacted seat cushion.
- X 12. Gently rock the upper torso ± 5 degrees (approximately 51 mm (2 inches)) side-to-side three times. (S16.3.3.1.7)
- X 13. If needed, extend the legs until the feet do not contact the floor pan. The thighs should be resting on the seat cushion. (S16.3.3.1.8)
- X 14. Use seat controls to line up the seat markings determined during the completion of Data Sheet 14 to set the foremost fore-aft position, mid-height position and the seat cushion mid-angle. If the dummy contacts the interior move the seat rearward until a maximum clearance of 5 mm (0.2 inches) is achieved or the seat is in the closest detent position that does not cause dummy contact. (S16.3.3.1.8)
X Foremost, mid-height position and the seat cushion mid-angle reached

___ Dummy contact. Clearance set at maximum of 5mm
Measured Clearance _____

___ Dummy Contact. Seat set at nearest detent position.
Seat position ___ detent positions rearward of foremost
(Foremost is position zero)
- X 15. If the seat back is adjustable, rotate the seat back forward while holding the thighs in place. Continue rotating the seat back forward until the transverse instrument platform of the dummy head is level ± 0.5 degrees. If head cannot be leveled using the seat back adjustment, or the seat back is not adjustable, use the lower neck bracket adjustment to level the head. If a level position cannot be achieved, adjust the head as closely as possible to the ± 0.5 degree range. (S16.3.3.1.9 and S16.3.3.1.10)
(Check All That Apply)
___ Seat back not adjustable

___ Seat back not independent of driver side seat back

X Head Level Achieved. (Check all that apply)
___ X Head leveled using the adjustable seat back
___ Head leveled using the neck bracket.
Head Angle 0.1 degrees

___ Head Level NOT Achieved. (Check all that apply)
___ Head adjusted using the adjustable seat back
___ Head adjusted using the neck bracket.
Head Angle _____ degrees

- ☒ 16. Verify the pelvis is not interfering with the seat bight. (S16.3.3.1.9)
☒ No interference
☐ Pelvis moved forward the minimum amount so that it is not caught in the seat bight.
- ☒ 17. Verify the dummy abdomen is properly installed. (S16.3.3.1.9)
☒ Abdomen still seated properly into dummy
☐ Abdomen was adjusted because it was not seated properly into dummy
- ☒ 18. Head Angle
☒ N/A, neither the pelvis nor the abdomen were adjusted.
- ☒ 18.1 Head still level (Go to 19)
- ☐ 18.2 Head level adjusted
- ☐ Head Level Achieved. (Check all that apply)
☐ Head leveled using the adjustable seat back
☐ Head leveled using the neck bracket.
Head Angle _____ degrees
- ☐ Head Level NOT Achieved. (Check all that apply)
☐ Head adjusted using the adjustable seat back
☐ Head adjusted using the neck bracket.
Head Angle _____ degrees
- ☒ 19. Measure and set the pelvic angle using the pelvic angle gage TE-2504. The pelvic angle should be 20.0 degrees \pm 2.5 degrees. If the pelvic angle cannot be set to the specified range because the head will not be level, adjust the pelvis as closely as possible to the angle range, but keep the head level.
☐ Pelvic angle set to 20.0 degrees \pm 2.5 degrees.
☒ Pelvic angle of 20.0 degrees not achieved, the angular difference was minimized.
☒ Record the pelvic angle. 25.2 degrees
- ☒ 20. Check the dummy for contact with the interior after completing adjustments.
☒ No contact.
☐ Dummy in contact with interior.
☐ Seat moved aft _____ mm from the previous position.
☐ Seat moved aft _____ detent positions from the previous position.
- ☒ 21. Verify the transverse instrument platform of the dummy head is level \pm 0.5 degrees. Use the lower neck bracket adjustment to level the head. If a level position cannot be achieved, minimize the angle. (S16.3.3.1.9, S16.3.3.1.10, and S16.3.3.1.11)
☒ Head Level Achieved
Head Angle 0.1 degrees
☐ Head Level NOT Achieved.
Head Angle _____ degrees

☒ 22. Check the dummy to see if additional interior clearance is obtained, allowing the seat to be moved forward. (S16.3.3.1.12)

☐ N/A Bench Seat

☒ N/A Seat already at full forward position.

☐ Clearance unchanged. No adjustments required.

☐ Additional clearance available

☐ Seat moved Forward mm from the previous position.

☐ Seat moved Forward detent positions from the previous position.

☐ Seat moved Forward, Full Forward position reached.

☒ 23. Passenger foot positioning. (Indicate final position achieved) (S16.3.3.2)

☐ 23.1 Place feet flat on the toe board; OR

☒ 23.2 If the feet cannot be placed flat on the toe board, set the feet perpendicular to the lower leg, and rest the heel as far forward on the floor pan as possible; OR

☐ 23.3 If the heels do not touch the floor pan, set the legs to vertical and set the feet parallel to the floor pan.

☒ 24. Passenger arm/hand positioning. (S16.3.3.3)

☒ 24.1 Place the dummy's upper arms adjacent to the torso with the arm centerlines as close to a vertical longitudinal plane as possible. (S16.3.2.3.1)

☒ 24.2 Place the palms of the dummy in contact with the outer part of the thighs (S16.3.3.3.2)

☒ 24.3 Place the little fingers in contact with the seat cushion. (S16.3.3.3.3)

☒ 25. Adjustable head restraints

☐ N/A, there is no head restraint adjustment

☐ 25.1 If the head restraint has an automatic adjustment, leave it where the system positions the restraint after the dummy is placed in the seat. (S16.3.4.1) Go to 26.

☒ 25.2 Adjust each head restraint vertically so that the horizontal plane determined in item 3 of Data Sheet 14 is aligned with the center of gravity (CG) of the dummy head. (S16.3.4.3)

☒ 25.3 If the above position is not attainable, move the vertical center of the head restraint to the closest detent below the center of the head CG. (S16.3.4.3)

☐ N/A midpoint position attained in previous step

☒ Headrest set at nearest detent below the head CG

☒ 25.4 If the head restraint has a fore and aft adjustment, place the restraint in the foremost position or until contact with the head is made, whichever occurs first. (S16.3.4.4)

☐ 26. Manual belt adjustment (for tests conducted with a belted dummy) S16.3.5

☒ N/A, **Unbelted test**

__26.1 If an adjustable seat belt D-ring anchorage exists, place it in the manufacturer's design position for a 5th percentile adult female.

This information will be supplied by the COTR.

Manufacturer's specified position _____

Actual Position _____

__26.2 Place the Type 2 manual belt around the test dummy and fasten the latch. (S16.3.5.2)

__26.3 Ensure that the dummy's head remains as level as possible. (S16.3.5.3)

__26.4 Remove all slack from the lap belt. Pull the upper torso webbing out of the retractor and allow it to retract; repeat this operation four times. Apply a 9 N (2 lbf) to 18 N (4 lbf) tension load to the lap belt. If the belt system is equipped with a tension-relieving device, introduce the maximum amount of slack into the upper torso belt that is recommended by the manufacturer. If the belt system is not equipped with a tension-relieving device, allow the excess webbing in the shoulder belt to be retracted by the retractive force of the retractor. (S16.3.5.4)

REMARKS: NONE

I certify that I have read and performed each instruction.

Signature: Wayne J. Ahl

Date: 7/23/04


DATA SHEET 35

DUMMY MEASUREMENTS


Test Vehicle: 2004 Mitsubishi Galant 4 Door
 Test Program: FMVSS 208 Compliance
 Test Technician: Eric Peschman

NHTSA No.: C45603
 Test Date: 7/23/04


DUMMY MEASUREMENTS FOR FRONT SEAT OCCUPANTS



AD	Arm to Door
HD	H-Point to Door
HR	Head to Side Header
HS	Head to Side Window
KK	Knee to Knee
SHY	Striker to H-Point (Y Axis)



CD	Chest to Dash
CS	Chest to Steering Wheel Hub
HH	Head to Header
HW	Head to Windshield
HZ	Head to Roof
KDA	Knee to Dash Angle
KDL	Left Knee to Dash
KDR	Right Knee to Dash
NA	Nose to Rim Angle
NR	Nose to Rim
PA	Pelvic Angle
RA	Rim to Abdomen
SA	Seat Back Angle
SCA	Steering Column Angle
SH	Striker to H-Point
SK	Striker to Knee
ST	Striker to Head
SWA	Steering Wheel Angle
TA	Tibial Angle
WA	Windshield Angle



DATA SHEET 35
DUMMY MEASUREMENTS


Test Vehicle: 2004 Mitsubishi Galant 4 Door
Test Program: FMVSS 208 Compliance
Test Technician: Eric Peschman

NHTSA No.: C45603
Test Date: 7/23/04

TEST DUMMY POSITION MEASUREMENTS

Code	Measurement Description	Driver SN 505		Passenger SN 511	
		Length (mm)	Angle (°)	Length (mm)	Angle (°)
WA	Windshield Angle		26.5		
SWA	Steering Wheel Angle		21.1		
SCA	Steering Column Angle		21.4		
SA	Seat Back Angle (On headrest post)		5.2		4.1
HZ	Head to Roof (Z)	168	90	174	90
HH	Head to Header	301	41.9	295	45.3
HW	Head to Windshield	672	0	682	0
HR	Head to Side Header (Y)	261		257	
NR	Nose to Rim	272	6.5		
CD	Chest to Dash	461		426	
CS	Chest to Steering Hub	219	9.5		
RA	Rim to Abdomen	112	0		
KDL	Left Knee to Dash	113	23.3	86	
KDR	Right Knee to Dash	107		94	28.9
PA	Pelvic Angle		26.7		25.2
TA	Tibia Angle		47.9		41.3
KK	Knee to Knee (Y)	283		215	
SK	Striker to Knee	689	95.7	715	93.9
ST	Striker to Head	482	27.9	487	33.3
SH	Striker to H-Point	385	113.3	419	114.0
SHY	Striker to H-Point (Y)	282		265	
HS	Head to Side Window	361		358	
HD	H-Point to Door (Y)	175		168	
AD	Arm to Door (Y)	166		155	
AA	Ankle to Ankle	283		191	

SEAT BELT POSITIONING DATA



FRONT VIEW OF DUMMY

SEAT BELT POSITIONING MEASUREMENTS

Measurement Description	Units	Driver	Passenger	Rear Passenger
PBU - Top surface of reference to belt upper edge	mm	N/A	N/A	N/A
PBL - To surface of reference to belt lower edge	mm	N/A	N/A	N/A

DATA SHEET 36

CRASH TEST

Test Vehicle: 2004 Mitsubishi Galant 4 Door
 Test Program: FMVSS 208 Compliance
 Test Technician: Eric Peschman

NHTSA No.: C45603
 Test Date: 7/23/04

IMPACT ANGLE:	Zero Degrees		
BELTED DUMMIES (YES/NO):	No – Front Occupants		
TEST SPEED:	<u>X</u> 32 to 40 kmph	<u> </u> 0 to 48 kmph	<u> </u> 0 to 56 kmph
DRIVER DUMMY:	<u>X</u> 5 TH female	<u> </u> 50 th Male	
PASSENGER DUMMY:	<u>X</u> 5 TH female	<u> </u> 50th Male	

- ☒ 1. Vehicle underbody painted
- ☒ 2. The speed measuring devices are in place and functioning.
- ☒ 3. The speed measuring devices are 1.0 m from the barrier (spec. 1.5m) and 30 cm from the barrier (spec. is 30 cm)
- ☒ 4. Convertible top is in the closed position.
- ☒ N/A, not a convertible
- ☒ 5. Instrumentation and wires are placed so the motion of the dummies during impact is not affected.
- ☒ 6. Tires inflated to pressure on tire placard or if it does not have a tire placard because it is not a passenger car, then inflated to the tire pressure specified in the owner information.

<u>220</u> kpa front left tire	<u>220</u> kpa specified on tire placard or in owner information
<u>220</u> kpa front right tire	<u>220</u> kpa specified on tire placard or in owner information
<u>220</u> kpa rear left tire	<u>220</u> kpa specified on tire placard or in owner information
<u>220</u> kpa rear right tire	<u>220</u> kpa specified on tire placard or in owner information

- ☒ 7. Time zero contacts on barrier in place.
- ☒ 8. Pre test zero and shunt calibration adjustments performed and recorded
- ☒ 9. Dummy temperature meets requirements of section 12.2 of the test procedure.
- ☒ 10. Vehicle hood closed and latched
- ☒ 11. Transmission placed in neutral
- ☒ 12. Parking brake off
- ☒ 13. Ignition in the ON position
- ☒ 14. Doors closed and latched but not locked
- ☒ 15. Posttest zero and shunt calibration checks performed and recorded
- ☒ 16. Actual test speed 39.8 kmph
- ☒ 17. Vehicle rebound from the barrier 449 cm
- ☒ 18. Describe whether the doors open after the test and what method is used to open the doors.
 - ☒ Left Front Door: Door remained closed and latched; Door opened without tools
 - ☒ Right Front Door: Door remained closed and latched; Door opened without tools
 - ☒ Left Rear Door: Door remained closed and latched; Door opened without tools
 - ☒ Right Rear Door: Door remained closed and latched; Door opened without tools

- ☒ 19. Describe the contact points of the dummy with the interior of the vehicle.
- ☒ Driver Dummy: Head to Air Bag, Headrest, and Visor; Chest and Abdomen to Air Bag and Rim; Knees to Knee Bolster
- ☒ Passenger Dummy: Head to Air Bag and A-Post; Chest and Abdomen to Air Bag; Knees to Glove Box

REMARKS: NONE

I certify that I have read and performed each instruction.

Signature: 

Date: 7/23/04

DATA SHEET NO. 38

ACCIDENT INVESTIGATION DIVISION DATA

Test Vehicle: 2004 Mitsubishi Galant 4 Door
 Test Program: FMVSS 208 Compliance
 Test Technician: Eric Peschman

NHTSA No.: C45603
 Test Date: 7/23/04

IMPACT ANGLE:	Zero Degrees		
BELTED DUMMIES (YES/NO):	No – Front Occupants		
TEST SPEED:	<input checked="" type="checkbox"/> 32 to 40 kmph	<input type="checkbox"/> 0 to 48 kmph	<input type="checkbox"/> 0 to 56 kmph
DRIVER DUMMY:	<input checked="" type="checkbox"/> 5 TH female	<input type="checkbox"/> 50 th Male	
PASSENGER DUMMY:	<input checked="" type="checkbox"/> 5 TH female	<input type="checkbox"/> 50th Male	

Vehicle Year/Make/Model/Body Style:	2004 Mitsubishi Galant 4 Door
VIN:	4A3AB56F64E051855
Wheelbase:	2750 mm
Build Date:	10/03
Vehicle Size Category:	3
Test Weight:	1689.7 kg
Front Overhang:	940 mm
Overall Width:	1840 mm
Overall Length Center:	4804 mm


Accelerometer Data	
Location:	As per measurements on Data Sheet 31
Linearity:	>99.9%

Integration Algorithm:	Trapezoidal
Vehicle Impact Speed:	39.8 kmph
Time of Separation:	106.3 ms
Velocity Change:	46.2 kmph

CRUSH PROFILE

Collision Deformation Classification: 12FDEW6
 Midpoint of Damage: Vehicle Longitudinal Centerline
 Damage Region Length (mm): 1516
 Impact Mode: Frontal Barrier

No.	Measurement Description	Units	Pre-Test	Post-Test	Difference
C1	Crush zone 1 at left side	mm	4605	4363	242
C2	Crush zone 2 at left side	mm	4725	4424	301
C3	Crush zone 3 at left side	mm	4779	4436	343
C4	Crush zone 4 at right side	mm	4779	4422	357
C5	Crush zone 5 at right side	mm	4724	4413	311
C6	Crush zone 6 at right side	mm	4608	4346	262



REMARKS: NONE

I certify that I have read and performed each instruction.

Signature: Clark S. Subit

Date: 7/23/04

DATA SHEET 39 **WINDSHIELD MOUNTING (FMVSS 212)**

Test Vehicle: 2004 Mitsubishi Galant 4 Door
 Test Program: FMVSS 208 Compliance
 Test Technician: Clark Subrt

NHTSA No.: C45603
 Test Date: 7/23/04

IMPACT ANGLE:	Zero Degrees		
BELTED DUMMIES (YES/NO):	No – Front Occupants		
TEST SPEED:	X 32 to 40 kmph	0 to 48 kmph	0 to 56 kmph
DRIVER DUMMY:	X 5 TH female		50 th Male
PASSENGER DUMMY:	X 5 TH female		50th Male

1. Pre-Crash
 - X**

1.1 Describe from visual inspection how the windshield is mounted and describe any trim material.

Retained with glue
Rubber and plastic trim
 - X**

1.2 Mark the longitudinal centerline of the windshield
 - X**

1.3 Measure pre-crash A, B, and C for the left side and record in the chart below.
 - X**

1.4 Measure pre-crash C, D, and E for the right side and record in the chart below.
 - X**

1.5 Measure from the edge of the retainer or molding to the edge of the windshield.
 - X**

Dimension G (mm): 8mm
 2. Post Crash
 - X**

2.1 Can a single thickness of copier type paper (as small a piece as necessary) slide between the windshield and the vehicle body?

X

No – Pass. Skip to the table of measurements, complete it by repeating the pre-crash measurements in the post crash column, and calculate the retention percentage, which will be 100%.

Yes, go to 2.2
 - 2.2 Visibly mark the beginning and end of the portions of the periphery where the paper slides between the windshield and the vehicle body.
 - 2.3 Measure and record post-crash A, B, C, D, E, and F such that the measurements do not include any of the parts of the windshield where the paper slides between the windshield and the vehicle body.
 - 2.4 Calculate and record the percent retention for the right and left side of the windshield.
 - 2.5 Is total right side percent retention less than 75%?

Yes, Fail

No, Pass
 - 2.6 Is total left side percent retention less than 75%?

Yes, Fail


No, Pass

WINDSHIELD RETENTION MEASUREMENTS

	Dimension	Pre-Crash (mm)	Post-Crash (mm)	Percent Retention (Post-Test ÷ Pre-Crash)
Left Side	A	607	607	100%
	B	820	820	100%
	C	762	762	100%
	Total	2189	2189	100%
Right Side	D	607	607	100%
	E	826	826	100%
	F	762	762	100%
	Total	2194	2194	100%

Indicate area of mounting failure. NONE

FRONT VIEW OF WINDSHIELD



REMARKS: NONE

I certify that I have read and performed each instruction.

Signature: Clark Subit

Date: 7/23/04

DATA SHEET 40 **WINDSHIELD ZONE INTRUSION (FMVSS 219)**


Test Vehicle: 2004 Mitsubishi Galant 4 Door
 Test Program: FMVSS 208 Compliance
 Test Technician: Clark Subrt

NHTSA No.: C45603
 Test Date: 7/23/04

IMPACT ANGLE:	Zero Degrees		
BELTED DUMMIES (YES/NO):	No – Front Occupants		
TEST SPEED:	<input checked="" type="checkbox"/> 32 to 40 kmph	<input type="checkbox"/> 0 to 48 kmph	<input type="checkbox"/> 0 to 56 kmph
DRIVER DUMMY:	<input checked="" type="checkbox"/> 5 TH female		<input type="checkbox"/> 50 th Male
PASSENGER DUMMY:	<input checked="" type="checkbox"/> 5 TH female		<input type="checkbox"/> 50th Male

- ☒ 1. Place a 165 mm diameter rigid sphere, with a mass of 6.8 kg on the instrument panel so that it is simultaneously touching the instrument panel and the windshield. (571.219 S6.1(a))
- ☒ 2. Roll the sphere from one side of the windshield to the other while marking on the windshield where the sphere contacts the windshield. (571.219 S6.1(b))
- ☒ 3. From the outermost contactable points on the windshield draw a horizontal line to the edges of the windshield. (571.219 S6.1(b))
- ☒ 4. Draw a line on the inner surface of the windshield that is 13 mm below the line determined in items 2 and 3
- ☒ 5. After the crash test, record any points where a part of the exterior of the vehicle has marked, penetrated, or broken the windshield.

Provide all dimensions necessary to reproduce the protected area.



WINDSHIELD DIMENSIONS

Item	Units	Value
A	mm	1214
B	mm	473
C	mm	1524
D	mm	820
E	mm	580
F	mm	558

AREA OF PROTECTED ZONE FAILURES:

- B. Provide coordinates of the area that the protected zone was penetrated more than 0.25 inches by a vehicle component other than one which is normally in contact with the windshield.

X	Y
NONE	

- C. Provide coordinates of the area beneath the protected zone template that the inner surface of the windshield was penetrated by a vehicle component.

X	Y
NONE	

REMARKS: NONE

I certify that I have read and performed each instruction.

Signature: Clark Subit

Date: 7/23/04

DATA SHEET 41
FUEL SYSTEM INTEGRITY (FMVSS 301)

Test Vehicle: 2004 Mitsubishi Galant 4 Door
Test Program: FMVSS 208 Compliance
Test Technician: Eric Peschman

NHTSA No.: C45603
Test Date: 7/23/04

TYPE OF IMPACT:	25 mph Unbelted Flat Frontal
-----------------	------------------------------

Stoddard Solvent Spillage Measurements


- A. From impact until vehicle motion ceases: 0.0 grams
(Maximum Allowable = 28 grams)
- B. For the 5 minute period after motion ceases: 0.0 grams
(Maximum Allowable = 142 grams)
- C. For the following 25 minutes: 0.0 grams
(Maximum Allowable = 28 grams/minute)
- D. Spillage: NONE

REMARKS: NO SPILLAGE

DATA SHEET NO. 41
FMVSS 301 STATIC ROLLOVER DATA

Test Vehicle: 2004 Mitsubishi Galant 4 Door
 Test Program: FMVSS 208 Compliance

NHTSA No.: C45603
 Test Date: 7/23/04



1. The specified fixture rollover rate for each 90° of rotation is 60 to 180 seconds.
2. The position hold time at each position is 300 seconds (minimum).
3. Details of Stoddard Solvent spillage locations: None

Test Phase	Rotation Time (sec.)	Hold Time (sec.)	Spillage (grams)
0° to 90°	169	300	0.0
90° to 180°	152	300	0.0
180° to 270°	134	300	0.0
270° to 360°	162	300	0.0

APPENDIX A
CRASH TEST DATA

TABLE OF DATA PLOTS

		<u>Page No.</u>
Figure No. 1.	Driver Head X Acceleration vs. Time	A-1
Figure No. 2.	Driver Head Y Acceleration vs. Time	A-1
Figure No. 3.	Driver Head Z Acceleration vs. Time	A-1
Figure No. 4.	Driver Head Resultant Acceleration vs. Time	A-1
Figure No. 5.	Driver Head X Velocity vs. Time	A-2
Figure No. 6.	Driver Head Y Velocity vs. Time	A-2
Figure No. 7.	Driver Head Z Velocity vs. Time	A-2
Figure No. 8.	Driver Neck Force X vs. Time	A-3
Figure No. 9.	Driver Neck Force Y vs. Time	A-3
Figure No. 10.	Driver Neck Force Z vs. Time	A-3
Figure No. 11.	Driver Neck Force Resultant vs. Time	A-3
Figure No. 12.	Driver Neck Moment X vs. Time	A-4
Figure No. 13.	Driver Neck Moment Y vs. Time	A-4
Figure No. 14.	Driver Neck Moment Z vs. Time	A-4
Figure No. 15.	Driver Neck Moment Resultant vs. Time	A-4
Figure No. 16.	Driver Chest X Acceleration vs. Time	A-5
Figure No. 17.	Driver Chest Y Acceleration vs. Time	A-5
Figure No. 18.	Driver Chest Z Acceleration vs. Time	A-5
Figure No. 19.	Driver Chest Resultant Acceleration vs. Time	A-5
Figure No. 20.	Driver Chest X Velocity vs. Time	A-6
Figure No. 21.	Driver Chest Y Velocity vs. Time	A-6
Figure No. 22.	Driver Chest Z Velocity vs. Time	A-6
Figure No. 23.	Driver Chest Displacement vs. Time	A-6
Figure No. 24.	Driver Left Femur Force vs. Time	A-7
Figure No. 25.	Driver Right Femur Force vs. Time	A-7
Figure No. 26.	Passenger Head X Acceleration vs. Time	A-8
Figure No. 27.	Passenger Head Y Acceleration vs. Time	A-8
Figure No. 28.	Passenger Head Z Acceleration vs. Time	A-8
Figure No. 29.	Passenger Head Resultant Acceleration vs. Time	A-8





		<u>Page No.</u>
Figure No. 30.	Passenger Head X Velocity vs. Time	A-9
Figure No. 31.	Passenger Head Y Velocity vs. Time	A-9
Figure No. 32.	Passenger Head Z Velocity vs. Time	A-9
Figure No. 33.	Passenger Neck Force X vs. Time	A-10
Figure No. 34.	Passenger Neck Force Y vs. Time	A-10
Figure No. 35.	Passenger Neck Force Z vs. Time	A-10
Figure No. 36.	Passenger Neck Force Resultant vs. Time	A-10
Figure No. 37.	Passenger Neck Moment X vs. Time	A-11
Figure No. 38.	Passenger Neck Moment Y vs. Time	A-11
Figure No. 39.	Passenger Neck Moment Z vs. Time	A-11
Figure No. 40.	Passenger Neck Moment Resultant vs. Time	A-11
Figure No. 41.	Passenger Chest X Acceleration vs. Time	A-12
Figure No. 42.	Passenger Chest Y Acceleration vs. Time	A-12
Figure No. 43.	Passenger Chest Z Acceleration vs. Time	A-12
Figure No. 44.	Passenger Chest Resultant Acceleration vs. Time	A-12
Figure No. 45.	Passenger Chest X Velocity vs. Time	A-13
Figure No. 46.	Passenger Chest Y Velocity vs. Time	A-13
Figure No. 47.	Passenger Chest Z Velocity vs. Time	A-13
Figure No. 48.	Passenger Chest Displacement vs. Time	A-13
Figure No. 49.	Passenger Left Femur Force vs. Time	A-14
Figure No. 50.	Passenger Right Femur Force vs. Time	A-14
Figure No. 51.	Driver Nij (N_{TF}) vs. Time	A-15
Figure No. 52.	Driver Nij (N_{TE}) vs. Time	A-15
Figure No. 53.	Driver Nij (N_{CF}) vs. Time	A-15
Figure No. 54.	Driver Nij (N_{CE}) vs. Time	A-15
Figure No. 55.	Passenger Nij (N_{TF}) vs. Time	A-16
Figure No. 56.	Passenger Nij (N_{TE}) vs. Time	A-16
Figure No. 57.	Passenger Nij (N_{CF}) vs. Time	A-16
Figure No. 58.	Passenger Nij (N_{CE}) vs. Time	A-16
Figure No. 59.	Driver Occipital Condyle Moment vs. Time	A-17

	<u>Page No.</u>
Figure No. 60. Passenger Occipital Condyle Moment vs. Time	A-17
Figure No. 61. Left Rear Seat Crossmember X Acceleration vs. Time	A-18
Figure No. 62. Left Rear Seat Crossmember X Velocity vs. Time	A-18
Figure No. 63. Right Rear Seat Crossmember X Acceleration vs. Time	A-18
Figure No. 64. Right Rear Seat Crossmember X Velocity vs. Time	A-18
Figure No. 65. Top of Engine X Acceleration vs. Time	A-19
Figure No. 66. Top of Engine X Velocity vs. Time	A-19
Figure No. 67. Bottom of Engine X Acceleration vs. Time	A-19
Figure No. 68. Bottom of Engine X Velocity vs. Time	A-19
Figure No. 69. Left Brake Caliper X Acceleration vs. Time	A-20
Figure No. 70. Left Brake Caliper X Velocity vs. Time	A-20
Figure No. 71. Right Brake Caliper X Acceleration vs. Time	A-20
Figure No. 72. Right Brake Caliper X Velocity vs. Time	A-20
Figure No. 73. Instrument Panel X Acceleration vs. Time	A-21
Figure No. 74. Instrument Panel X Velocity vs. Time	A-21
Figure No. 75. Trunk Z Acceleration vs. Time	A-21
Figure No. 76. Trunk Z Velocity vs. Time	A-21
Figure No. 77. Barrier Force – Upper Left vs. Time	A-22
Figure No. 78. Barrier Force – Upper Center vs. Time	A-22
Figure No. 79. Barrier Force – Upper Right vs. Time	A-22
Figure No. 80. Barrier Force – Lower Left vs. Time	A-23
Figure No. 81. Barrier Force – Lower Center vs. Time	A-23
Figure No. 82. Barrier Force – Lower Right vs. Time	A-23
Figure No. 83. Barrier Force – Sum Left vs. Time	A-24
Figure No. 84. Barrier Force – Sum Center vs. Time	A-24
Figure No. 85. Barrier Force – Sum Right vs. Time	A-24
Figure No. 86. Barrier Force – Sum All vs. Time	A-24
Figure No. 87. Barrier Force – Sum All vs. Average Seat X-member Displacement	A-25



25MPH FRONTAL UNBELTED
2004 MITSUBISHI GALANT (C45603)

Test Date: 07/23/04
Speed: 24.7 mph (39.8 km/h)







25MPH FRONTAL UNBELTED
2004 MITSUBISHI GALANT (C45603)

Test Date: 07/23/04
Speed: 24.7 mph (39.8 km/h)


DRIVER HEAD X Velocity (kph) vs TIME (ms)



DRIVER HEAD Y Velocity (kph) vs TIME (ms)



DRIVER HEAD Z Velocity (kph) vs TIME (ms)







25MPH FRONTAL UNBELTED
2004 MITSUBISHI GALANT (C45603)

Test Date: 07/23/04
Speed: 24.7 mph (39.8 km/h)


DRIVER NECK FX (N) vs TIME (ms)




DRIVER NECK FY (N) vs TIME (ms)



DRIVER NECK FZ (N) vs TIME (ms)







DRIVER NECK FResultant (N) vs TIME (ms)





25MPH FRONTAL UNBELTED
2004 MITSUBISHI GALANT (C45603)





Test Date: 07/23/04
Speed: 24.7 mph (39.8 km/h)









25MPH FRONTAL UNBELTED
2004 MITSUBISHI GALANT (C45603)

Test Date: 07/23/04
Speed: 24.7 mph (39.8 km/h)









25MPH FRONTAL UNBELTED
2004 MITSUBISHI GALANT (C45603)





Test Date: 07/23/04
Speed: 24.7 mph (39.8 km/h)





25MPH FRONTAL UNBELTED
2004 MITSUBISHI GALANT (C45603)




Test Date: 07/23/04
Speed: 24.7 mph (39.8 km/h)





25MPH FRONTAL UNBELTED
2004 MITSUBISHI GALANT (C45603)

Test Date: 07/23/04
Speed: 24.7 mph (39.8 km/h)







25MPH FRONTAL UNBELTED
2004 MITSUBISHI GALANT (C45603)

Test Date: 07/23/04
Speed: 24.7 mph (39.8 km/h)


PASSENGER NECK FX (N) vs TIME (ms)




PASSENGER NECK FY (N) vs TIME (ms)



PASSENGER NECK FZ (N) vs TIME (ms)







PASSENGER NECK FResultant (N) vs TIME (ms)





25MPH FRONTAL UNBELTED
2004 MITSUBISHI GALANT (C45603)





Test Date: 07/23/04
Speed: 24.7 mph (39.8 km/h)





25MPH FRONTAL UNBELTED
2004 MITSUBISHI GALANT (C45603)





Test Date: 07/23/04
Speed: 24.7 mph (39.8 km/h)





25MPH FRONTAL UNBELTED
2004 MITSUBISHI GALANT (C45603)



Test Date: 07/23/04
Speed: 24.7 mph (39.8 km/h)





25MPH FRONTAL UNBELTED
2004 MITSUBISHI GALANT (C45603)

Test Date: 07/23/04
Speed: 24.7 mph (39.8 km/h)







25MPH FRONTAL UNBELTED
2004 MITSUBISHI GALANT (C45603)

Test Date: 07/23/04
Speed: 24.7 mph (39.8 km/h)


Drv. nij (NTF) () vs TIME (ms)




Drv. nij (NTE) () vs TIME (ms)



Drv. nij (NCF) () vs TIME (ms)







Drv. nij (NCE) () vs TIME (ms)





25MPH FRONTAL UNBELTED
2004 MITSUBISHI GALANT (C45603)



Test Date: 07/23/04
Speed: 24.7 mph (39.8 km/h)









25MPH FRONTAL UNBELTED
2004 MITSUBISHI GALANT (C45603)

Test Date: 07/23/04
Speed: 24.7 mph (39.8 km/h)











25MPH FRONTAL UNBELTED
2004 MITSUBISHI GALANT (C45603)





Test Date: 07/23/04
Speed: 24.7 mph (39.8 km/h)





25MPH FRONTAL UNBELTED
2004 MITSUBISHI GALANT (C45603)





Test Date: 07/23/04
Speed: 24.7 mph (39.8 km/h)





25MPH FRONTAL UNBELTED
2004 MITSUBISHI GALANT (C45603)

Test Date: 07/23/04
Speed: 24.7 mph (39.8 km/h)







25MPH FRONTAL UNBELTED
2004 MITSUBISHI GALANT (C45603)

Test Date: 07/23/04
Speed: 24.7 mph (39.8 km/h)


BARRIER FORCE - UPPER LEFT (kn) vs TIME (ms)



BARRIER FORCE - UPPER CENTER (kn) vs TIME (ms)




BARRIER FORCE - UPPER RIGHT (kn) vs TIME (ms)







BARRIER FORCE - LOWER LEFT (kn) vs TIME (ms)



BARRIER FORCE - LOWER CENTER (kn) vs TIME (ms)



BARRIER FORCE - LOWER RIGHT (kn) vs TIME (ms)







25MPH FRONTAL UNBELTED
2004 MITSUBISHI GALANT (C45603)

Test Date: 07/23/04
Speed: 24.7 mph (39.8 km/h)


BARRIER FORCE - SUM LEFT (kn) vs TIME (ms)




BARRIER FORCE - SUM CENTER (kn) vs TIME (ms)



BARRIER FORCE - SUM RIGHT (kn) vs TIME (ms)




BARRIER FORCE - SUM ALL (kn) vs TIME (ms)





25MPH FRONTAL UNBELTED
2004 MITSUBISHI GALANT (C45603)

Test Date: 07/23/04
Speed: 24.7 mph (39.8 km/h)



APPENDIX B
LOW RISK TEST DATA

TABLE OF DATA PLOTS





		<u>Page No.</u>
Figure No. 1.	5 th Fem. P1 Driver Head X Acceleration vs. Time	B-1
Figure No. 2.	5 th Fem. P1 Driver Head Y Acceleration vs. Time	B-1
Figure No. 3.	5 th Fem. P1 Driver Head Z Acceleration vs. Time	B-1
Figure No. 4.	5 th Fem. P1 Driver Head Resultant Acceleration vs. Time	B-1
Figure No. 5.	5 th Fem. P1 Driver Head X Velocity vs. Time	B-2
Figure No. 6.	5 th Fem. P1 Driver Head Y Velocity vs. Time	B-2
Figure No. 7.	5 th Fem. P1 Driver Head Z Velocity vs. Time	B-2
Figure No. 8.	5 th Fem. P1 Driver Neck Force X vs. Time	B-3
Figure No. 9.	5 th Fem. P1 Driver Neck Force Y vs. Time	B-3
Figure No. 10.	5 th Fem. P1 Driver Neck Force Z vs. Time	B-3
Figure No. 11.	5 th Fem. P1 Driver Neck Force Resultant vs. Time	B-3
Figure No. 12.	5 th Fem. P1 Driver Neck Moment X vs. Time	B-4
Figure No. 13.	5 th Fem. P1 Driver Neck Moment Y vs. Time	B-4
Figure No. 14.	5 th Fem. P1 Driver Neck Moment Z vs. Time	B-4
Figure No. 15.	5 th Fem. P1 Driver Occipital Condyle Moment vs. Time	B-4
Figure No. 16.	5 th Fem. P1 Driver Chest X Acceleration vs. Time	B-5
Figure No. 17.	5 th Fem. P1 Driver Chest Y Acceleration vs. Time	B-5
Figure No. 18.	5 th Fem. P1 Driver Chest Z Acceleration vs. Time	B-5
Figure No. 19.	5 th Fem. P1 Driver Chest Resultant Acceleration vs. Time	B-5
Figure No. 20.	5 th Fem. P1 Driver Chest X Velocity vs. Time	B-6
Figure No. 21.	5 th Fem. P1 Driver Chest Y Velocity vs. Time	B-6
Figure No. 22.	5 th Fem. P1 Driver Chest Z Velocity vs. Time	B-6
Figure No. 23.	5 th Fem. P1 Driver Chest Displacement vs. Time	B-6
Figure No. 24.	5 th Fem. P1 Driver Left Femur Force vs. Time	B-7
Figure No. 25.	5 th Fem. P1 Driver Right Femur Force vs. Time	B-7
Figure No. 26.	Fire Voltage #1 Voltage vs. Time	B-8
Figure No. 27.	Fire Current #1 Voltage vs. Time	B-8
Figure No. 28.	Fire Voltage #2 Voltage vs. Time	B-8
Figure No. 29.	Fire Current #2 Voltage vs. Time	B-8




	<u>Page No.</u>
Figure No. 30.	5 th Fem. P1 Driver Nij (N_{TF}) vs. Time
Figure No. 31.	5 th Fem. P1 Driver Nij (N_{TE}) vs. Time
Figure No. 32.	5 th Fem. P1 Driver Nij (N_{CF}) vs. Time
Figure No. 33.	5 th Fem. P1 Driver Nij (N_{CE}) vs. Time
Figure No. 34.	5 th Fem. P2 Driver Head X Acceleration vs. Time
Figure No. 35.	5 th Fem. P2 Driver Head Y Acceleration vs. Time
Figure No. 36.	5 th Fem. P2 Driver Head Z Acceleration vs. Time
Figure No. 37.	5 th Fem. P2 Driver Head Resultant Acceleration vs. Time
Figure No. 38.	5 th Fem. P2 Driver Head X Velocity vs. Time
Figure No. 39.	5 th Fem. P2 Driver Head Y Velocity vs. Time
Figure No. 40.	5 th Fem. P2 Driver Head Z Velocity vs. Time
Figure No. 41.	5 th Fem. P2 Driver Neck Force X vs. Time
Figure No. 42.	5 th Fem. P2 Driver Neck Force Y vs. Time
Figure No. 43.	5 th Fem. P2 Driver Neck Force Z vs. Time
Figure No. 44.	5 th Fem. P2 Driver Neck Force Resultant vs. Time
Figure No. 45.	5 th Fem. P2 Driver Neck Moment X vs. Time
Figure No. 46.	5 th Fem. P2 Driver Neck Moment Y vs. Time
Figure No. 47.	5 th Fem. P2 Driver Neck Moment Z vs. Time
Figure No. 48.	5 th Fem. P2 Driver Occipital Condyle Moment vs. Time
Figure No. 49.	5 th Fem. P2 Driver Chest X Acceleration vs. Time
Figure No. 50.	5 th Fem. P2 Driver Chest Y Acceleration vs. Time
Figure No. 51.	5 th Fem. P2 Driver Chest Z Acceleration vs. Time
Figure No. 52.	5 th Fem. P2 Driver Chest Resultant Acceleration vs. Time
Figure No. 53.	5 th Fem. P2 Driver Chest X Velocity vs. Time
Figure No. 54.	5 th Fem. P2 Driver Chest Y Velocity vs. Time
Figure No. 55.	5 th Fem. P2 Driver Chest Z Velocity vs. Time
Figure No. 56.	5 th Fem. P2 Driver Chest Displacement vs. Time
Figure No. 57.	5 th Fem. P2 Driver Left Femur Force vs. Time
Figure No. 58.	5 th Fem. P2 Driver Right Femur Force vs. Time
Figure No. 59.	Fire Voltage #1 Voltage vs. Time

		<u>Page No.</u>
Figure No. 60.	Fire Current #1 Voltage vs. Time	B-17
Figure No. 61.	Fire Voltage #2 Voltage vs. Time	B-17
Figure No. 62.	Fire Current #2 Voltage vs. Time	B-17
Figure No. 63.	5 th Fem. P2 Driver Nij (N_{TF}) vs. Time	B-18
Figure No. 64.	5 th Fem. P2 Driver Nij (N_{TE}) vs. Time	B-18
Figure No. 65.	5 th Fem. P2 Driver Nij (N_{CF}) vs. Time	B-18
Figure No. 66.	5 th Fem. P2 Driver Nij (N_{CE}) vs. Time	B-18
Figure No. 67.	6 Year Old Passenger P1 Head X Acceleration vs. Time	B-19
Figure No. 68.	6 Year Old Passenger P1 Head Y Acceleration vs. Time	B-19
Figure No. 69.	6 Year Old Passenger P1 Head Z Acceleration vs. Time	B-19
Figure No. 70.	6 Year Old Passenger P1 Head Resultant Acceleration vs. Time	B-19
Figure No. 71.	6 Year Old Passenger P1 Head X Velocity vs. Time	B-20
Figure No. 72.	6 Year Old Passenger P1 Head Y Velocity vs. Time	B-20
Figure No. 73.	6 Year Old Passenger P1 Head Z Velocity vs. Time	B-20
Figure No. 74.	6 Year Old Passenger P1 Neck Force X vs. Time	B-21
Figure No. 75.	6 Year Old Passenger P1 Neck Force Y vs. Time	B-21
Figure No. 76.	6 Year Old Passenger P1 Neck Force Z vs. Time	B-21
Figure No. 77.	6 Year Old Passenger P1 Neck Force Resultant vs. Time	B-21
Figure No. 78.	6 Year Old Passenger P1 Neck Moment X vs. Time	B-22
Figure No. 79.	6 Year Old Passenger P1 Neck Moment Y vs. Time	B-22
Figure No. 80.	6 Year Old Passenger P1 Neck Moment Z vs. Time	B-22
Figure No. 81.	6 Year Old Passenger P1 Occipital Condyle Moment vs. Time	B-22
Figure No. 82.	6 Year Old Passenger P1 Chest X Acceleration vs. Time	B-23
Figure No. 83.	6 Year Old Passenger P1 Chest Y Acceleration vs. Time	B-23
Figure No. 84.	6 Year Old Passenger P1 Chest Z Acceleration vs. Time	B-23
Figure No. 85.	6 Year Old Passenger P1 Chest Resultant Acceleration vs. Time	B-23
Figure No. 86.	6 Year Old Passenger P1 Chest X Velocity vs. Time	B-24
Figure No. 87.	6 Year Old Passenger P1 Chest Y Velocity vs. Time	B-24
Figure No. 88.	6 Year Old Passenger P1 Chest Z Velocity vs. Time	B-24
Figure No. 89.	6 Year Old Passenger P1 Chest Displacement vs. Time	B-24

	<u>Page No.</u>
Figure No. 90. Fire Voltage #1 Voltage vs. Time	B-25
Figure No. 91. Fire Current #1 Voltage vs. Time	B-25
Figure No. 92. Fire Voltage #2 Voltage vs. Time	B-25
Figure No. 93. Fire Current #2 Voltage vs. Time	B-25
Figure No. 94. 6 Year Old Passenger P1 Nij (N_{TF}) vs. Time	B-26
Figure No. 95. 6 Year Old Passenger P1 Nij (N_{TE}) vs. Time	B-26
Figure No. 96. 6 Year Old Passenger P1 Nij (N_{CF}) vs. Time	B-26
Figure No. 97. 6 Year Old Passenger P1 Nij (N_{CE}) vs. Time	B-26
Figure No. 98. 6 Year Old Passenger P2 Head X Acceleration vs. Time	B-27
Figure No. 99. 6 Year Old Passenger P2 Head Y Acceleration vs. Time	B-27
Figure No. 100. 6 Year Old Passenger P2 Head Z Acceleration vs. Time	B-27
Figure No. 101. 6 Year Old Passenger P2 Head Resultant Acceleration vs. Time	B-27
Figure No. 102. 6 Year Old Passenger P2 Head X Velocity vs. Time	B-28
Figure No. 103. 6 Year Old Passenger P2 Head Y Velocity vs. Time	B-28
Figure No. 104. 6 Year Old Passenger P2 Head Z Velocity vs. Time	B-28
Figure No. 105. 6 Year Old Passenger P2 Neck Force X vs. Time	B-29
Figure No. 106. 6 Year Old Passenger P2 Neck Force Y vs. Time	B-29
Figure No. 107. 6 Year Old Passenger P2 Neck Force Z vs. Time	B-29
Figure No. 108. 6 Year Old Passenger P2 Neck Force Resultant vs. Time	B-29
Figure No. 109. 6 Year Old Passenger P2 Neck Moment X vs. Time	B-30
Figure No. 110. 6 Year Old Passenger P2 Neck Moment Y vs. Time	B-30
Figure No. 111. 6 Year Old Passenger P2 Neck Moment Z vs. Time	B-30
Figure No. 112. 6 Year Old Passenger P2 Occipital Condyle Moment vs. Time	B-30
Figure No. 113. 6 Year Old Passenger P2 Chest X Acceleration vs. Time	B-31
Figure No. 114. 6 Year Old Passenger P2 Chest Y Acceleration vs. Time	B-31
Figure No. 115. 6 Year Old Passenger P2 Chest Z Acceleration vs. Time	B-31
Figure No. 116. 6 Year Old Passenger P2 Chest Resultant Acceleration vs. Time	B-31
Figure No. 117. 6 Year Old Passenger P2 Chest X Velocity vs. Time	B-32
Figure No. 118. 6 Year Old Passenger P2 Chest Y Velocity vs. Time	B-32
Figure No. 119. 6 Year Old Passenger P2 Chest Z Velocity vs. Time	B-32


		<u>Page No.</u>
Figure No. 120.	6 Year Old Passenger P2 Chest Displacement vs. Time	B-32
Figure No. 121.	Fire Voltage #1 Voltage vs. Time	B-33
Figure No. 122.	Fire Current #1 Voltage vs. Time	B-33
Figure No. 123.	Fire Voltage #2 Voltage vs. Time	B-33
Figure No. 124.	Fire Current #2 Voltage vs. Time	B-33
Figure No. 125.	6 Year Old Passenger P2 Nij (N_{TF}) vs. Time	B-34
Figure No. 126.	6 Year Old Passenger P2 Nij (N_{TE}) vs. Time	B-34
Figure No. 127.	6 Year Old Passenger P2 Nij (N_{CF}) vs. Time	B-34
Figure No. 128.	6 Year Old Passenger P2 Nij (N_{CE}) vs. Time	B-34









5TH FEM. DRIVER NECK FX (N) vs TIME (ms)




5TH FEM. DRIVER NECK FY (N) vs TIME (ms)



5TH FEM. DRIVER NECK FZ (N) vs TIME (ms)




5TH FEM. DRIVER NECK FResultant (N) vs TIME (ms)







5TH FEM. DRIVER NECK MX (Nm) vs TIME (ms)




5TH FEM. DRIVER NECK MY (Nm) vs TIME (ms)



5TH FEM. DRIVER NECK MZ (Nm) vs TIME (ms)




Drv. Occipital Condyle Moment (Nm) vs TIME (ms)






5TH FEM. DRIVER CHEST X (G's) vs TIME (ms)




Max: 1.9 G's
Tmax: 64.8 ms
Min: -6.6 G's
Tmin: 11.1 ms
CFC 180

5TH FEM. DRIVER CHEST Y (G's) vs TIME (ms)




Max: 1.2 G's
Tmax: 29.3 ms
Min: -2.0 G's
Tmin: 23.3 ms
CFC 180

5TH FEM. DRIVER CHEST Z (G's) vs TIME (ms)



Max: 5.1 G's
Tmax: 12.1 ms
Min: -6.7 G's
Tmin: 8.0 ms
CFC 180


5TH FEM. DRIVER CHEST Resultant (G's) vs TIME (ms)




Max: 7.7 G's
Tmax: 12.1 ms
Min: 0.0 G's
Tmin: 2.1 ms
CFC 180




5TH FEM. DRIVER CHEST X Velocity (kph) vs TIME (ms)




5TH FEM. DRIVER CHEST Y Velocity (kph) vs TIME (ms)



5TH FEM. DRIVER CHEST Z Velocity (kph) vs TIME (ms)




5TH FEM. DRIVER CHEST DISPLACEMENT (mm) vs TIME (ms)






5TH FEM. DRIVER LEFT FEMUR (N) vs TIME (ms)




5TH FEM. DRIVER RIGHT FEMUR (N) vs TIME (ms)







FIRE VOLTAGE #1 (Volts) vs TIME (ms)




FIRE CURRENT #1 (Amps) vs TIME (ms)











FIRE VOLTAGE #2 (Volts) vs TIME (ms)










FIRE CURRENT #2 (Amps) vs TIME (ms)
















5TH FEM. DRIVER NECK MX (Nm) vs TIME (ms)




5TH FEM. DRIVER NECK MY (Nm) vs TIME (ms)







5TH FEM. DRIVER NECK MZ (Nm) vs TIME (ms)




Drv. Occipital Condyle Moment (Nm) vs TIME (ms)









5TH FEM. DRIVER CHEST X Velocity (kph) vs TIME (ms)




5TH FEM. DRIVER CHEST Y Velocity (kph) vs TIME (ms)









5TH FEM. DRIVER CHEST Z Velocity (kph) vs TIME (ms)



5TH FEM. DRIVER CHEST DISPLACEMENT (mm) vs TIME (ms)












Drv. nij (NTF) () vs TIME SPECIAL CHS (ms)




Drv. nij (NTE) () vs TIME SPECIAL CHS (ms)










Drv. nij (NCF) () vs TIME SPECIAL CHS (ms)



Drv. nij (NCE) () vs TIME SPECIAL CHS (ms)












6YR OLD PASSENGER NECK FX (N) vs TIME (ms)




6YR OLD PASSENGER NECK FY (N) vs TIME (ms)











6YR OLD PASSENGER NECK FZ (N) vs TIME (ms)



6YR OLD PASSENGER NECK FResultant (N) vs TIME (ms)












1 6YR OLD PASSENGER CHEST X Velocity (kph) vs TIME (ms)




6YR OLD PASSENGER CHEST Y Velocity (kph) vs TIME (ms)



6YR OLD PASSENGER CHEST Z Velocity (kph) vs TIME (ms)




2 6YR OLD PASSENGER CHEST DISPLACEMENT (mm) vs TIME (ms)







FIRE VOLTAGE #1 (Volts) vs TIME (ms)




FIRE CURRENT #1 (Amps) vs TIME (ms)











FIRE VOLTAGE #2 (Volts) vs TIME (ms)






FIRE CURRENT #2 (Amps) vs TIME (ms)














6YR OLD PASSENGER NECK FX (N) vs TIME (ms)




6YR OLD PASSENGER NECK FY (N) vs TIME (ms)



6YR OLD PASSENGER NECK FZ (N) vs TIME (ms)




6YR OLD PASSENGER NECK FResultant (N) vs TIME (ms)







6YR OLD PASSENGER NECK MX (Nm) vs TIME (ms)




6YR OLD PASSENGER NECK MY (Nm) vs TIME (ms)



6YR OLD PASSENGER NECK MZ (Nm) vs TIME (ms)




Pass. Occipital Condyle Moment (Nm) vs TIME (ms)







6YR OLD PASSENGER CHEST X (G's) vs TIME (ms)




6YR OLD PASSENGER CHEST Y (G's) vs TIME (ms)



6YR OLD PASSENGER CHEST Z (G's) vs TIME (ms)




6YR OLD PASSENGER CHEST Resultant (G's) vs TIME (ms)







6YR OLD PASSENGER CHEST X Velocity (kph) vs TIME (ms)




6YR OLD PASSENGER CHEST Y Velocity (kph) vs TIME (ms)



6YR OLD PASSENGER CHEST Z Velocity (kph) vs TIME (ms)




6YR OLD PASSENGER CHEST DISPLACEMENT (mm) vs TIME (ms)







FIRE VOLTAGE #1 (Volts) vs TIME (ms)




FIRE CURRENT #1 (Amps) vs TIME (ms)



FIRE VOLTAGE #2 (Volts) vs TIME (ms)




FIRE CURRENT #2 (Amps) vs TIME (ms)







PASS. nij (NTF) () vs TIME SPECIAL CHS (ms)




Pass. nij (NTE) () vs TIME SPECIAL CHS (ms)



Pass. nij (NCF) () vs TIME SPECIAL CHS (ms)



Pass. nij (NCE) () vs TIME SPECIAL CHS (ms)



APPENDIX C
CRASH TEST PHOTOGRAPHS

TABLE OF PHOTOGRAPHS

Page No.

Photo No. 1.	Vehicle Certification Label	C-1
Photo No. 2.	Tire Placard	C-2
Photo No. 3.	Pre-Test Front View of Test Vehicle	C-3
Photo No. 4.	Post-Test Front View of Test Vehicle	C-4
Photo No. 5.	Pre-Test Left Side View of Test Vehicle	C-5
Photo No. 6.	Post-Test Left Side View of Test Vehicle	C-6
Photo No. 7.	Pre-Test Right Side View of Test Vehicle	C-7
Photo No. 8.	Post-Test Right Side View of Test Vehicle	C-8
Photo No. 9.	Pre-Test Right Front Three-Quarter View of Test Vehicle	C-9
Photo No. 10.	Post-Test Right Front Three-Quarter View of Test Vehicle	C-10
Photo No. 11.	Pre-Test Left Rear Three-Quarter View of Test Vehicle	C-11
Photo No. 12.	Post-Test Left Rear Three-Quarter View of Test Vehicle	C-12
Photo No. 13.	Pre-Test Rear View of Test Vehicle	C-13
Photo No. 14.	Post-Test Rear View of Test Vehicle	C-14
Photo No. 15.	Pre-Test Windshield View	C-15
Photo No. 16.	Post-Test Windshield View	C-16
Photo No. 17.	Pre-Test Engine Compartment View	C-17
Photo No. 18.	Post-Test Engine Compartment View	C-18
Photo No. 19.	Pre-Test Fuel Filler Cap View	C-19
Photo No. 20.	Post-Test Fuel Filler Cap View	C-20
Photo No. 21.	Pre-Test Front Underbody View	C-21
Photo No. 22.	Post-Test Front Underbody View	C-22
Photo No. 23.	Pre-Test Front Mid Underbody	C-23
Photo No. 24.	Pre-Test Rear Mid Underbody	C-24
Photo No. 25.	Post-Test Mid Underbody	C-25
Photo No. 26.	Pre-Test Rear Underbody View	C-26
Photo No. 27.	Post-Test Rear Underbody View	C-27

Page No.

Photo No. 28.	Post-Test Fuel Tank View	C-28
Photo No. 29.	Pre-Test Driver Dummy Front View (head position)	C-29
Photo No. 30.	Post-Test Driver Dummy Front View (head position)	C-30
Photo No. 31.	Pre-Test Driver Dummy Position Left Side View	C-31
Photo No. 32.	Post-Test Driver Dummy Position Left Side View	C-32
Photo No. 33.	Pre-Test Driver Dummy Position Left Side View (Door Open)	C-33
Photo No. 34.	Post-Test Driver Dummy Position Left Side View (Door Open)	C-34
Photo No. 35.	Pre-Test Driver Dummy Seat Position	C-35
Photo No. 36.	Post-Test Driver Dummy Seat Position	C-36
Photo No. 37.	Pre-Test Driver Dummy Feet Position	C-37
Photo No. 38.	Post-Test Driver Dummy Feet Position	C-38
Photo No. 39.	Pre-Test Driver Side Knee Bolster View	C-39
Photo No. 40.	Post-Test Driver Side Knee Bolster View	C-40
Photo No. 41.	Post-Test Driver Dummy Head Contact	C-41
Photo No. 42.	Post-Test Driver Dummy Head Contact (visor)	C-42
Photo No. 43.	Post-Test Driver Dummy Knee Contact	C-43
Photo No. 44.	Post-Test Driver Dummy Airbag Contact	C-44
Photo No. 45.	Pre-Test Passenger Dummy Front View (head position)	C-45
Photo No. 46.	Post-Test Passenger Dummy Front View (head position)	C-46
Photo No. 47.	Pre-Test Passenger Dummy Position Right Side View	C-47
Photo No. 48.	Post-Test Passenger Dummy Position Right Side View	C-48
Photo No. 49.	Pre-Test Passenger Dummy Position Right Side View (Door Open)	C-49
Photo No. 50.	Post-Test Passenger Dummy Position Right Side View (Door Open)	C-50
Photo No. 51.	Pre-Test Passenger Dummy Seat Position	C-51
Photo No. 52.	Post-Test Passenger Dummy Seat Position	C-52
Photo No. 53.	Pre-Test Passenger Dummy Feet Position	C-53
Photo No. 54.	Post-Test Passenger Dummy Feet Position	C-54
Photo No. 55.	Pre-Test Passenger Side Knee Bolster View	C-55

Page No.

Photo No. 56.	Post-Test Passenger Side Knee Bolster View	C-56
Photo No. 57.	Post-Test Passenger Dummy Head Contact	C-57
Photo No. 58.	Post-Test Passenger Dummy Knee Contact	C-58
Photo No. 59.	Post-Test Passenger Dummy Airbag Contact	C-59
Photo No. 60.	Rollover 90 Degrees	C-60
Photo No. 61.	Rollover 180 Degrees	C-61
Photo No. 62.	Rollover 270 Degrees	C-62
Photo No. 63.	Rollover 360 Degrees	C-63
Photo No. 64.	Vehicle Impact	C-64
Photo No. 65.	Temperature Plot	C-65

MADE IN U.S.A. DATE OCT. 2003
MFD BY MITSUBISHI MOTORS NORTH AMERICA, INC.

GVWR 4321 LBS GAWR 2293 LBS GAWR 2028 LBS
1960 KG FR. 1040 KG RR. 920 KG

THIS VEHICLE CONFORMS TO ALL APPLICABLE
FEDERAL MOTOR VEHICLE SAFETY, BUMPER, AND
THEFT PREVENTION STANDARDS IN EFFECT ON
THE DATE OF MANUFACTURE SHOWN ABOVE.

4 A 3 A B 5 6 F 6 4 E 0 5 1 8 5 5



MDH 100811

VEHICLE TYPE: PASSENGER CAR MU900282



Tire Placard



Pre-Test Front View of Test Vehicle



Post-Test Front View of Test Vehicle



Pre-Test Left Side View of Test Vehicle



Post-Test Left Side View of Test Vehicle



Pre-Test Right Side View of Test Vehicle



Post-Test Right Side View of Test Vehicle



Pre-Test Right Front Three-Quarter View of Test Vehicle



Post-Test Right Front Three-Quarter View of Test Vehicle



Pre-Test Left Rear Three-Quarter View of Test Vehicle



Post-Test Left Rear Three-Quarter View of Test Vehicle



Pre-Test Rear View of Test Vehicle



Post-Test Rear View of Test Vehicle



Pre-Test Windshield View



Post-Test Windshield View



Pre-Test Engine Compartment View



Post-Test Engine Compartment View


mga
mga research corporation
PRE-TEST
C45603
25 MPH FRONTAL UNBELTED
04072301
MGA RESEARCH CORP.
2004 MITSUBISHI GALANT




Pre-Test Fuel Filler Cap View



Post-Test Fuel Filler Cap View



Pre-Test Front Underbody View



Post-Test Front Underbody View




Pre-Test Front Mid Underbody




Pre-Test Rear Mid Underbody




Post-Test Mid Underbody



Pre-Test Rear Underbody View



Post-Test Rear Underbody View



Post-Test Fuel Tank View



Pre-Test Driver Dummy Front View (head position)



Post-Test Driver Dummy Front View (head position)



Pre-Test Driver Dummy Position Left Side View



Post-Test Driver Dummy Position Left Side View



Pre-Test Driver Dummy Position Left Side View (Door Open)



Post-Test Driver Dummy Position Left Side View (Door Open)



Pre-Test Driver Dummy Seat Position



Post-Test Driver Dummy Seat Position



Pre-Test Driver Dummy Feet Position



Post-Test Driver Dummy Feet Position



Pre-Test Driver Side Knee Bolster View



Post-Test Driver Side Knee Bolster View

C-41.



Post-Test Driver Dummy Head Contact



Post-Test Driver Dummy Head Contact (visor)



Post-Test Driver Dummy Knee Contact



Post-Test Driver Dummy Airbag Contact



Pre-Test Passenger Dummy Front View (head position)



Post-Test Passenger Dummy Front View (head position)



Pre-Test Passenger Dummy Position Right Side View



Post-Test Passenger Dummy Position Right Side View



Pre-Test Passenger Dummy Position Right Side View (Door Open)



Post-Test Passenger Dummy Position Right Side View (Door Open)



Pre-Test Passenger Dummy Seat Position



Post-Test Passenger Dummy Seat Position



Pre-Test Passenger Dummy Feet Position




Post-Test Passenger Dummy Feet Position



Pre-Test Passenger Side Knee Bolster View



Post-Test Passenger Side Knee Bolster View



Post-Test Passenger Dummy Head Contact



Post-Test Passenger Dummy Knee Contact



Post-Test Passenger Dummy Airbag Contact



C-60.

Rollover 90 Degrees



Rollover 180 Degrees



Rollover 270 Degrees



Rollover 360 Degrees

Vehicle Impact

APPENDIX D
LOW RISK PHOTOGRAPHS

TABLE OF PHOTOGRAPHS

	<u>Page No.</u>
Photo No. 1. Post-Test 5 th Fem. P1 Driver Dummy Left Side View	D-1
Photo No. 2. Pre-Test 5 th Fem. P1 Driver Dummy Left Side View (Door Open)	D-2
Photo No. 3. Post-Test 5 th Fem. P1 Driver Dummy Left Side View (Door Open)	D-3
Photo No. 4. Pre-Test 5 th Fem. P1 Driver Dummy Right Side View (Door Open)	D-4
Photo No. 5. Post-Test 5 th Fem. P1 Driver Dummy Right Side View (Door Open)	D-5
Photo No. 6. Pre-Test 5 th Fem. P1 Driver Dummy Left Side Head Position View	D-6
Photo No. 7. Post-Test 5 th Fem. P1 Driver Dummy Left Side Head Position View	D-7
Photo No. 8. Pre-Test 5 th Fem. P1 Driver Dummy Right Side Head Position View	D-8
Photo No. 9. Post-Test 5 th Fem. P1 Driver Dummy Right Side Head Position View	D-9
Photo No. 10. Pre-Test 5 th Fem. P1 Driver Dummy Left Side Knee Position View	D-10
Photo No. 11. Post-Test 5 th Fem. P1 Driver Dummy Left Side Knee Position View	D-11
Photo No. 12. Pre-Test 5 th Fem. P1 Driver Dummy Right Side Knee Position View	D-12
Photo No. 13. Post-Test 5 th Fem. P1 Driver Dummy Right Side Knee Position View	D-13
Photo No. 14. Post-Test 5 th Fem. P1 Driver Dummy Airbag Left View	D-14
Photo No. 15. Post-Test 5 th Fem. P1 Driver Dummy Airbag Right View	D-15
Photo No. 16. Post-Test 5 th Fem. P1 Driver Dummy Airbag Front View	D-16
Photo No. 17. Post-Test 5 th Fem. P2 Driver Dummy Left Side View	D-17
Photo No. 18. Post-Test 5 th Fem. P2 Driver Dummy Right Side View	D-18
Photo No. 19. Pre-Test 5 th Fem. P2 Driver Dummy Left Side View (Door Open)	D-19
Photo No. 20. Post-Test 5 th Fem. P2 Driver Dummy Left Side View (Door Open)	D-20
Photo No. 21. Pre-Test 5 th Fem. P2 Driver Dummy Right Side View (Door Open)	D-21
Photo No. 22. Post-Test 5 th Fem. P2 Driver Dummy Right Side View (Door Open)	D-22
Photo No. 23. Pre-Test 5 th Fem. P2 Driver Dummy Left Side Head Position View	D-23
Photo No. 24. Post-Test 5 th Fem. P2 Driver Dummy Left Side Head Position View	D-24
Photo No. 25. Pre-Test 5 th Fem. P2 Driver Dummy Right Side Head Position View	D-25
Photo No. 26. Post-Test 5 th Fem. P2 Driver Dummy Right Side Head Position View	D-26
Photo No. 27. Pre-Test 5 th Fem. P2 Driver Dummy Left Side Mid Position View	D-27

Photo No. 28.	Pre-Test 5 th Fem. P2 Driver Dummy Right Side Mid Position View	D-28
Photo No. 29.	Pre-Test 5 th Fem. P2 Driver Dummy Left Side Knee Position View	D-29
Photo No. 30.	Post-Test 5 th Fem. P2 Driver Dummy Left Side Knee Position View	D-30
Photo No. 31.	Pre-Test 5 th Fem. P2 Driver Dummy Right Side Knee Position View	D-31
Photo No. 32.	Post-Test 5 th Fem. P2 Driver Dummy Right Side Knee Position View	D-32
Photo No. 33.	Post-Test 5 th Fem. P2 Driver Dummy Head Contact (visor)	D-33
Photo No. 34.	Post-Test 5 th Fem. P2 Driver Dummy Airbag Left View	D-34
Photo No. 35.	Post-Test 5 th Fem. P2 Driver Dummy Airbag Right View	D-35
Photo No. 36.	Post-Test 6 Year Old Passenger P1 Dummy Left Side View	D-36
Photo No. 37.	Post-Test 6 Year Old Passenger P1 Dummy Right Side View	D-37
Photo No. 38.	Pre-Test 6 Year Old Passenger P1 Dummy Left Side View (Door Open)	D-38
Photo No. 39.	Post-Test 6 Year Old Passenger P1 Dummy Left Side View (Door Open)	D-39
Photo No. 40.	Pre-Test 6 Year Old Passenger P1 Dummy Right Side View (Door Open)	D-40
Photo No. 41.	Post-Test 6 Year Old Passenger P1 Dummy Right Side View (Door Open)	D-41
Photo No. 42.	Pre-Test 6 Year Old Passenger P1 Dummy Left Side Mid Position View	D-42
Photo No. 43.	Post-Test 6 Year Old Passenger P1 Dummy Left Side Mid Position View	D-43
Photo No. 44.	Pre-Test 6 Year Old Passenger P1 Dummy Right Side Mid Position View	D-44
Photo No. 45.	Post-Test 6 Year Old Passenger P1 Dummy Right Side Mid Position View	D-45
Photo No. 46.	Pre-Test 6 Year Old Passenger P1 Dummy Left Side Seat Position View	D-46
Photo No. 47.	Pre-Test 6 Year Old Passenger P1 Dummy Right Side Seat Position View	D-47
Photo No. 48.	Post-Test 6 Year Old Passenger P1 Dummy Left Side Head Contact View	D-48
Photo No. 49.	Post-Test 6 Year Old Passenger P1 Dummy Right Side Head Contact View	D-49
Photo No. 50.	Post-Test 6 Year Old Passenger P1 Dummy Airbag Contact	D-50
Photo No. 51.	Post-Test 6 Year Old Passenger P2 Dummy Left Side View	D-51
Photo No. 52.	Post-Test 6 Year Old Passenger P2 Dummy Right Side View	D-52
Photo No. 53.	Pre-Test 6 Year Old Passenger P2 Dummy Left Side View (Door Open)	D-53
Photo No. 54.	Pre-Test 6 Year Old Passenger P2 Dummy Right Side View (Door Open)	D-54
Photo No. 55.	Post-Test 6 Year Old Passenger P2 Dummy Right Side View (Door Open)	D-55
Photo No. 56.	Pre-Test 6 Year Old Passenger P2 Dummy Left Side Head Position View	D-56

Page No.

Photo No. 57.	Post-Test 6 Year Old Passenger P2 Dummy Left Side Head Position View	D-57
Photo No. 58.	Pre-Test 6 Year Old Passenger P2 Dummy Right Side Head Position View	D-58
Photo No. 59.	Post-Test 6 Year Old Passenger P2 Dummy Right Side Head Position View	D-59
Photo No. 60.	Pre-Test 6 Year Old Passenger P2 Dummy Left Side Knee Position View	D-60
Photo No. 61.	Post-Test 6 Year Old Passenger P2 Dummy Left Side Knee Position View	D-61
Photo No. 62.	Pre-Test 6 Year Old Passenger P2 Dummy Right Side Knee Position View	D-62
Photo No. 63.	Post-Test 6 Year Old Passenger Dummy Airbag Left View	D-63
Photo No. 64.	Post-Test 6 Year Old Passenger Dummy Airbag Right View	D-64
Photo No. 65.	Geometric Center (2004 Mitsubishi Galant)	D-65
Photo No. 66.	Geometric Center (2004 Mitsubishi Galant)	D-66



Post-Test 5th Fem. P1 Driver Dummy Left Side View



Pre-Test 5th Fem. P1 Driver Dummy Left Side View (Door Open)




Post-Test 5th Fem. P1 Driver Dummy Left Side View (Door Open)



Pre-Test 5th Fem. P1 Driver Dummy Right Side View (Door Open)



Post-Test 5th Fem. P1 Driver Dummy Right Side View (Door Open)




Pre-Test 5th Fem. P1 Driver Dummy Left Side Head Position View



Post-Test 5th Fem. P1 Driver Dummy Left Side Head Position View



Pre-Test 5th Fem. P1 Driver Dummy Right Side Head Position View




Post-Test 5th Fem. P1 Driver Dummy Right Side Head Position View


D-10.



Pre-Test 5th Fem. P1 Driver Dummy Left Side Knee Position View




Post-Test 5th Fem. P1 Driver Dummy Left Side Knee Position View




Pre-Test 5th Fem. P1 Driver Dummy Right Side Knee Position View

D-13.



Post-Test 5th Fem. P1 Driver Dummy Right Side Knee Position View

D-14.



Post-Test 5th Fem. P1 Driver Dummy Airbag Left View

D-15.



Post-Test 5th Fem. P1 Driver Dummy Airbag Right View

D-16.



Post-Test 5th Fem. P1 Driver Dummy Airbag Front View



5th % Low Risk Deployment Position 2
7-8-04 C45603
2004 Mitsubishi Galant
MGA Research Corp.

mga research corporation
POST-TEST
5th % Low Risk Deployment Position 2
C45603 7-8-04
2004 Mitsubishi Galant
MGA Research Corp.

Post-Test 5th Fem. P2 Driver Dummy Left Side View



Post-Test 5th Fem. P2 Driver Dummy Right Side View



Pre-Test 5th Fem. P2 Driver Dummy Left Side View (Door Open)



Post-Test 5th Fem. P2 Driver Dummy Left Side View (Door Open)



Pre-Test 5th Fem. P2 Driver Dummy Right Side View (Door Open)




Post-Test 5th Fem. P2 Driver Dummy Right Side View (Door Open)



Pre-Test 5th Fem. P2 Driver Dummy Left Side Head Position View



Post-Test 5th Fem. P2 Driver Dummy Left Side Head Position View




Pre-Test 5th Fem. P2 Driver Dummy Right Side Head Position View




Post-Test 5th Fem. P2 Driver Dummy Right Side Head Position View



Pre-Test 5th Fem. P2 Driver Dummy Left Side Mid Position View



Pre-Test 5th Fem. P2 Driver Dummy Right Side Mid Position View



Pre-Test 5th Fem. P2 Driver Dummy Left Side Knee Position View




Post-Test 5th Fem. P2 Driver Dummy Left Side Knee Position View



Pre-Test 5th Fem. P2 Driver Dummy Right Side Knee Position View



Post-Test 5th Fem. P2 Driver Dummy Right Side Knee Position View



Post-Test 5th Fem. P2 Driver Dummy Head Contact (visor)




Post-Test 5th Fem. P2 Driver Dummy Airbag Left View



Post-Test 5th Fem. P2 Driver Dummy Airbag Right View



Post-Test 6 Year Old Passenger P1 Dummy Left Side View



Post-Test 6 Year Old Passenger P1 Dummy Right Side View



Pre-Test 6 Year Old Passenger P1 Dummy Left Side View (Door Open)



Post-Test 6 Year Old Passenger P1 Dummy Left Side View (Door Open)



Pre-Test 6 Year Old Passenger P1 Dummy Right Side View (Door Open)



Post-Test 6 Year Old Passenger P1 Dummy Right Side View (Door Open)



Pre-Test 6 Year Old Passenger P1 Dummy Left Side Mid Position View



Post-Test 6 Year Old Passenger P1 Dummy Left Side Mid Position View

D-44.



Pre-Test 6 Year Old Passenger P1 Dummy Right Side Mid Position View

D-45.



Post-Test 6 Year Old Passenger P1 Dummy Right Side Mid Position View



Pre-Test 6 Year Old Passenger P1 Dummy Left Side Seat Position View



Pre-Test 6 Year Old Passenger P1 Dummy Right Side Seat Position View

D-48.



Post-Test 6 Year Old Passenger P1 Dummy Left Side Head Contact View



Post-Test 6 Year Old Passenger P1 Dummy Right Side Head Contact View



Post-Test 6 Year Old Passenger P1 Dummy Airbag Contact



Post-Test 6 Year Old Passenger P2 Dummy Left Side View



Post-Test 6 Year Old Passenger P2 Dummy Right Side View




Pre-Test 6 Year Old Passenger P2 Dummy Left Side View (Door Open)



Pre-Test 6 Year Old Passenger P2 Dummy Right Side View (Door Open)




Post-Test 6 Year Old Passenger P2 Dummy Right Side View (Door Open)



Pre-Test 6 Year Old Passenger P2 Dummy Left Side Head Position View




Post-Test 6 Year Old Passenger P2 Dummy Left Side Head Position View



Pre-Test 6 Year Old Passenger P2 Dummy Right Side Head Position View




Post-Test 6 Year Old Passenger P2 Dummy Right Side Head Position View



Pre-Test 6 Year Old Passenger P2 Dummy Left Side Knee Position View



Pre-Test 6 Year Old Passenger P2 Dummy Left Side Knee Position View




Pre-Test 6 Year Old Passenger P2 Dummy Right Side Knee Position View



Post-Test 6 Year Old Passenger Dummy Airbag Left View



Post-Test 6 Year Old Passenger Dummy Airbag Right View




Geometric Center (2004 Mitsubishi Galant)

The location of the geometric center of the opening "

A line : Boundary line between side air outlet(RH) and instrument pad

B line : From A line to 232.7 mm left measured along instrument panel face

C line : From the gap to 236 mm forward measured along instrument panel face



Geometric Center (2004 Mitsubishi Galant)

APPENDIX E
SUPPRESSION PHOTOGRAPHS

TABLE OF PHOTOGRAPHS

	<u>Page #</u>
Photo No. 1. Cosco Dream Ride Car Bed With Belt, Middle Seat Track	E-1
Photo No. 2. Unbelted 5 th Percentile Female Reactivation, Middle Seat Track	E-1
Photo No. 3. Britax Handle With Care 191 With Belt, Forward Seat Track, Handle Down	E-2
Photo No. 4. Britax Handle With Care 191 With Belt, Middle Seat Track, Handle Down	E-2
Photo No. 5. Britax Handle With Care 191 With Belt, Rearward Seat Track, Handle Down	E-2
Photo No. 6. Britax Handle With Care 191 Unbelted, Forward Seat Track, Handle Down	E-2
Photo No. 7. Britax Handle With Care 191 Unbelted, Middle Seat Track, Handle Down	E-3
Photo No. 8. Britax Handle With Care 191 Unbelted, Rearward Seat Track, Handle Down	E-3
Photo No. 9. Britax Handle With Care 191 Fwd Facing Unbelted, Forward Seat Track, Handle Down	E-3
Photo No. 10. Britax Handle With Care 191 Fwd Facing Unbelted, Middle Seat Track, Handle Down	E-3
Photo No. 11. Britax Handle With Care 191 Fwd Facing Unbelted, Rearward Seat Track, Handle Down	E-4
Photo No. 12. Unbelted 5 th Percentile Female Reactivation, Rearward Seat Track	E-4
Photo No. 13. Evenflo First Choice 204 With Belt, Forward Seat Track, Handle Up	E-5
Photo No. 14. Evenflo First Choice 204 With Belt, Middle Seat Track, Handle Up	E-5
Photo No. 15. Evenflo First Choice 204 With Belt, Rearward Seat Track, Handle Down	E-5
Photo No. 16. Evenflo First Choice 204 Unbelted, Forward Seat Track, Handle Up	E-5
Photo No. 17. Evenflo First Choice 204 Unbelted, Middle Seat Track, Handle Up	E-6
Photo No. 18. Evenflo First Choice 204 Unbelted, Rearward Seat Track, Handle Down	E-6
Photo No. 19. Evenflo First Choice 204 Fwd Facing Unbelted, Forward Seat Track, Handle Up	E-6
Photo No. 20. Evenflo First Choice 204 Fwd Facing Unbelted, Middle Seat Track, Handle Up	E-6
Photo No. 21. Evenflo First Choice 204 Fwd Facing Unbelted, Rearward Seat Track, Handle Up	E-7
Photo No. 22. Unbelted 5 th Percentile Female Reactivation, Middle Seat Track	E-7
Photo No. 23. Graco Infant W/ Base With Belt, Forward Seat Track, Handle Up	E-8
Photo No. 24. Graco Infant W/ Base With Belt, Middle Seat Track, Handle Down	E-8
Photo No. 25. Graco Infant W/ Base With Belt, Rearward Seat Track, Handle Down	E-8
Photo No. 26. Graco Infant W/ Base Unbelted, Forward Seat Track, Handle Up	E-8
Photo No. 27. Graco Infant W/ Base Unbelted, Middle Seat Track, Handle Up	E-9
Photo No. 28. Graco Infant W/ Base Unbelted, Rearward Seat Track, Handle Down	E-9
Photo No. 29. Graco Infant W/ Base Fwd Facing Unbelted, Forward Seat Track, Handle Up	E-9
Photo No. 30. Graco Infant W/ Base Fwd Facing Unbelted, Middle Seat Track, Handle Up	E-9
Photo No. 31. Graco Infant W/ Base Fwd Facing Unbelted, Rearward Seat Track, Handle Up	E-10
Photo No. 32. Graco Infant W/O Base With Belt, Forward Seat Track, Handle Up	E-10
Photo No. 33. Graco Infant W/O Base With Belt, Middle Seat Track, Handle Up	E-10

Photo No. 34.	Graco Infant W/O Base With Belt, Rearward Seat Track, Handle Up	E-10
Photo No. 35.	Graco Infant W/O Base Unbelted, Forward Seat Track, Handle Up	E-11
Photo No. 36.	Graco Infant W/O Base Unbelted, Middle Seat Track, Handle Up	E-11
Photo No. 37.	Graco Infant W/O Base Unbelted, Rearward Seat Track, Handle Up	E-11
Photo No. 38.	Graco Infant W/O Base Fwd Facing Unbelted, Forward Seat Track, Handle Up	E-11
Photo No. 39.	Graco Infant W/O Base Fwd Facing Unbelted, Middle Seat Track, Handle Up	E-12
Photo No. 40.	Graco Infant W/O Base Fwd Facing Unbelted, Rearward Seat Track, Handle Up	E-12
Photo No. 41.	Unbelted 5 th Percentile Female Reactivation, Forward Seat Track	E-12
Photo No. 42.	Britax Roundabout 161 Fwd Facing With Belt, Forward Seat Track	E-13
Photo No. 43.	Britax Roundabout 161 Fwd Facing With Belt, Middle Seat Track	E-13
Photo No. 44.	Britax Roundabout 161 Fwd Facing With Belt, Rearward Seat Track	E-13
Photo No. 45.	Britax Roundabout 161 Fwd Facing Unbelted, Forward Seat Track	E-13
Photo No. 46.	Britax Roundabout 161 Fwd Facing Unbelted, Middle Seat Track	E-14
Photo No. 47.	Britax Roundabout 161 Fwd Facing Unbelted, Rearward Seat Track	E-14
Photo No. 48.	Britax Roundabout 161 Rear Facing With Belt, Forward Seat Track	E-14
Photo No. 49.	Britax Roundabout 161 Rear Facing With Belt, Middle Seat Track	E-14
Photo No. 50.	Britax Roundabout 161 Rear Facing With Belt, Rearward Seat Track	E-15
Photo No. 51.	Britax Roundabout 161 Rear Facing Unbelted, Forward Seat Track	E-15
Photo No. 52.	Britax Roundabout 161 Rear Facing Unbelted, Middle Seat Track	E-15
Photo No. 53.	Britax Roundabout 161 Rear Facing Unbelted, Rearward Seat Track	E-15
Photo No. 54.	Unbelted 5 th Percentile Female Reactivation, Rearward Seat Track	E-16
Photo No. 55.	Century Encore Fwd Facing With Belt, Forward Seat Track	E-17
Photo No. 56.	Century Encore Fwd Facing With Belt, Middle Seat Track	E-17
Photo No. 57.	Century Encore Fwd Facing With Belt, Rearward Seat Track	E-17
Photo No. 58.	Century Encore Fwd Facing Unbelted, Forward Seat Track	E-17
Photo No. 59.	Century Encore Fwd Facing Unbelted, Middle Seat Track	E-18
Photo No. 60.	Century Encore Fwd Facing Unbelted, Rearward Seat Track	E-18
Photo No. 61.	Century Encore Rear Facing With Belt, Forward Seat Track	E-18
Photo No. 62.	Century Encore Rear Facing With Belt, Middle Seat Track	E-18
Photo No. 63.	Century Encore Rear Facing With Belt, Rearward Seat Track	E-19
Photo No. 64.	Century Encore Rear Facing Unbelted, Forward Seat Track	E-19
Photo No. 65.	Century Encore Rear Facing Unbelted, Middle Seat Track	E-19
Photo No. 66.	Century Encore Rear Facing Unbelted, Rearward Seat Track	E-19
Photo No. 67.	Unbelted 5 th Percentile Female Reactivation, Middle Seat Track	E-20
Photo No. 68.	Evenflo Medallion 254 Fwd Facing With Belt, Forward Seat Track	E-21

Photo No. 69.	Evenflo Medallion 254 Fwd Facing With Belt, Middle Seat Track	E-21
Photo No. 70.	Evenflo Medallion 254 Fwd Facing With Belt, Rearward Seat Track	E-21
Photo No. 71.	Evenflo Medallion 254 Fwd Facing Unbelted, Forward Seat Track	E-21
Photo No. 72.	Evenflo Medallion 254 Fwd Facing Unbelted, Middle Seat Track	E-22
Photo No. 73.	Evenflo Medallion 254 Fwd Facing Unbelted, Rearward Seat Track	E-22
Photo No. 74.	Evenflo Medallion 254 Rear Facing With Belt, Forward Seat Track	E-22
Photo No. 75.	Evenflo Medallion 254 Rear Facing With Belt, Middle Seat Track	E-22
Photo No. 76.	Evenflo Medallion 254 Rear Facing With Belt, Rearward Seat Track	E-23
Photo No. 77.	Evenflo Medallion 254 Rear Facing Unbelted, Forward Seat Track	E-23
Photo No. 78.	Evenflo Medallion 254 Rear Facing Unbelted, Middle Seat Track	E-23
Photo No. 79.	Evenflo Medallion 254 Rear Facing Unbelted, Rearward Seat Track	E-23
Photo No. 80.	Unbelted 5 th Percentile Female Reactivation, Rearward Seat Track	E-24
Photo No. 81.	3-Year-Old Fwd Facing Britax Roundabout Belted, Forward Seat Track	E-25
Photo No. 82.	3-Year-Old Fwd Facing Britax Roundabout Belted, Middle Seat Track	E-25
Photo No. 83.	3-Year-Old Fwd Facing Britax Roundabout Belted, Rearward Seat Track	E-25
Photo No. 84.	Unbelted 5 th Percentile Female Reactivation, Rearward Seat Track	E-25
Photo No. 85.	3-Year-Old Fwd Facing Century Encore Belted, Forward Seat Track	E-26
Photo No. 86.	3-Year-Old Fwd Facing Century Encore Belted, Middle Seat Track	E-26
Photo No. 87.	3-Year-Old Fwd Facing Century Encore Belted, Rearward Seat Track	E-26
Photo No. 88.	Unbelted 5 th Percentile Female Reactivation, Middle Seat Track	E-26
Photo No. 89.	3-Year-Old Fwd Facing Evenflo Medallion Belted, Forward Seat Track	E-27
Photo No. 90.	3-Year-Old Fwd Facing Evenflo Medallion Belted, Middle Seat Track	E-27
Photo No. 91.	3-Year-Old Fwd Facing Evenflo Medallion Belted, Rearward Seat Track	E-27
Photo No. 92.	Unbelted 5 th Percentile Female Reactivation, Forward Seat Track	E-27
Photo No. 93.	3-Year-Old Century Next Step Belted, Forward Seat Track	E-28
Photo No. 94.	3-Year-Old Century Next Step Belted, Middle Seat Track	E-28
Photo No. 95.	3-Year-Old Century Next Step Belted, Rearward Seat Track	E-28
Photo No. 96.	3-Year-Old Century Next Step Cinched With Harness, Forward Seat Track	E-28
Photo No. 97.	3-Year-Old Century Next Step Cinched With Harness, Middle Seat Track	E-29
Photo No. 98.	3-Year-Old Century Next Step Cinched With Harness, Rearward Seat Track	E-29
Photo No. 99.	Unbelted 5 th Percentile Female Reactivation, Rearward Seat Track	E-29
Photo No. 100.	3-Year-Old Cosco High Back Booster Belted, Forward Seat Track	E-30
Photo No. 101.	3-Year-Old Cosco High Back Booster Belted, Middle Seat Track	E-30
Photo No. 102.	3-Year-Old Cosco High Back Booster Belted, Rearward Seat Track	E-30
Photo No. 103.	3-Year-Old Cosco High Back Booster Cinched With Harness, Forward Seat Track	E-30

Photo No. 104.	3-Year-Old Cosco High Back Booster Cinched With Harness, Middle Seat Track	E-31
Photo No. 105.	3-Year-Old Cosco High Back Booster Cinched With Harness, Rearward Seat Track	E-31
Photo No. 106.	Unbelted 5 th Percentile Female Reactivation, Rearward Seat Track	E-31
Photo No. 107.	3-Year-Old Unbelted, Forward Seat Track, Position 1	E-32
Photo No. 108.	3-Year-Old Unbelted, Forward Seat Track, Position 2	E-32
Photo No. 109.	3-Year-Old Unbelted, Forward Seat Track, Position 3	E-32
Photo No. 110.	3-Year-Old Unbelted, Forward Seat Track, Position 4	E-32
Photo No. 111.	3-Year-Old Unbelted, Forward Seat Track, Position 5	E-33
Photo No. 112.	3-Year-Old Unbelted, Forward Seat Track, Position 6	E-33
Photo No. 113.	3-Year-Old Unbelted, Forward Seat Track, Position 7	E-33
Photo No. 114.	3-Year-Old Unbelted, Middle Seat Track, Position 1	E-33
Photo No. 115.	3-Year-Old Unbelted, Middle Seat Track, Position 2	E-34
Photo No. 116.	3-Year-Old Unbelted, Middle Seat Track, Position 3	E-34
Photo No. 117.	3-Year-Old Unbelted, Middle Seat Track, Position 4	E-34
Photo No. 118.	3-Year-Old Unbelted, Middle Seat Track, Position 5	E-34
Photo No. 119.	3-Year-Old Unbelted, Middle Seat Track, Position 6	E-35
Photo No. 120.	3-Year-Old Unbelted, Middle Seat Track, Position 7	E-35
Photo No. 121.	3-Year-Old Unbelted, Rearward Seat Track, Position 1	E-35
Photo No. 122.	3-Year-Old Unbelted, Rearward Seat Track, Position 2	E-35
Photo No. 123.	3-Year-Old Unbelted, Rearward Seat Track, Position 3	E-36
Photo No. 124.	3-Year-Old Unbelted, Rearward Seat Track, Position 4	E-36
Photo No. 125.	3-Year-Old Unbelted, Rearward Seat Track, Position 5	E-36
Photo No. 126.	3-Year-Old Unbelted, Rearward Seat Track, Position 6	E-36
Photo No. 127.	3-Year-Old Unbelted, Rearward Seat Track, Position 7	E-37
Photo No. 128.	Unbelted 5 th Percentile Female Reactivation, Rearward Seat Track	E-37

DOT/NHTSA 208 Suppression Test – 2004 Mitsubishi Galant (C45603)

Newborn

Section A

Car Bed



Cosco Dream Ride Car Bed With Belt, Middle Seat Track



Unbelted 5th Percentile Female Reactivation,
Middle Seat Track

DOT/NHTSA 208 Suppression Test – 2004 Mitsubishi Galant (C45603)

12 Month

Section B

Rear Facing CRS



Britax Handle With Care 191 With Belt, Forward Seat Track, Handle Down



Britax Handle With Care 191 With Belt, Middle Seat Track, Handle Down



Britax Handle With Care 191 With Belt, Rearward Seat Track, Handle Down



Britax Handle With Care 191 Unbelted, Forward Seat Track, Handle Down

DOT/NHTSA 208 Suppression Test – 2004 Mitsubishi Galant (C45603)

12 Month

Section B

Rear Facing CRS



Britax Handle With Care 191 Unbelted, Middle Seat Track, Handle Down



Britax Handle With Care 191 Unbelted, Rearward Seat Track, Handle Down



Britax Handle With Care 191 Fwd Facing Unbelted, Forward Seat Track, Handle Down



Britax Handle With Care 191 Fwd Facing Unbelted, Middle Seat Track, Handle Down

DOT/NHTSA 208 Suppression Test – 2004 Mitsubishi Galant (C45603)

12 Month

Section B

Rear Facing CRS



Britax Handle With Care 191 Fwd Facing Unbelted,
Rearward Seat Track, Handle Down



Unbelted 5th Percentile Female Reactivation,
Rearward Seat Track

DOT/NHTSA 208 Suppression Test – 2004 Mitsubishi Galant (C45603)

12 Month

Section B

Rear Facing CRS



Evenflo First Choice 204 With Belt, Forward Seat Track,
Handle Up



Evenflo First Choice 204 With Belt, Middle Seat Track,
Handle Up



Evenflo First Choice 204 With Belt, Rearward Seat Track,
Handle Down



Evenflo First Choice 204 Unbelted, Forward Seat Track,
Handle Up

DOT/NHTSA 208 Suppression Test – 2004 Mitsubishi Galant (C45603)

12 Month

Section B

Rear Facing CRS



Evenflo First Choice 204 Unbelted, Middle Seat Track, Handle Up



Evenflo First Choice 204 Unbelted, Rearward Seat Track, Handle Down



Evenflo First Choice 204 Fwd Facing Unbelted, Forward Seat Track, Handle Up



Evenflo First Choice 204 Fwd Facing Unbelted, Middle Seat Track, Handle Up

DOT/NHTSA 208 Suppression Test – 2004 Mitsubishi Galant (C45603)

12 Month

Section B

Rear Facing CRS



Evenflo First Choice 204 Fwd Facing Unbelted,
Rearward Seat Track, Handle Up



Unbelted 5th Percentile Female Reactivation,
Middle Seat Track

DOT/NHTSA 208 Suppression Test – 2004 Mitsubishi Galant (C45603)

12 Month

Section B

Rear Facing CRS



Graco Infant W/ Base With Belt, Forward Seat Track,
Handle Up



Graco Infant W/ Base With Belt, Middle Seat Track,
Handle Down



Graco Infant W/ Base With Belt, Rearward Seat Track,
Handle Down



Graco Infant W/ Base Unbelted, Forward Seat Track,
Handle Up

DOT/NHTSA 208 Suppression Test – 2004 Mitsubishi Galant (C45603)

12 Month

Section B

Rear Facing CRS

E-9



Graco Infant W/ Base Unbelted, Middle Seat Track,
Handle Up



Graco Infant W/ Base Unbelted, Rearward Seat Track,
Handle Down



Graco Infant W/ Base Fwd Facing Unbelted, Forward Seat Track,
Handle Up



Graco Infant W/ Base Fwd Facing Unbelted, Middle Seat Track,
Handle Up

DOT/NHTSA 208 Suppression Test – 2004 Mitsubishi Galant (C45603)

12 Month

Section B

Rear Facing CRS

E-10



Graco Infant W/ Base Fwd Facing Unbelted,
Rearward Seat Track, Handle Up



Graco Infant W/O Base With Belt,
Forward Seat Track, Handle Up



Graco Infant W/O Base With Belt, Middle Seat Track,
Handle Up



Graco Infant W/O Base With Belt, Rearward Seat Track,
Handle Up

DOT/NHTSA 208 Suppression Test – 2004 Mitsubishi Galant (C45603)

12 Month

Section B

Rear Facing CRS

E-11



Graco Infant W/O Base Unbelted, Forward Seat Track, Handle Up



Graco Infant W/O Base Unbelted, Middle Seat Track, Handle Up



Graco Infant W/O Base Unbelted, Rearward Seat Track, Handle Up



Graco Infant W/O Base Fwd Facing Unbelted, Forward Seat Track, Handle Up

DOT/NHTSA 208 Suppression Test – 2004 Mitsubishi Galant (C45603)

12 Month

Section B

Rear Facing CRS



Graco Infant W/O Base Fwd Facing Unbelted,
Middle Seat Track, Handle Up



Graco Infant W/O Base Fwd Facing Unbelted,
Rearward Seat Track, Handle Up



Unbelted 5th Percentile Female Reactivation,
Forward Seat Track

DOT/NHTSA 208 Suppression Test – 2004 Mitsubishi Galant (C45603)

12 Month

Section C

Forward Facing Convertible CRS



Britax Roundabout 161 Fwd Facing With Belt,
Forward Seat Track



Britax Roundabout 161 Fwd Facing With Belt,
Middle Seat Track



Britax Roundabout 161 Fwd Facing With Belt,
Rearward Seat Track



Britax Roundabout 161 Fwd Facing Unbelted,
Forward Seat Track

DOT/NHTSA 208 Suppression Test – 2004 Mitsubishi Galant (C45603)

12 Month

Section C

Forward Facing Convertible CRS



Britax Roundabout 161 Fwd Facing Unbelted,
Middle Seat Track



Britax Roundabout 161 Fwd Facing Unbelted,
Rearward Seat Track



Britax Roundabout 161 Rear Facing With Belt,
Forward Seat Track



Britax Roundabout 161 Rear Facing With Belt,
Middle Seat Track

DOT/NHTSA 208 Suppression Test – 2004 Mitsubishi Galant (C45603)

12 Month

Section C

Forward Facing Convertible CRS



Britax Roundabout 161 Rear Facing With Belt,
Rearward Seat Track



Britax Roundabout 161 Rear Facing Unbelted,
Forward Seat Track



Britax Roundabout 161 Rear Facing Unbelted,
Middle Seat Track



Britax Roundabout 161 Rear Facing Unbelted,
Rearward Seat Track

DOT/NHTSA 208 Suppression Test – 2004 Mitsubishi Galant (C45603)

12 Month

Section C

Forward Facing Convertible CRS



Unbelted 5th Percentile Female Reactivation,
Forward Seat Track

DOT/NHTSA 208 Suppression Test – 2004 Mitsubishi Galant (C45603)

12 Month

Section C

Forward Facing Convertible CRS



Century Encore Fwd Facing With Belt, Forward Seat Track



Century Encore Fwd Facing With Belt, Middle Seat Track



Century Encore Fwd Facing With Belt, Rearward Seat Track



Century Encore Fwd Facing Unbelted, Forward Seat Track

DOT/NHTSA 208 Suppression Test – 2004 Mitsubishi Galant (C45603)

12 Month

Section C

Forward Facing Convertible CRS



Century Encore Fwd Facing Unbelted, Middle Seat Track



Century Encore Fwd Facing Unbelted, Rearward Seat Track



Century Encore Rear Facing With Belt, Forward Seat Track



Century Encore Rear Facing With Belt, Middle Seat Track

DOT/NHTSA 208 Suppression Test – 2004 Mitsubishi Galant (C45603)

12 Month

Section C

Forward Facing Convertible CRS



Century Encore Rear Facing With Belt, Rearward Seat Track



Century Encore Rear Facing Unbelted, Forward Seat Track



Century Encore Rear Facing Unbelted, Middle Seat Track



Century Encore Rear Facing Unbelted, Rearward Seat Track

DOT/NHTSA 208 Suppression Test – 2004 Mitsubishi Galant (C45603)

12 Month

Section C

Forward Facing Convertible CRS



Unbelted 5th Percentile Female Reactivation,
Middle Seat Track

DOT/NHTSA 208 Suppression Test – 2004 Mitsubishi Galant (C45603)

12 Month

Section C

Forward Facing Convertible CRS



Evenflo Medallion 254 Fwd Facing With Belt,
Forward Seat Track



Evenflo Medallion 254 Fwd Facing With Belt,
Middle Seat Track



Evenflo Medallion 254 Fwd Facing With Belt,
Rearward Seat Track



Evenflo Medallion 254 Fwd Facing Unbelted,
Forward Seat Track

DOT/NHTSA 208 Suppression Test – 2004 Mitsubishi Galant (C45603)

12 Month

Section C

Forward Facing Convertible CRS



Evenflo Medallion 254 Fwd Facing Unbelted,
Middle Seat Track



Evenflo Medallion 254 Fwd Facing Unbelted,
Rearward Seat Track



Evenflo Medallion 254 Rear Facing With Belt,
Forward Seat Track



Evenflo Medallion 254 Rear Facing With Belt,
Middle Seat Track

DOT/NHTSA 208 Suppression Test – 2004 Mitsubishi Galant (C45603)

12 Month

Section C

Forward Facing Convertible CRS



Evenflo Medallion 254 Rear Facing With Belt,
Rearward Seat Track



Evenflo Medallion 254 Rear Facing Unbelted,
Forward Seat Track



Evenflo Medallion 254 Rear Facing Unbelted,
Middle Seat Track



Evenflo Medallion 254 Rear Facing Unbelted,
Rearward Seat Track

DOT/NHTSA 208 Suppression Test – 2004 Mitsubishi Galant (C45603)

12 Month

Section C

Forward Facing Convertible CRS



Unbelted 5th Percentile Female Reactivation,
Rearward Seat Track

DOT/NHTSA 208 Suppression Test – 2004 Mitsubishi Galant (C45603)

3 Year Old

Section C

Forward Facing Convertible CRS



3-Year-Old Fwd Facing Britax Roundabout Belted,
Forward Seat Track



3-Year-Old Fwd Facing Britax Roundabout Belted,
Middle Seat Track



3-Year-Old Fwd Facing Britax Roundabout Belted,
Rearward Seat Track



Unbelted 5th Percentile Female Reactivation,
Rearward Seat Track

DOT/NHTSA 208 Suppression Test – 2004 Mitsubishi Galant (C45603)

3 Year Old

Section C

Forward Facing Convertible CRS



3-Year-Old Fwd Facing Century Encore Belted,
Forward Seat Track



3-Year-Old Fwd Facing Century Encore Belted,
Middle Seat Track



3-Year-Old Fwd Facing Century Encore Belted,
Rearward Seat Track



Unbelted 5th Percentile Female Reactivation,
Middle Seat Track

DOT/NHTSA 208 Suppression Test – 2004 Mitsubishi Galant (C45603)

3 Year Old

Section C

Forward Facing Convertible CRS



3-Year-Old Fwd Facing Evenflo Medallion Belted,
Forward Seat Track



3-Year-Old Fwd Facing Evenflo Medallion Belted,
Middle Seat Track



3-Year-Old Fwd Facing Evenflo Medallion Belted,
Rearward Seat Track



Unbelted 5th Percentile Female Reactivation,
Forward Seat Track

DOT/NHTSA 208 Suppression Test – 2004 Mitsubishi Galant (C45603)

3 Year Old

Section D

Forward Facing Toddler

Belt Positioning Booster Seat

E-28



3-Year-Old Century Next Step Belted, Forward Seat Track



3-Year-Old Century Next Step Belted, Middle Seat Track



3-Year-Old Century Next Step Belted,
Rearward Seat Track



3-Year-Old Century Next Step Cinched With Harness,
Forward Seat Track

DOT/NHTSA 208 Suppression Test – 2004 Mitsubishi Galant (C45603)

3 Year Old

Section D

Forward Facing Toddler

Belt Positioning Booster Seat



3-Year-Old Century Next Step Cinched With Harness,
Middle Seat Track



3-Year-Old Century Next Step Cinched With Harness,
Rearward Seat Track



Unbelted 5th Percentile Female Reactivation,
Rearward Seat Track

DOT/NHTSA 208 Suppression Test – 2004 Mitsubishi Galant (C45603)

3 Year Old

Section D

Forward Facing Toddler

Belt Positioning Booster Seat

E-30



3-Year-Old Cosco High Back Booster Belted,
Forward Seat Track



3-Year-Old Cosco High Back Booster Belted,
Middle Seat Track



3-Year-Old Cosco High Back Booster Belted,
Rearward Seat Track



3-Year-Old Cosco High Back Booster Cinched With Harness,
Forward Seat Track

DOT/NHTSA 208 Suppression Test – 2004 Mitsubishi Galant (C45603)

3 Year Old

Section D

Forward Facing Toddler

Belt Positioning Booster Seat



3-Year-Old Cosco High Back Booster Cinched With Harness,
Middle Seat Track



3-Year-Old Cosco High Back Booster Cinched With Harness,
Rearward Seat Track



Unbelted 5th Percentile Female Reactivation,
Rearward Seat Track

DOT/NHTSA 208 Suppression Test – 2004 Mitsubishi Galant (C45603)
3 Year Old No CRS



3-Year-Old Unbelted, Forward Seat Track, Position 1



3-Year-Old Unbelted, Forward Seat Track, Position 2



3-Year-Old Unbelted, Forward Seat Track, Position 3



3-Year-Old Unbelted, Forward Seat Track, Position 4

DOT/NHTSA 208 Suppression Test – 2004 Mitsubishi Galant (C45603)
3 Year Old No CRS

E-33



3-Year-Old Unbelted, Forward Seat Track, Position 5



3-Year-Old Unbelted, Forward Seat Track, Position 6



3-Year-Old Unbelted, Forward Seat Track, Position 7



3-Year-Old Unbelted, Middle Seat Track, Position 1


DOT/NHTSA 208 Suppression Test – 2004 Mitsubishi Galant (C45603)

3 Year Old

No CRS



3-Year-Old Unbelted, Middle Seat Track, Position 2



3-Year-Old Unbelted, Middle Seat Track, Position 3



3-Year-Old Unbelted, Middle Seat Track, Position 4



3-Year-Old Unbelted, Middle Seat Track, Position 5

DOT/NHTSA 208 Suppression Test – 2004 Mitsubishi Galant (C45603)
3 Year Old No CRS

E-35



3-Year-Old Unbelted, Middle Seat Track, Position 6



3-Year-Old Unbelted, Middle Seat Track, Position 7



3-Year-Old Unbelted, Rearward Seat Track, Position 1



3-Year-Old Unbelted, Rearward Seat Track, Position 2

DOT/NHTSA 208 Suppression Test – 2004 Mitsubishi Galant (C45603)

3 Year Old

No CRS



3-Year-Old Unbelted, Rearward Seat Track, Position 3



3-Year-Old Unbelted, Rearward Seat Track, Position 4



3-Year-Old Unbelted, Rearward Seat Track, Position 5



3-Year-Old Unbelted, Rearward Seat Track, Position 6

DOT/NHTSA 208 Suppression Test – 2004 Mitsubishi Galant (C45603)
3 Year Old No CRS



3-Year-Old Unbelted, Rearward Seat Track, Position 7



Unbelted 5th Percentile Female Reactivation,
Rearward Seat Track

APPENDIX F
INSTRUMENTATION CALIBRATION

INSTRUMENTS FOR DRIVER DUMMY NO. 505

	SERIAL NO.	MANUFACTURER	CALIBRATION DATE
Head X	APYN0	Endevco	2/20/04
Head Y	ALFJ7	Endevco	2/20/04
Head Z	APYN3	Endevco	2/20/04
Neck Load Cell	1703	Denton	2/25/04
Chest X	AKAD6	Endevco	4/16/04
Chest Y	AM748	Endevco	4/16/04
Chest Z	AHTF1	Endevco	4/16/04
Chest Displacement	505	Servo	3/30/04
Left Femur Load Cell	1362	GSE	3/03/04
Right Femur Load Cell	1361	GSE	3/03/04

INSTRUMENTS FOR PASSENGER DUMMY NO. 506

	SERIAL NO.	MANUFACTURER	CALIBRATION DATE
Head X	J10866	Endevco	2/23/04
Head Y	J11548	Endevco	2/23/04
Head Z	AM749	Endevco	4/08/04
Neck Load Cell	606	Denton	3/24/04
Chest X	A12-A14	Entran	2/04/04
Chest Y	L17-Z13	Entran	2/04/04
Chest Z	L18-N01	Entran	2/04/04
Chest Displacement	506	Servo	2/24/04
Left Femur Load Cell	946	GSE	7/20/04
Right Femur Load Cell	945	GSE	7/20/04

INSTRUMENTS FOR DRIVER DUMMY NO. 505 (LOW RISK DEPLOYMENT P1)

	SERIAL NO.	MANUFACTURER	CALIBRATION DATE
Head X	APYN0	Endevco	2/20/04
Head Y	ALFJ7	Endevco	2/20/04
Head Z	APYN3	Endevco	2/20/04
Neck Load Cell	1713	Denton	2/28/04
Chest X	J12471	Endevco	1/14/04
Chest Y	AP179	Endevco	1/13/04
Chest Z	J12423	Endevco	1/14/04
Chest Displacement	505	Servo	3/30/04
Left Femur Load Cell	946	GSE	1/17/04
Right Femur Load Cell	945	GSE	1/17/04

INSTRUMENTS FOR DRIVER DUMMY NO. 506 (LOW RISK DEPLOYMENT P2)

	SERIAL NO.	MANUFACTURER	CALIBRATION DATE
Head X	J10866	Endevco	2/23/04
Head Y	J11548	Endevco	2/23/04
Head Z	AK972	Endevco	2/23/04
Neck Load Cell	1562	Denton	2/07/04
Chest X	A12-A14	Entran	2/04/04
Chest Y	L17-Z13	Entran	2/04/04
Chest Z	L18-N01	Entran	2/04/04
Chest Displacement	506	Servo	2/24/04
Left Femur Load Cell	86	GSE	6/08/04
Right Femur Load Cell	85	GSE	6/08/04

INSTRUMENTS FOR PASSENGER DUMMY NO. 153 (LOW RISK DEPLOYMENT P1 & P2)

	SERIAL NO.	MANUFACTURER	CALIBRATION DATE
Head X	AJ9Y3	Endevco	2/20/04
Head Y	AMT78	Endevco	2/20/04
Head Z	AP1Y8	Endevco	2/20/04
Neck Load Cell	1703	Denton	2/25/04
Chest X	AHY71	Entran	2/23/04
Chest Y	AP1Y1	Entran	2/23/04
Chest Z	ACC81	Entran	2/23/04
Chest Displacement	153	Servo	2/11/04

VEHICLE INSTRUMENTS

	SERIAL NO.	MANUFACTURER	CALIBRATION DATE
Left Rear Seat Crossmember X	A29-B06	Entran	3/11/04
Right Rear Seat Crossmember X	A29-B10	Entran	3/11/04
Top of Engine X	A29-J02	Entran	3/12/04
Bottom of Engine X	L17-D25	Entran	3/30/04
Left Brake Caliper X	A08-M02	Entran	3/09/04
Right Brake Caliper X	A08-M06	Entran	3/09/04
Instrument Panel X	A29-F09	Entran	3/11/04
Trunk Z	I25-F09	Entran	4/19/04